



# Front-Tiller

The Robust Front Harrow



# Front-Tiller

The HE-VA Front-Tiller is a 2-row front harrow for working depths of up to 300 mm. The Front-Tiller can be used together with a seeding combination or in stubble fields, whereby optimal utilization of the tractor is achieved.



There are two types of tines to choose from:

The automatic tine with spring release for 560 kg...



... or the double-twisted spring tine 40x40 mm.

Both types are equipped with 50x25mm reversible wear points.



The robust pivot depth wheels (10.0/80x12) ensure reliable depth control.

Adjustment is easily done using spindles.

## Extra Equipment

Warning Boards



LED Marking Lights



Edge Equipment



Revers. Wear Point 75x12



Revers. Wear Point 75x19



Tungsten Point



Goose Foot Point



Goose Foot P., Hardmetal




## Technical Specifications



3.00 - 4.00 m



1,090 - 1,695 kg



9 - 13 pcs.

| Working Width, m | Description                                             | Number of Tines | Weight, kg    |
|------------------|---------------------------------------------------------|-----------------|---------------|
| 3.00             | Front-Tiller with double coil springs or spring release | 9               | 1,090 / 1,405 |
| 4.00             | Front-Tiller with double coil springs or spring release | 13              | 1,240 / 1,695 |



Tel.: +45 97 72 42 88  
E-mail: [info@he-va.com](mailto:info@he-va.com)

Web: [www.he-va.com](http://www.he-va.com)

N.A. Christensensvej 34  
DK-7900 Nykøbing Mors

Your HE-VA dealer

HE-VA reserves the right to make design and construction changes without notice

