

EURO-DAN ECO



Euro-Dan Eco 8.00 m with Strong front-harrow, Spring-Board spring tine levelling bar and Spring-Board after-harrow.



Depth adjustment.

- Strong frame construction without clogging – 60 cm bar spacing.
- Wide 300 mm depth/transport wheels - ensure precise harrow depth.
- The harrow depth is easily adjusted by:
 - Distance clips on the lifting cylinder of the wheels and by spindles (5-6 m).
 - Central operated electric depth stop (7-8 m).
- Indicative max. harrow depth: 12 - 14 cm.
- If a strong front-harrow is mounted before the levelling bar, an extra good preparation can be made on heavy soil types (extra equipment):
 - The crust is broken, and tracks or compressed soil is loosened.
 - The levelling bar ensures a precise levelling of the loosened soil.
 - The four rows of harrow tines can harrow for precise seed depth followed by chosen retrofitted implement.
- Average row spacing is 6.7 cm when the harrow is equipped with a strong front-harrow (extra equipment) - the standard model is with a row spacing of 9.0 cm.
- Can be delivered with jackpot tines, no extra cost (inform of this when ordering).

MACHINES

Work Width, m	Type		Power Req., HP	No. of Tines	Weight, kg	Transport Height, m	Transport Width, m	Item Number
5.00	Standard harrow with hydraulic folding Wheels on side sections: adjustable via spindles	^{1*}	85+	55	2,100	2.05	2.90	3850100
6.00	Standard harrow with hydraulic folding Wheels on side sections: adjustable via spindles	^{1*}	100+	63	2,300	2.55	2.90	3860100
7.00	Standard harrow with hydraulic folding Wheels on side sections: with hydraulic lifting	^{1*}	120+	75	2,600	3.05	2.90	3870100
8.00	Standard harrow with hydraulic folding Wheels on side sections: with hydraulic lifting	^{1*}	140+	85	2,800	3.55	2.90	3878100

^{1*}Requires 2 double-acting oil outlets

STANDARD EQUIPMENT

- Wheels: 300x65/12 8 PLY.
- Mounted with 45x10 curved tines with reversible point.
- Hydraulic folding with automatic transport locking.
- Pivotal towing eye, secured by bolts, item no. 630757028.
- 7 and 8 m: central adjustment of the harrow depth with electric depth stop.

EXTRA EQUIPMENT

- Spare wheel attached on the harrow.
- Strong front-harrow for mounting before front levelling bar, the aggressiveness (tine row angle) is adjusted on spindles. As standard with 12x45 mm tines.
- Spring-Board spring tine levelling bar with hydraulic adjustable aggressiveness. Mounted with 45x10 mm tine with 100 mm wearing plate.
- Spring-Board after-harrow is connected to the front levelling bar, thus making the aggressiveness hydraulically adjustable. The relation between the front and rear bars can be adjusted on spindles. Mounted with 45x10 mm tine with 150 mm wearing plate, mounted leniently.
- The long finger after-harrow with Ø12 mm arched tines can also be mounted along with a Spring-board (with the long finger after-harrow placed at the back).

EXTRA EQUIPMENT

Work Width, m	Description	Weight, kg	Item Number
-	LED lights	15	3895100
5.00	Hydraulic lifting of wheels on the side sections and electric depth stop	-	3895030
5.00	Strong front-harrow in front of front Spring-Board levelling bar	260	3896500
5.00	Spring-Board w/wide wear points mounted in front of harrow tines	^{1*} 240	3897500
5.00	Spring-Board mounted after harrow tines	320	3895500
5.00	Long finger after-harrow	100	3850900
6.00	Hydraulic lifting of wheels on the side sections and electric depth stop	-	3895031
6.00	Strong front-harrow in front of front Spring-Board levelling bar	310	3896600
6.00	Spring-Board w/wide wear points mounted in front of harrow tines	^{1*} 290	3897600
6.00	Spring-Board mounted after harrow tines	380	3895600
6.00	Long finger after-harrow	120	3860900
7.00	Strong front-harrow in front of front Spring-Board levelling bar	365	3896700
7.00	Spring-Board w/wide wear points mounted in front of harrow tines	^{1*} 340	3897700
7.00	Spring-Board mounted after harrow tines	445	3895700
7.00	Long finger after-harrow	140	3870900
8.00	Strong front-harrow in front of front Spring-Board levelling bar	415	3896780
8.00	Spring-Board w/wide wear points mounted in front of harrow tines	^{1*} 390	3897780
8.00	Spring-Board mounted after harrow tines	510	3895800
8.00	Long finger after-harrow	160	3878900
-	3.00 m wheel track eradicator set, three-point mounted, 6 tines (65x12 mm)	200	67701-00
-	4.00 m wheel track eradicator set, three-point mounted, 8 tines (65x12 mm)	280	67702-00
-	Wheel track eradicator set, with 2x4 tines for harrows without a strong front-harrow	140	3895015
-	Wheel track eradicator tine for strong front-harrow, 2x4 longer and stronger tines	-	3895020
-	Spare wheel w/bracket	35	3895050
-	Goose foot point 100x4 mm for standard tine 45x10 mm (Additional price per m)	-	2896820
-	Harrow tine "Jackpot" (straight) 45x12 mm incl. point	5	0422171
-	Mechanical double change-over valve, mounted on the drawbar, for tractors missing 1 piece of double-acting oil outlet.	5	690207102

^{1*}Requires 1 double-acting oil outlet.

