

# VIP-ROLLER



- Compact construction of sectional tubes.
- Low transport height – stable and safe transport.
- Simple transfer between transport and working position.
- Hydraulic system released during transport/storage.
- 60 mm axles, special quality, and triple-sealed ball bearings.
- Transport width of max 2.45 m.

## MACHINES

Work Width, m	Ring Type	No. of Rings	No. of Spokes	Power Req., HP	Weight, kg	Item Number
3.30	510 mm/21" Cambridge 1*	63	3	40-60	1,500	63060-51
3.30	510 mm/21" Cambridge 1*	63	8	40-60	1,550	63060-46
3.30	560 mm/22.5" Cambridge 1*	63	9	40-60	1,830	63060-54
3.30	450/500 mm Star ring •/1*	60	-	40-60	1,520	63060-56
3.30	550 mm Cam ring 1*	22	-	40-60	1,090	63060-55
3.30	485-530 mm Crosskill 1*	33	-	40-60	1,430	63060-53
3.30	500 mm 2D-Corrugated 1*	41	8	40-60	1,470	63060-50
3.30	550 mm 2D-Corrugated 1*	41	9	40-60	1,730	63060-59
3.70	510 mm/21" Cambridge 1*	71	3	45-65	1,640	63061-51
3.70	510 mm/21" Cambridge 1*	71	8	45-65	1,660	63061-46
3.70	560 mm/22.5" Cambridge 1*	71	9	45-65	2,000	63061-54
3.70	450/500 mm Star ring •/1*	68	-	45-65	1,670	63061-56
3.70	550 mm Cam ring 1*	25	-	45-65	1,150	63061-55
3.70	485-530 mm Crosskill 1*	37	-	45-65	1,570	63061-53
3.70	500 mm 2D-Corrugated 1*	46	8	45-65	1,480	63061-50
3.70	550 mm 2D-Corrugated 1*	46	9	45-65	1,900	63061-59
4.10	510 mm/21" Cambridge 1*	79	3	50-70	1,870	63062-51
4.10	510 mm/21" Cambridge 1*	79	8	50-70	1,890	63062-46
4.10	560 mm/22.5" Cambridge 1*	79	9	50-70	2,260	63062-54
4.10	450/500 mm Star ring •/1*	76	-	50-70	1,890	63062-56
4.10	550 mm Cam ring 1*	28	-	50-70	1,330	63062-55
4.10	485-530 mm Crosskill 1*	41	-	50-70	1,780	63062-53
4.10	500 mm 2D-Corrugated 1*	51	8	50-70	1,830	63062-50
4.10	550 mm 2D-Corrugated 1*	51	9	50-70	2,160	63062-59
4.50	510 mm/21" Cambridge 1*	87	3	60-80	2,020	63063-51
4.50	510 mm/21" Cambridge 1*	87	8	60-80	2,190	63063-46
4.50	560 mm/22.5" Cambridge 1*	87	9	60-80	2,450	63063-54
4.50	450/500 mm Star ring •/1*	84	-	60-80	2,050	63063-56
4.50	550 mm Cam ring 1*	30	-	60-80	1,430	63063-55
4.50	485-530 mm Crosskill 1*	45	-	60-80	1,970	63063-53
4.50	500 mm 2D-Corrugated 1*	57	8	60-80	1,910	63063-50
4.50	550 mm 2D-Corrugated 1*	57	9	60-80	2,140	63063-59
5.40	510 mm/21" Cambridge 1*	105	3	70-90	2,560	63064-51
5.40	510 mm/21" Cambridge 1*	105	8	70-90	2,600	63064-46
5.40	560 mm/22.5" Cambridge 1*	105	9	70-90	3,020	63064-54
5.40	450/500 mm Star ring •/1*	98	-	70-90	2,520	63064-56
5.40	550 mm Cam ring 1*	36	-	70-90	1,790	63064-55
5.40	485-530 mm Crosskill 1*	54	-	70-90	2,500	63064-53
5.40	500 mm 2D-Corrugated 1*	69	8	70-90	2,340	63064-50
5.40	550 mm 2D-Corrugated 1*	69	9	70-90	2,880	63064-59

\*Requires 1 single-acting and 1 double-acting oil outlet.

• Steel cast ring, 8 year breakage warranty

## MACHINES (CONTINUED)

Work Width, m	Ring Type	No. of Rings	No. of Spokes	Power Req., HP	Weight, kg	Item Number
6.30	510 mm/21" Cambridge 1*	123	3	80-100	3,100	63065-51
6.30	510 mm/21" Cambridge 1*	123	8	80-100	3,260	63065-46
6.30	560 mm/22.5" Cambridge 1*	123	9	80-100	3,610	63065-54
6.30	450/500 mm Star ring •/1*	120	-	80-100	3,170	63065-56
6.30	550 mm Cam ring 1*	42	-	80-100	2,000	63065-55
6.30	485-530 mm Crosskill 1*	63	-	80-100	3,010	63065-53
6.30	500 mm 2D-Corrugated 1*	78	8	80-100	2,800	63065-50
6.30	550 mm 2D-Corrugated 1*	78	9	80-100	3,140	63065-59
7.30	510 mm/21" Cambridge 1*	143	3	100-120	3,440	63066-51
7.30	510 mm/21" Cambridge 1*	143	8	100-120	3,720	63066-46
7.30	560 mm/22.5" Cambridge 1*	143	9	100-120	4,190	63066-54
7.30	450/500 mm Star ring •/1*	140	-	100-120	3,590	63066-56
7.30	550 mm Cam ring 1*	43	-	85-105	2,450	63066-55
7.30	485-530 mm Crosskill 1*	73	-	100-120	3,300	63066-53
7.30	500 mm 2D-Corrugated 1*	90	8	90-110	3,380	63066-50
7.30	550 mm 2D-Corrugated 1*	90	9	90-110	3,750	63066-59
7.60	510 mm/21" Cambridge 1*	151	3	100-120	3,614	63165-51
7.60	510 mm/21" Cambridge 1*	151	8	100-120	3,874	63165-46
7.60	560 mm/22.5" Cambridge 1*	151	9	100-120	4,368	63165-54
7.60	450/500 mm Star ring •/1*	148	-	100-120	3,730	63165-56
7.60	550 mm Cam ring 1*	45	-	85-105	2,588	63165-55
7.60	485-530 mm Crosskill 1*	79	-	100-120	3,370	63165-53
7.60	500 mm 2D-Corrugated 1*	99	8	90-110	3,490	63165-50
7.60	550 mm 2D-Corrugated 1*	99	9	90-110	3,872	63165-59
8.20	510 mm/21" Cambridge 1*	161	3	120-140	3,670	63166-51
8.20	510 mm/21" Cambridge 1*	161	8	120-140	3,840	63166-46
8.20	450/500 mm Star ring •/1*	152	-	120-140	3,750	63166-56
8.20	550 mm Cam ring 1*	55	-	100-120	2,640	63166-55
8.20	485-530 mm Crosskill 1*	81	-	120-140	3,580	63166-53
8.20	500 mm 2D-Corrugated 1*	102	8	110-130	3,340	63166-50

\*Requires 1 single-acting and 1 double-acting oil outlet.

• Steel cast ring, 8 year breakage warranty

## STANDARD EQUIPMENT

- Adjustable jack stand.
- Towing eye, secured by bolts, item no. 630757028.
- Wheels:
  - 3.30 – 4.50 m. 10.0/80x12, 10 PLY.
  - 5.40 – 6.30 m. 10.0/75x15.3, 10 PLY.
  - 7.30 – 8.20 m. 11.5/80x15.3, 14 PLY.
- Triple-sealed ball bearings.
- Parking device for hydr. hoses.

## EXTRA EQUIPMENT

Description	Weight, kg	Item Number
EU-Type Approval (EU-S1a) 40 km/h (without brakes, but incl. LED lighting, reflectors, approved towing eye with chain, safety chain and COC document). For machines with axle weight below 3,499 kg.	-	69300-03
LED lights, complete with wire and socket, mounted	3	63060-01
Mechanical double change-over valve, mounted on drawbar, for tractors with only one double-acting oil outlet	5	690207102
Electrically operated double change-over valve, with contact to the cab, for tractors with too few double-acting oil outlets.	8	690207105
3.00 m wheel track eradicator set, three-point mounted, 6 tines (65x12 mm)	200	67701-00
4.00 m wheel track eradicator set, three-point mounted, 8 tines (65x12 mm)	280	67702-00
Stone box set (2 pieces) for 3.30 / 3.70 / 4.10 and 4.50 m	32	630555000
Stone box set (2 pieces) for 5.40 / 6.30 / 7.30 / 7.60 / 8.20 m	32	630555001
Air brakes, <b>factory-mounted</b>	18	63098-07
Hydraulic brakes, 1-circuit, <b>factory-mounted</b>	7	63098-08
Hydraulic brakes, 2-circuit, <b>factory-mounted</b>	-	63098-09
Wheels 400/60 x 15.5 – 16 PLY, only for Vip-Roller 7.30, 7.60 and 8.20 m (all ring types). NB: Transport width: 2.56 m. (Additional price per set)	50	63080-09
Wheel for 6.30 m. models 400/60 x 15.5 – 16 PLY, only <b>factory-mounted</b> (Additional price per set)	-	63080-13

The Spring-Board cannot be mounted on the Vip-Roller