

# WEEDER



- Free floating sections – optimum soil adaptation.
- Quick dismantling and mounting of tines without any tools.
- Adjustable tine aggressiveness in 5 different angles.
- Wide carrying wheels, height adjustable on spindles.
- The long flexible standard tine is suitable for row crops.
- Three-point linkage with cat. 2 pins and cat. 2 distance.

## MACHINES

Work Width, m	Description	No. of Tines/Points	No. of Sections	No. of Wheels	Height Folded, m	Power Req., HP	Lifting Req., kg	Weight, kg	Item Number
3.00	Complete Weeder with double tines	1* 60/120	2	2	1.10	30	750	309	4800001
4.50	Complete Weeder with hydr. folding and double tines	1* 90/180	3	2	2.00	40	825	550	4800000
6.00	Complete Weeder with hydr. folding and double tines	1*/3* 120/240	4	2	2.95	50	975	650	4801000
7.50	Complete Weeder with hydr. folding and double tines	1* 150/300	5	4	3.40	60	1,200	800	4802000
9.00	Complete Weeder with hydr. folding and double tines	1*/4* 180/360	6	4	3.70	70	1,650	1,000	4803001
9.00	LOW - Complete Weeder with hydr. folding and double tines	1* 180/360	6	4	3.35	70	1,650	1,180	4803000
12.00	Complete Weeder with hydr. folding and double tines	2* 240/480	8	4	3.35	90	2,250	1,500	4805000
15.00	Complete Weeder with hydr. folding and double tines	2* 300/600	10	6	4.25	110	2,850	1,900	4807000

<sup>1</sup>Requires 1 double-acting oil outlet.

<sup>3</sup>Height folded: 2.50 m with sections in transport position.

\*Transport width for all models is 3.00 m / Row Spacing: 2.50 cm 5 rows

<sup>2</sup>Requires 2 double-acting oil outlets.

<sup>4</sup>Height folded with levelling board: 4.35 m

## STANDARD EQUIPMENT

- Weeder sections with 7 x 600 mm double tines mounted with pins.
- Weeder sections with 7 x 450 mm double tines are available without additional price. To be ordered corresponding to number of sections.
- Carrying wheel:
  - 3.00 - 6.00 m: 2 pcs. 16x6.5x8 – 6 PLY.
  - 7.50 m: 4 pcs. 16x6.5x8 – 6 PLY.
  - 9.00 – 12.00 m: 2 pcs. 16x6.5x8 – 6 PLY. and 2 pcs. 18.5x8.5x8 – 6 PLY.
  - 15.00 m: 2 pcs. 20x8.00-10 and 4 pcs. 18.5x8.5x8 - 6 PLY.
- Support stand, pins and locking pins.

## EXTRA EQUIPMENT



Hydraulically adjustable tine pressure.



Levelling bar.



Levelling plate.

Work Width, m	Description	Weight, kg	Item Number
3.00 - 6.00 + 9.00	LED lights with wire and socket incl. holder - Rear mounted	-	4895100
7.50 + 12.00 - 15.00	LED lights with wire and socket incl. holder - Rear mounted	15	4895150
12.00 - 15.00	LED lights w/wire and socket for models with Multi-Seeder incl. holder - Rear mounted	-	4895200
3.00 - 7.50	LED marking lights incl. holder - Front mounted	12	4895050
3.00 - 7.50	LED marking lights and set of reflective warning boards incl. holder - Front mounted	-	4895425
3.00 - 7.50	Set of reflective warning boards incl. holder - Front mounted	-	4895400
3.00 - 15.00	Set of reflective warning boards incl. holder - Rear mounted	-	4895375
-	7 x 450 mm double tines, when replacing 7 x 600 mm tines. Order by number of sections	1	4899015
3.00	Hydraulically adjustable tine pressure	1*	20
4.50	Hydraulically adjustable tine pressure	1*	30
6.00	Hydraulically adjustable tine pressure	1*	40
7.50	Hydraulically adjustable tine pressure	1*	50
9.00	Hydraulically adjustable tine pressure	1*	60
12.00	Hydraulically adjustable tine pressure	1*	80
15.00	Hydraulically adjustable tine pressure	1*	100
3.00	Levelling bar for levelling of molehills, cow pats etc. ( <b>Only factory-mounted</b> )	-	4896025
6.00	Levelling bar for levelling of molehills, cow pats etc. ( <b>Only factory-mounted</b> )	200	4896000
7.50	Levelling bar for levelling of molehills, cow pats etc. ( <b>Only factory-mounted</b> )	-	4896050
9.00	Levelling bar for levelling of molehills, cow pats etc. ( <b>Only factory-mounted</b> )	300	4896100
-	Levelling plate (600 mm tines) suitable for molehills and livestock manure (Per section)	11	4899002
-	Levelling plate (450 mm tines) suitable for molehills and livestock manure (Per section)	11	4899003
6.00	Extra wheel set, 2 pcs. 16x6.5x8 - 6 PLY	2*	40
12.00	Extra wheel set, 2 pcs. 18.5 x 8.5 x8 - 6 PLY	60	4893050
-	18.5x8.5x8-6 PLY instead of 16x6.5x8-6 PLY (Additional price per set)	50	4893100
-	Rear mounted wheel set - 18.5x8.5x8-6 PLY	240	4892800
-	Mounting set for Universal-Spreader, incl. mounting on new Weeder. Prices and info on Universal-Spreader	-	4894070
3.00 - 7.50	Front mounting of Weeder models. Double three-point linkage for front and rear mounting (Additional price)	68	4894200
-	Expansion kit - 2 x 25 cm	30	4894350
-	Fixation brackets (Per section)	-	4894300

<sup>1\*</sup>The equipment requires 1 additional double-acting oil outlet.

<sup>2\*</sup>When retrofitting levelling bar on 6.00 m model, the wheel set, item no. 4893050 must be ordered.

### MOUNTING SET FOR MULTI-SEEDER INCL. STEPS, INCL. MOUNTING ON NEW WEEDER - MAX. 300 KG LOAD IN FINE SEED HOPPER.

Work Width, m	Description	Weight, kg	Item Number
3.00	Mounting set for Multi-Seeder	45	4894060
4.50	Mounting set for Multi-Seeder	45	4894061
6.00	Mounting set for Multi-Seeder	45	4894062
7.50	Mounting set for Multi-Seeder	45	4894065
9.00	Mounting set for Multi-Seeder	95	4894066
9.00 LOW - 12.00	Mounting set for Multi-Seeder	120	4894067
15.00	Mounting set for Multi-Seeder	120	4894068
-	Hydraulic lifting of seed wheel on Multi-Seeder	1*	-
			4893200

<sup>1\*</sup>The equipment requires 1 additional double-acting oil outlet.



Wheel set, rear.