FRONT-TILLER





- 2 rows of harrow sections with good clearance.
- Up to 300 mm working depth.
- 2 types of tines:
  - Tines with double-stranded springs 40x40 mm, 0-30 cm working depth.
  - Automatic with spring release for 560 kg, 0-30 cm working depth.
- Compact machine.
- Oblong hole for top link.
- Spindle adjustable strong depth wheels.
- Three-point linkage with cat. 2 pins and cat. 2 distance.

MACHINES

Work Width, m	Description	Weight, kg	Item Number
3.00	9 tines, double-stranded springs	1,081	67510-15
3.00	9 tines, with spring release	1,405	67510-05
4.00	13 tines, double-stranded springs	1,227	67510-20
4.00	13 tines, with spring release	1,695	67510-10

STANDARD EQUIPMENT

- Pivotal depth wheels, 2 pieces 300/55x12 – 8 PLY.
- 50x25 mm reversible wearing point.
- Pins and locking pins.

EXTRA EQUIPMENT

Description	Weight, kg	Item Number
LED marking lights with clear and red glass	4	67510-50
Set of reflective warning boards (2 pieces)	8	67055-74
Edge equipment set w/adjustable discs	60	67510-55
75 x 12 mm reversible and high adjustable wearing point. (Additional price per tine)	4	67510-60
75 x 19 mm reversible and high adjustable wearing point. (Additional price per tine)	-	67510-61
Tip with tungsten with straight mould board (Additional price per tine)	-	67510-65
Goose foot tip with straight mould board (Additional price per tine)	-	67510-63
Goose-foot tip with hardmetal with straight mould board (Additional price per tine)	-	67510-64