LIFT-ROLLER



3.00 m with 510 mm/21" Cambridge.



- Drawbar, free movable up/down.
- 60 mm bearings and shafts, special quality.
- Small lifting requirement – close to the tractor.
- Three-point mounting for cat. 2.

MACHINES

Work Width, m	Ring Type		No. of Rings	No. of Spokes	Power Req., HP	Lifting Req., kg	Weight, kg	Item Number
2.60	510 mm/21" Cambridge		45	3	40	1,400	930	63073-51
2.60	510 mm/21" Cambridge		45	8	40	1,400	1,101	63073-46
2.60	560 mm/22.5" Cambridge		45	9	45	1,630	1,160	63073-54
2.60	620 mm/24" Cambridge		45	10	45	1,880	1,250	63073-62
2.60	450/500 mm Star ring	•	42	-	45	1,470	980	63073-56
2.60	550/600 mm Star ring	•	42	-	45	1,850	1,230	63073-57
2.60	550 mm Cam ring		16	-	30	1,020	680	63073-55
2.60	485/530 mm Crosskill		25	-	40	1,100	730	63073-53
2.60	550/600 mm Crosskill		25	-	40	1,570	1,050	63073-63
2.60	500 mm 2D-Corrugated		31	8	40	1,250	830	63073-50
2.60	550 mm 2D-Corrugated		31	9	40	1,290	860	63073-59
2.60	600 mm 2D-Corrugated		31	10	45	1,320	880	63073-60
3.00	510 mm/21" Cambridge		53	3	55	1,590	1,060	63074-51
3.00	510 mm/21" Cambridge		53	8	55	1,590	1,261	63074-46
3.00	560 mm/22.5" Cambridge		53	9	60	1,910	1,320	63074-54
3.00	620 mm/24" Cambridge		53	10	60	2,150	1,430	63074-62
3.00	450/500 mm Star ring	•	50	-	60	1,670	1,110	63074-56
3.00	550/600 mm Star ring	•	50	-	60	2,100	1,400	63074-57
3.00	550 mm Cam ring		19	-	40	1,220	820	63074-55
3.00	485/530 mm Crosskill		27	-	55	1,250	830	63074-53
3.00	550/600 mm Crosskill		27	-	55	1,760	1,170	63074-63
3.00	500 mm 2D-Corrugated		35	8	55	1,380	920	63074-50
3.00	550 mm 2D-Corrugated		35	9	55	1,440	960	63074-59
3.00	600 mm 2D-Corrugated		35	10	60	1,480	990	63074-60

• Steel cast ring, 8 year breakage warranty

STANDARD EQUIPMENT

- Support stand, pins and locking pins.

EXTRA EQUIPMENT



Description	Weight, kg	Item Number
LED lights, complete with wire and socket, mounted	4	63003-01
Set of reflective warning boards (2 pieces)	8	67055-74
Stone box set (2 pieces)	32	630555005

GRASS-SEEDER KIT EXCL. MULTI-SEEDER

Work Width, m	Description	Item Number
2.60	230 mm adjustable plain roller behind the implement, adjustable longfinger harrow in front and mounting set for Multi-Seeder	63073-20
3.00	230 mm adjustable plain roller behind the implement, adjustable longfinger harrow in front and mounting set for Multi-Seeder	63074-20