COMBI-FLEX





- Optimal design for deep loosening in combination with a rear-mounted implement – e.g., a seed drill.
- The machine is particularly advantageous for soil cultivation in non-ploughing systems.
- Discs and tines can be adjusted independently of the attached implement.
- Max. weight of mounted machine after Combi-Flex: 4 t.
- Good clearance with 420 mm tine staggering.
- Max. working depth: 400 mm.
- Length coupling to coupling point (centre): 2.180 mm
- Three-point linkage with cat. 3 pins and cat. 3 distance.
- Lift with cat. 3 snap-couplings and cat. 3 distance (1,010 mm middle - middle).

MACHINES

Work Width, m	Type	Support Wheels	Stone Protection	Number of Tines	Power Req., HP	Weight, kg	Item Number
3.00	Rigid	No	Shear Bolt	6	150	2,055	64546-01
3.00	Rigid	No	Hydr. auto.	6	150	2,175	64546-02
4.00	Rigid	No	Shear Bolt	8	200	2,405	64546-03
4.00	Rigid	No	Hydr. auto.	8	200	2,525	64546-04
4.00	Foldable	No	Shear Bolt	8	200	2,505	64546-05
4.00	Foldable	No	Hydr. auto.	8	200	2,625	64546-06
5.00	Foldable	Yes	Shear Bolt	10	250	3,440	64546-07
5.00	Foldable	Yes	Hydr. auto.	10	250	3,640	64546-08
6.00	Foldable	Yes	Shear Bolt	8	200	3,423	64546-09
6.00	Foldable	Yes	Hydr. auto.	8	200	3,618	64546-10
6.00	Foldable	Yes	Shear Bolt	12	300	3,795	64546-11
6.00	Foldable	Yes	Hydr. auto.	12	300	3,990	64546-12

STANDARD EQUIPMENT

- Hydraulic lifting of the subsoiler tines
- Ø470 mm discs in front of the tines.
- 3 sets of hydraulic connections conveniently positioned for the following implement.
- Electrical socket for lighting connection.
- Support wheels for 5.00 m and 6.00 m (Attention: Twin wheels on tractor may cause issues)

EXTRA EQUIPMENT

Description	Item Number
Linkage with cat. 3 snap-couplings and cat. 3 distance (1010 mm middle - middle) Rigid models. (Additional price)	64519-35
Lift with cat. 3 snap-couplings and cat. 2 distance (870 mm middle - middle) Only for foldable models.	64519-36
Ball hitch	64546-20
Fork hitch	64546-21
Point with 120 mm wing shares (Price reduction per tine)	645000043A
Points 120 mm with hard metal plate. (Additional price per tine)	645000043TA
Point with 350 mm wing shares (Additional price per tine)	645000063A
Points 200 mm with hard metal plate (Additional price per tine)	645000044TA
Points with 120 mm wing shares, Longlife, with hard metal (Additional price per tine)	645000043HDA
Points with 200 mm wing shares, Longlife, with hard metal (Additional price per tine)	645000044HDA
Points with 350 mm wing shares, Longlife, with hard metal (Additional price per tine)	645000063HDA
Easy-Draft kit. 15 mm tine w/120 mm wear point w/hard metal plate. Max working depth: 300 mm. Quick-Push stone protection (Additional price per tine)	64512-06
Easy-Draft kit. 15 mm tine w/120 mm wear point w/hard metal plate. Max working depth: 300 mm. Quick-Push stone protection (Retrofitting per tine)	64512-05
Easy-Draft kit. 15 mm tine w/120 mm wear point w/hard metal plate. Max working depth: 300 mm. Hydraulic auto release (Additional price per tine)	64512-16
Easy-Draft kit. 15 mm tine w/120 mm wear point w/hard metal plate. Max working depth: 300 mm. Hydraulic auto release (Retrofitting per tine)	64512-15
120 mm wear point for Easy-Draft, with hard metal plate in center + wings (Additional price per tine)	645000056TA
200 mm wear point for Easy-Draft, with hard metal plate in center (Additional price per tine)	645000054A
200 mm wear point for Easy-Draft, with hard metal plate in center + wings (Additional price per tine)	645000054TA
120 mm welded wear point for Easy-Draft (Additional price per tine)	645000056SA
Tine reinforcement, hard metal 60x25x15 mm incl. factory fitting on new tine. Recommended when tilling > 350 mm. Omittable for item numbers 645000044T / 645000043T. (Additional price per tine)	645000085
Tine reinforcement, hard metal 60x15x15 mm incl. factory-mounting on new tine. Only applied for Easy-Draft (Additional price per tine)	645000083