SUB-TILLER ECO



3.00 m with hydraulic auto-release system, 4 tines, V-Profile Roller and hydr. depth control.







3.00 m. with hydraulic auto-release system and 4 tines.

- Tine height under the frame 820 mm.
- Max. working depth 600 mm.
- Good clearance with a frame height of 820 mm.
- Strong frame construction, 180x180x8 mm sectional tubes.
- 2 stone protection types: Quick-Push or Hydraulic automatic.
- Infinitely variable tine spacing, depending on the models and number of tines.
- Three-point linkage with cat. 3 pins and cat. 2 distance.

- For machines with roller:
- Hydr. depth control for Square Tube Roller and V-Profile Roller. (Requires one double-acting oil outlet).

MACHINES

					
				Without Roller	Square Tube Roller Ø550 mm	V-Profile Roller Ø600 mm
Work Width, m	Stone Protection	No. of Tines	Standard Row Spacing, cm	Item Number	Item Number	Item Number
2.50	Quick-Push	2	180	64541-01	64542-01	64543-01
2.50	Quick-Push	3	90	64541-02	64542-02	64543-02
2.50	Hydr. auto.	2	180	64541-06	64542-06	64543-06
2.50	Hydr. auto.	3	90	64541-07	64542-07	64543-07
3.00	Quick-Push	2	200	64541-11	64542-11	64543-11
3.00	Quick-Push	3	100	64541-12	64542-12	64543-12
3.00	Quick-Push	4	75	64541-13	64542-13	64543-13
3.00	Hydr. auto.	2	200	64541-16	64542-16	64543-16
3.00	Hydr. auto.	3	100	64541-17	64542-17	64543-17
3.00	Hydr. auto.	4	75	64541-18	64542-18	64543-18
3.50	Quick-Push	5	70	64541-20	64542-20	64543-20
3.50	Hydr. auto.	5	70	64541-26	64542-26	64543-26

							
						Without Roller	Square Tube Roller Ø550 mm	V-Profile Roller Ø600 mm
Work Width, m	Stone Protection	No. of Tines	Total Tine Spacing between Outer Tines, cm	Power Req., HP	Max HP	Weight, kg		
2.50	Quick-Push	2	195	60-100	250	500	860	1,375
2.50	Quick-Push	3	195	90-120	250	580	940	1,445
2.50	Hydr. auto.	2	195	60-100	250	540	900	1,405
2.50	Hydr. auto.	3	195	90-120	250	630	990	1,495
3.00	Quick-Push	2	245	60-100	250	520	930	1,550
3.00	Quick-Push	3	245	90-120	250	600	1,010	1,630
3.00	Quick-Push	4	245	110-160	250	680	1,090	1,710
3.00	Hydr. auto.	2	245	60-100	250	580	990	1,610
3.00	Hydr. auto.	3	245	90-120	250	690	1,100	1,720
3.00	Hydr. auto.	4	245	110-160	250	810	1,220	1,840
3.50	Quick-Push	5	295	130-200	300	780	1,260	1,980
3.50	Hydr. auto.	5	295	130-200	300	900	1,380	2,100

*All models require 1 double-acting oil outlet

IMPORTANT: If a change of stated row spacing is wanted, please inform when placing an order.

STANDARD EQUIPMENT

- Hydr. depth control incl. depth scale for Square Tube Roller and V-Profile Roller.
- Supporting leg on machines witout roller.
- For Quick-push stone protection: 8 steps per bolt.
- Scraper between the V-Profile rings.
- Points with 200 mm wing shares, mounted on 25 mm wide tine.

EXTRA EQUIPMENT

Description	Weight, kg	Item Number
LED lights complete w/wire and socket	8	64509-01
Set of reflective warning boards (2 pieces)	8	67055-74
Check valve (pilot-controlled) for hydr. depth control	-	64543-85
Cat.II pins for three-point mounting	-	64509-08
Cat. 3 for three-point mounting (1010 mm middle - middle) (Additional price)	-	64545-30
Points with 120 mm wing shares (Price reduction per tine)	-	645000043A
Points 120 mm with hard metal plate (Additional price per tine)	-	645000043TA
Points with 350 mm wing shares (Additional price per tine)	-	645000063A
Points 200 mm with hard metal plate (Additional price per tine)	16	645000044TA
Points with 120 mm wing shares, Longlife, with hard metal (Additional price per tine)	-	645000043HDA
Points with 200 mm wing shares, Longlife, with hard metal (Additional price per tine)	19	645000044HDA
Points with 350 mm wing shares, Longlife, with hard metal (Additional price per tine)	-	645000063HDA
Easy-Draft kit. 15 mm tine w/120 mm wear point w/hard metal plate. Max working depth: 300 mm. Quick-Push stone protection (Additional price per tine)	90	64509-12
Easy-Draft kit. 15 mm tine w/120 mm wear point w/hard metal plate. Max working depth: 300 mm. Hydraulic auto release (Additional price per tine)	125	64509-09
Tine for retrofitting complete, Quick-Push stone protection	85	64543-98
Tine for retrofitting complete, Hydr. stone protection	121	64543-99
Tine reinforcement, hard metal 60x25x15 mm incl. factory fitting on new tine. Recommended when tilling > 350 mm. Omittable for item numbers 645000044T / 645000043T. (Additional price per tine)	-	645000085
Tine reinforcement, hard metal 60x15x15 mm incl. factory-mounting on new tine. Only applied for Easy-Draft (Additional price per tine)	-	645000083
Return circuit from release system. Recommended for difficult, rocky, extreme conditions. (Price per tine)	-	64509-54
Torpedo-drain kit, for tine with Quick-Push. **Factory-mounted**. (Additional price per tine)	-	64508-95
Torpedo drain kit, for tine with hydraulic automatic release. **Factory-mounted**. (Additional price per tine)	-	64508-96