SUB-TILLER COMBI





- Intended as front tool / tool carrier for maize seed drills.
- Loosens the soil down to 40 cm depth in front of each crop row.
- Net weight of approx. 10 tons ensures extremely stabile depth control.
- Various possibilities for the composition of the machine.
- Possible to mount fertilizer equipment on sub soiler.
- V-Profile Roller, Ø700 mm with scraper between the rings.
- Lift with cat. 3 snap-couplings and cat. 3 distance (1,010 mm middle - middle).

MACHINES

Work Width, m	Stone Protection	No. of Tines	Row Spacing	Item Number
6.00	Quick-Push	8	75	64535-00
6.00	Hydr. auto.	8	75	64535-01
6.00	Quick-Push	12	45	64535-02
6.00	Hydr. auto.	12	45	64535-03

For machines in special working widths, contact HE-VA.

STANDARD EQUIPMENT

- Standard fitted with 4-ton double-acting lift at the rear.
- Wheels: 710/40 R22.5. .
- Hydr. support wheel 300x65/12 8 PLY, in front.
- Ball joint towing eye, cat. 4 / Ø51 mm, item no.. 7420082 .
- Hydr. depth control via the roller and support wheel.
- For Quick-push stone protection: 8 steps per bolt.
- Points with 200 mm wing shares, mounted on 25 mm wide tine.
- Incl. 3 x double acting oil socket and extension cable t / light. 2 sets 1/4 and 1 set 3/8.

EXTRA EQUIPMENT

Description	Weight, kg	Item Number
LED lights cpl. with wire and socket, mounted	3	64500-05
Points with 120 mm wing shares (Price reduction per tine)	-	645000043A
Points 120 mm with hard metal plate (Additional price per tine)	-	645000043TA
Points with 350 mm wing shares (Additional price per tine)	-	645000063A
Points 200 mm with hard metal plate (Additional price per tine)	16	645000044TA
Points with 120 mm wing shares, Longlife, with hard metal (Additional price per tine)	-	645000043HDA
Points with 200 mm wing shares, Longlife, with hard metal (Additional price per tine)	19	645000044HDA
Points with 350 mm wing shares, Longlife, with hard metal (Additional price per tine)	-	645000063HDA
Easy-Draft kit. 15 mm tine w/120 mm wear point w/hard metal plate. Max working depth: 300 mm. Quick-Push stone protection (Additional price per tine)	90	64509-12
Easy-Draft kit. 15 mm tine w/120 mm wear point w/hard metal plate. Max working depth: 300 mm. Quick-Push stone protection (Retrofitting per tine)	90	64509-16
Easy-Draft kit. 15 mm tine w/120 mm wear point w/hard metal plate. Max working depth: 300 mm. Hydraulic auto release (Additional price per tine)	125	64509-09
Easy-Draft kit. 15 mm tine w/120 mm wear point w/hard metal plate. Max working depth: 300 mm. Hydraulic auto release (Retrofitting per tine)	125	64509-17
120 mm wear point for Easy-Draft, with hard metal plate in center + wings (Additional price per tine)	-	645000056TA
200 mm wear point for Easy-Draft, with hard metal plate in center (Additional price per tine)	-	645000054A
200 mm wear point for Easy-Draft, with hard metal plate in center + wings (Additional price per tine)	-	645000054TA
120 mm welded wear point for Easy-Draft (Additional price per tine)	-	645000056SA
Air brakes, **factory-mounted**	18	64509-34
Hydraulic brakes, 1-circuit, **factory-mounted**	7	64509-33
Hydraulic brakes, 2-circuit, **factory-mounted**	-	64509-39
Discs for 6.00 m. (8 tines) - with Ø470 mm discs in front of tine, turnable and protected from stones via rubber suspension, maintenance free bearings (not for retrofitting)	-	64539-00
Discs for 6.00 m. (12 tines) - with Ø470 mm discs in front of tine, turnable and protected from stones via rubber suspension, maintenance free bearings (not for retrofitting)	-	64539-01
One extra set of double-acting hydraulic hoses 3/8", with female quick-acting coupling.	-	64539-20
A set of air brake outlets	-	64539-21