# DISC-ROLLER CONTOUR (THREE-POINT MOUNTED)







- HE-VA SAT-System on models with 2 and 3 sections.
- Sabre disc" 510 x 4 mm large scalloped disc with specially designed coulter profile – thus ensuring an improved cutting of surface stubble preparation.
- Maintenance-free disc-hubs.
- Working depth of up to 125 mm in minimal tillage cultivations.
- "DSD - Technology": Depth Synchronized Disc-Aggressiveness.
- Three-point linkage with cat. 3 pins and cat. 2 distance.

## MACHINES

| Model, m | Work / Transport Width, m | Roller Type | No. of Rings | No. of Discs | Power Req., HP | Weight, kg | Item Number |
|---|---|---|---|---|---|---|---|
| **1-SECTION RIGID MODELS WITHOUT HYDRAULIC FOLDING** | | | | | | | |
| **2.50** | 2.25 / 2.50 | Square Tube Roller / 550 mm [1*] | - | 18 | 80 + | 1,300 | 63090-47 |
| **2.50** | 2.25 / 2.50 | Wave roller / 600 mm [1*] | 16 | 18 | 80 + | 1,600 | 63090-83 |
| **2.50** | 2.25 / 2.50 | U-Profile Roller / 600 mm [1*] | 16 | 18 | 90 + | - | 63090-84 |
| **2.50** | 2.25 / 2.50 | V-Profile Roller / 600 mm [1*] | 16 | 18 | 90 + | 1,820 | 63090-86 |
| **2.50** | 2.25 / 2.50 | V-Profile Roller / 700 mm [1*] | 16 | 18 | 90 + | - | 63090-85 |
| **2.50** | 2.25 / 2.50 | Twin U-Profile 600-600 mm [1*] | 16 | 18 | 90 + | - | 63090-88 |
| **2.50** | 2.25 / 2.50 | Twin V-Profile 600-600 mm [1*] | 16 | 18 | 90 + | - | 63090-87 |
| **3.00** | 2.75 / 3.00 | Square Tube Roller / 550 mm [1*] | - | 22 | 90 + | 1,500 | 63094-47 |
| **3.00** | 2.75 / 3.00 | Wave roller / 600 mm [1*] | 20 | 22 | 90 + | 1,850 | 63094-83 |
| **3.00** | 2.75 / 3.00 | U-Profile Roller / 600 mm [1*] | 20 | 22 | 100 + | - | 63094-84 |
| **3.00** | 2.75 / 3.00 | V-Profile Roller / 600 mm [1*] | 20 | 22 | 100 + | 2,120 | 63094-86 |
| **3.00** | 2.75 / 3.00 | V-Profile Roller / 700 mm [1*] | 20 | 22 | 100 + | - | 63094-85 |
| **3.00** | 2.75 / 3.00 | Twin U-Profile 600-600 mm [1*] | 20 | 22 | 100 + | - | 63094-88 |
| **3.00** | 2.75 / 3.00 | Twin V-Profile 600-600 mm [1*] | 20 | 22 | 100 + | - | 63094-87 |
| **3.50** | 3.25 / 3.50 | Square Tube Roller / 550 mm [1*] | - | 26 | 100 + | 1,710 | 63095-47 |
| **3.50** | 3.25 / 3.50 | Wave roller / 600 mm [1*] | 23 | 26 | 100 + | 2,165 | 63095-83 |
| **3.50** | 3.25 / 3.50 | U-Profile Roller / 600 mm [1*] | 23 | 26 | 110 + | - | 63095-84 |
| **3.50** | 3.25 / 3.50 | V-Profile Roller / 600 mm [1*] | 23 | 26 | 110 + | 2,435 | 63095-86 |
| **3.50** | 3.25 / 3.50 | V-Profile Roller / 700 mm [1*] | 23 | 26 | 110 + | - | 63095-85 |
| **3.50** | 3.25 / 3.50 | Twin U-Profile 600-600 mm [1*] | 23 | 26 | 110 + | - | 63095-88 |
| **3.50** | 3.25 / 3.50 | Twin V-Profile 600-600 mm [1*] | 23 | 26 | 110 + | - | 63095-87 |
| **4.00** | 3.75 / 4.00 | Square Tube Roller / 550 mm [1*] | - | 30 | 110 + | 1,920 | 63096-47 |
| **4.00** | 3.75 / 4.00 | Wave roller / 600 mm [1*] | 26 | 30 | 110 + | 2,480 | 63096-83 |
| **4.00** | 3.75 / 4.00 | U-Profile Roller / 600 mm [1*] | 26 | 30 | 120 + | - | 63096-84 |
| **4.00** | 3.75 / 4.00 | V-Profile Roller / 600 mm [1*] | 26 | 30 | 120 + | 2,750 | 63096-86 |
| **4.00** | 3.75 / 4.00 | V-Profile Roller / 700 mm [1*] | 26 | 30 | 120 + | - | 63096-85 |
| **4.00** | 3.75 / 4.00 | Twin U-Profile 600-600 mm [1*] | 26 | 30 | 120 + | - | 63096-88 |
| **4.00** | 3.75 / 4.00 | Twin V-Profile 600-600 mm [1*] | 26 | 30 | 120 + | - | 63096-87 |
| **2-SECTION MODELS WITH HYDRAULIC FOLDING** | | | | | | | |
| **4.50** | 4.25 / 2.32 | Square Tube Roller / 550 mm [2*] | - | 34 | 130 + | - | 63097-47 |
| **4.50** | 4.25 / 2.32 | Wave roller / 600 mm [2*] | 30 | 34 | 140 + | - | 63097-83 |
| **4.50** | 4.25 / 2.32 | U-Profile Roller / 600 mm [2*] | 30 | 34 | 140 + | - | 63097-84 |
| **4.50** | 4.25 / 2.32 | V-Profile Roller / 600 mm [2*] | 30 | 34 | 140 + | - | 63097-86 |
| **4.50** | 4.25 / 2.32 | V-Profile Roller / 700 mm [2*] | 30 | 34 | 140 + | - | 63097-85 |
| **5.50** | 5.25 / 2.32 | Square Tube Roller / 550 mm [2*] | - | 42 | 160 + | - | 63098-47 |
| **5.50** | 5.25 / 2.32 | Wave roller / 600 mm [2*] | 36 | 42 | 170 + | - | 63098-83 |
| **5.50** | 5.25 / 2.32 | U-Profile Roller / 600 mm [2*] | 36 | 42 | 170 + | - | 63098-84 |
| **5.50** | 5.25 / 2.32 | V-Profile Roller / 600 mm [2*] | 36 | 42 | 170 + | - | 63098-86 |
| **5.50** | 5.25 / 2.32 | V-Profile Roller / 700 mm [2*] | 36 | 42 | 170 + | - | 63098-85 |
| **6.50** | 6.25 / 2.32 | Square Tube Roller / 550 mm [2*] | - | 50 | 190 + | 4,010 | 63099-47 |
| **6.50** | 6.25 / 2.32 | Wave roller / 600 mm [2*] | 42 | 50 | 200 + | - | 63099-83 |
| **6.50** | 6.25 / 2.32 | U-Profile Roller / 600 mm [2*] | 42 | 50 | 200 + | - | 63099-84 |
| **6.50** | 6.25 / 2.32 | V-Profile Roller / 600 mm [2*] | 42 | 50 | 200 + | - | 63099-86 |
| **6.50** | 6.25 / 2.32 | V-Profile Roller / 700 mm [2*] | 42 | 50 | 200 + | - | 63099-85 |

*[1*]Requires 1 double-acting oil outlet.*

*[2*]Requires 2 double-acting oil outlets.*

# STANDARD EQUIPMENT

- HE-VA SAT-System on models with 2- and 3-sections: hydr. adjustable weight transfer system, ensuring equal weight transfer in the total working width.
- Hydr. adjustment of the working depth, at the same time used for lifting of “disc” on headland.
- Adjustable drawbar height with distance clips and parking device for hydraulic hoses.
- Adjustable edge disc for retain soil on right side.
- Scraper between the rings, only on Single V and U-Profile Roller as well as Wave roller.
- 60 mm axles, fitted with 60 mm triple-sealed ball bearings on all models.




*Standard equipment on all models:*
*Adjustable edge disc for retain soil on right side.*



*Standard equipment on all models:*
*”DSD”: Depth Synchronized Disc-Aggressiveness.*



*Standard equipment on models with 2 and 3 section: HE-VA SAT-System:*
*Hydr. adjustable weight transfer system, ensuring equal weight transfer in the total working width, resulting in the fact that the wing sections follow the terrain.*

# DISC-ROLLER CONTOUR (TRAILED)



*8.00 m Disc-Roller Contour with V-Profile Roller and support wheels.*



*5.50 m Disc-Roller Contour with Twin V-Profile Roller and material damper guard.*

- HE-VA SAT-System on models with 2 and 3 sections.
- Sabre disc" 510 x 4 mm large scalloped disc with specially designed coulter profile – thus ensuring an improved cutting of surface stubble preparation.
- Maintenance-free disc-hubs.
- Working depth of up to 125 mm in minimal tillage cultivations.
- "DSD - Technology": Depth Synchronized Disc-Aggressiveness.

## MACHINES

| Model, m | Work / Transport Width, m | Roller Type | No. of Rings | No. of Discs | Power Req., HP | Weight, kg | Item Number |
|---|---|---|---|---|---|---|---|
| **1-SECTION RIGID MODELS WITHOUT HYDRAULIC FOLDING** | | | | | | | |
| **2.50** | 2.25 / 2.50 | Wave roller / 600 mm [1*] | 16 | 18 | 80 + | - | 63093-61 |
| **2.50** | 2.25 / 2.50 | U-Profile Roller / 600 mm [1*] | 16 | 18 | 90 + | - | 63093-68 |
| **2.50** | 2.25 / 2.50 | V-Profile Roller / 600 mm [1*] | 16 | 18 | 90 + | - | 63093-63 |
| **2.50** | 2.25 / 2.50 | V-Profile Roller / 700 mm [1*] | 16 | 18 | 90 + | - | 63093-69 |
| **2.50** | 2.25 / 2.50 | Twin U-Profile 600-600 mm [1*] | 16 | 18 | 90 + | - | 63093-67 |
| **2.50** | 2.25 / 2.50 | Twin V-Profile 600-600 mm [1*] | 16 | 18 | 90 + | - | 63093-66 |
| **3.00** | 2.75 / 3.00 | Wave roller / 600 mm [1*] | 20 | 22 | 100 + | 2,400 | 63091-61 |
| **3.00** | 2.75 / 3.00 | U-Profile Roller / 600 mm [1*] | 20 | 22 | 100 + | 2,500 | 63091-68 |
| **3.00** | 2.75 / 3.00 | V-Profile Roller / 600 mm [1*] | 20 | 22 | 100 + | 3,040 | 63091-63 |
| **3.00** | 2.75 / 3.00 | V-Profile Roller / 700 mm [1*] | 20 | 22 | 100 + | - | 63091-69 |
| **3.00** | 2.75 / 3.00 | Twin U-Profile 600-600 mm [1*] | 20 | 22 | 100 + | - | 63091-67 |
| **3.00** | 2.75 / 3.00 | Twin V-Profile 600-600 mm [1*] | 20 | 22 | 100 + | - | 63091-66 |
| **3.50** | 3.25 / 3.50 | Wave roller / 600 mm [1*] | 23 | 26 | 100 + | 2,710 | 63096-61 |
| **3.50** | 3.25 / 3.50 | U-Profile Roller / 600 mm [1*] | 23 | 26 | 110 + | - | 63096-68 |
| **3.50** | 3.25 / 3.50 | V-Profile Roller / 600 mm [1*] | 23 | 26 | 110 + | 3,160 | 63096-63 |
| **3.50** | 3.25 / 3.50 | V-Profile Roller / 700 mm [1*] | 23 | 26 | 110 + | - | 63096-69 |
| **3.50** | 3.25 / 3.50 | Twin U-Profile 600-600 mm [1*] | 23 | 26 | 110 + | - | 63096-67 |
| **3.50** | 3.25 / 3.50 | Twin V-Profile 600-600 mm [1*] | 23 | 26 | 110 + | - | 63096-66 |
| **4.00** | 3.75 / 4.00 | Wave roller / 600 mm [1*] | 26 | 30 | 110 + | 3,030 | 63092-61 |
| **4.00** | 3.75 / 4.00 | U-Profile Roller / 600 mm [1*] | 26 | 30 | 120 + | - | 63092-68 |
| **4.00** | 3.75 / 4.00 | V-Profile Roller / 600 mm [1*] | 26 | 30 | 120 + | 3,300 | 63092-63 |
| **4.00** | 3.75 / 4.00 | V-Profile Roller / 700 mm [1*] | 26 | 30 | 120 + | - | 63092-69 |
| **4.00** | 3.75 / 4.00 | Twin U-Profile 600-600 mm [1*] | 26 | 30 | 120 + | - | 63092-67 |
| **4.00** | 3.75 / 4.00 | Twin V-Profile 600-600 mm [1*] | 26 | 30 | 120 + | - | 63092-66 |
| **2-SECTION MODELS WITH HYDRAULIC FOLDING** | | | | | | | |
| **4.50** | 4.25 / 2.42 | Wave roller / 600 mm [2*] | 30 | 34 | 130 + | - | 63092-83 |
| **4.50** | 4.25 / 2.42 | U-Profile Roller / 600 mm [2*] | 30 | 34 | 140 + | - | 63092-84 |
| **4.50** | 4.25 / 2.42 | V-Profile Roller / 600 mm [2*] | 30 | 34 | 140 + | 3,715 | 63092-86 |
| **4.50** | 4.25 / 2.42 | V-Profile Roller / 700 mm [2*] | 30 | 34 | 140 + | 4,380 | 63092-81 |
| **4.50** | 4.25 / 2.42 | Twin U-Profile 600-600 mm [2*] | 30 | 34 | 140 + | 4,200 | 63092-88 |
| **4.50** | 4.25 / 2.42 | Twin V-Profile 600-600 mm [2*] | 30 | 34 | 140 + | 4,825 | 63092-87 |
| **5.50** | 5.25 / 2.42 | Wave roller / 600 mm [2*] | 36 | 42 | 160 + | - | 63093-83 |
| **5.50** | 5.25 / 2.42 | U-Profile Roller / 600 mm [2*] | 36 | 42 | 170 + | - | 63093-84 |
| **5.50** | 5.25 / 2.42 | V-Profile Roller / 600 mm [2*] | 36 | 42 | 170 + | 4,770 | 63093-86 |
| **5.50** | 5.25 / 2.42 | V-Profile Roller / 700 mm [2*] | 36 | 42 | 170 + | 5,090 | 63093-81 |
| **5.50** | 5.25 / 2.42 | Twin U-Profile 600-600 mm [2*] | 36 | 42 | 170 + | - | 63093-88 |
| **5.50** | 5.25 / 2.42 | Twin V-Profile 600-600 mm [2*] | 36 | 42 | 170 + | 5,090 | 63093-87 |
| **6.50** | 6.25 / 2.62 | Wave roller / 600 mm [2*] | 42 | 50 | 190 + | - | 63091-83 |
| **6.50** | 6.25 / 2.62 | U-Profile Roller / 600 mm [2*] | 42 | 50 | 200 + | - | 63091-84 |
| **6.50** | 6.25 / 2.62 | V-Profile Roller / 600 mm [2*] | 42 | 50 | 200 + | 5,915 | 63091-86 |
| **6.50** | 6.25 / 2.62 | V-Profile Roller / 700 mm [2*] | 42 | 50 | 200 + | - | 63091-81 |
| **6.50** | 6.25 / 2.62 | Twin U-Profile 600-600 mm [2*] | 42 | 50 | 200 + | - | 63091-88 |
| **6.50** | 6.25 / 2.62 | Twin V-Profile 600-600 mm [2*] | 42 | 50 | 200 + | - | 63091-87 |
| **3-SECTION MODELS WITH HYDRAULIC FOLDING** | | | | | | | |
| **8.00** | 7.75 / 2.45 | Wave roller / 600 mm [2*] | 53 | 64 | 220 + | - | 63095-66 |
| **8.00** | 7.75 / 2.45 | U-Profile Roller / 600 mm [2*] | 53 | 64 | 240 + | - | 63095-68 |
| **8.00** | 7.75 / 2.45 | V-Profile Roller / 600 mm [2*] | 53 | 64 | 240 + | - | 63095-65 |

*[1*]Requires 2 double-acting oil outlets.*

*[2*]Requires 3 double-acting oil outlets.*

# STANDARD EQUIPMENT

- HE-VA SAT-System on models with 2- and 3-sections: hydr. adjustable weight transfer system, ensuring equal weight transfer in the total working width.
- Hydr. adjustment of the working depth, at the same time used for lifting of “disc” on headland.
- Adjustable drawbar height with distance clips and parking device for hydraulic hoses.
- Adjustable edge disc for retain soil on right side.
- Scraper between the rings, only on Single V and U-Profile Roller as well as Wave roller.
- 60 mm axles, fitted with 60 mm triple-sealed ball bearings on all models.

- Wheels :
  - 2.50 and 3.00 m 1-section: 11.5/80x 15.3 – 14 PLY.
  - 3.50 and 4.00 m 1-section and 4.50 m 2-section: 400/60 x 15.5 – 16 PLY.
  - 5.50, 6.50 and 8.00 m: 500/50 x 17.0 – 18 PLY.

- Pivotal towing eye, secured by bolts :
  - 2.50 – 4.00 m, item no.. 630757028.
  - 4.50 – 8.00 m, item no.. 630757017.

- Only 8.00 m:
  - Hydr. jack stand with change-over valve from folding function.
  - Electric depth stop with switch in the cabin.
  - Hydr. operation of locking f/middle section in working position.



*5.50 m Disc-Roller Contour with Twin V-Profile Roller and material damper guard.*




*3.50 m Disc-Roller Contour trailed with Twin V-Profile Roller and Spring-Board.*







*6.50 m Disc-Roller Contour with V-Profile Roller, material damper guard, pivoting support wheels and two-point pivoting crossbar.*



# EXTRA EQUIPMENT - THREE-POINT MOUNTED / TRAILED

| Description | | Weight, kg | Item Number |
|---|---|---|---|
| LED lights with wire and socket, for 1-section three-point mounted models | | 3 | 63090-01 |
| LED lights with wire and socket, for 2-section three-point mounted models | | 3 | 63097-01 |
| LED lights w/wire and socket, for 1-section trailed models | | 3 | 63092-01 |
| LED lights w/wire and socket, for 2-sections trailed models | | 29 | 3401951 |
| LED lights w/wire and socket, for 3-sections trailed models | | 3 | 63094-01 |
| Set of reflective warning boards (2 pieces) | | 8 | 67055-74 |
| In line-system for all 1- and 2-section models. By means of Memory cylinder, the machine's parallelism with the soil surface can be hydraulically adjusted during work. | 1* | 20 | 63091-25 |
| HPV-Controller: El-hydr. operation of 4 functions. | | 7 | 3409430 |

*[1*]Requires 1 additional double-acting oil outlet.*

| Work Width, m | Description | Weight, kg | Item Number |
|---|---|---|---|
| **2.50 - 4.50** | Electrical depth stop | 4 | 63092-90 |
| **5.50 - 6.50** | Electrical depth stop | 8 | 63092-89 |
| **2.50 - 4.00** | Drawbar extension, 300 mm M16 for bolting on | 25 | 63091-95 |
| **4.50 - 8.00** | Drawbar extension 400 mm M20 | 32 | 63094-12 |
| **3.50 - 4.50** | Wheels 500/50x17.0-18 PLY (Additional price per set) | 85 | 3409750 |
| **2.50 - 3.00** | Trail kit, 11.5/80x15.3 | 1,075 | 63090-80 |
| **3.50 - 4.50** | Trail kit, 400/60x15.5 | 1,105 | 63095-80 |
| **5.50 - 6.50** | Trail kit, 500/50x17.0 | 1,155 | 63094-80 |
| **3.00 - 6.50** | Air brakes | 18 | 63093-96 |
| **8.00** | Air brakes | 18 | 63094-96 |
| **3.00 - 6.50** | Hydraulic brakes, 1-circuit | 7 | 63093-94 |
| **8.00** | Hydraulic brakes, 1-circuit | 7 | 63094-94 |
| **3.00 - 6.50** | Hydraulic brakes, 2-circuit, **factory-mounted** | - | 63093-95 |
| **8.00** | Hydraulic brakes, 2-circuit, **factory-mounted** | - | 63094-95 |
| **2.50** | Material damper guard | 45 | 63090-98 |
| **3.00** | Material damper guard | 50 | 63091-96 |
| **3.50** | Material damper guard | 56 | 63096-96 |
| **4.00** | Material damper guard | 84 | 63092-96 |
| **4.50** | Material damper guard | 105 | 63092-97 |
| **5.50** | Material damper guard | 120 | 63093-97 |
| **6.50** | Material damper guard | 125 | 63091-99 |
| **8.00** | Material damper guard | 160 | 63095-98 |
| **2.50 - 4.00** | Rubber sealed/non-lubricant ball bearings, single roller (Additional price per set) | 16 | 63090-03 |
| **2.50 - 4.00** | Rubber sealed/non-lubricant ball bearings, double roller (Additional price per set) | 33 | 63090-05 |
| **4.00 - 6.50** | Rubber sealed/non-lubricant ball bearings, single roller (Additional price per set) | 33 | 63090-05 |
| **4.00 - 6.50** | Rubber sealed/non-lubricant ball bearings, double roller (Additional price per set) | 66 | 63090-08 |
| **8.00** | Rubber sealed/non-lubricant ball bearings (Additional price per set) | 49 | 63090-06 |
| **-** | Bearing protector for packing roller (Per unit) | 1 | 7355054 |
| **-** | Ø510 x 5 mm "Sabre discs" HD aggressive (Additional price per m) | 8 | 63090-10 |
| **4.50 - 6.50** | Wheel track eradicator set with 4 pcs. of 65x12 mm tines for models without Spring-Board | 122 | 63090-38 |
| **4.50 - 6.50** | Wheel track eradicator set with 4 pcs. of 65x12 mm tines for models with Spring-Board | 122 | 63090-39 |
| **-** | Extension kit with 4 pcs. of 65x12 mm tines | - | 63090-40 |



*Rubber sealed ball bearings.*



*Bearing protector for packing roller.*



*Ø510 x 5 mm "Sabre discs" HD aggressive.*



**LONGFINGER AFTERHARROW AFTER ROLLER.**
**SPINDLE ADJUSTMENT OF WORKING DEPTH W/POSSIBILITY OF WEIGHT TRANSFER.**

| Work Width, m | Description | Item Number |
|---|---|---|
| **2.50** | For three-point mounted model | 63090-50 |
| **3.00** | For three-point mounted model | 63094-50 |
| **3.50** | For three-point mounted model | 63095-50 |
| **4.00** | For three-point mounted model | 63096-50 |
| **4.50** | For three-point mounted model | 63097-49 |
| **5.50** | For three-point mounted model | 63098-49 |
| **6.50** | For three-point mounted model | 63099-49 |
| **2.50** | For trailed model - mounted behind transport wheels | 63093-51 |
| **3.00** | For trailed model - mounted behind transport wheels | 63091-51 |
| **3.50** | For trailed model - mounted behind transport wheels | 63096-51 |
| **4.00** | For trailed model - mounted behind transport wheels | 63092-51 |
| **4.50** | For trailed model - mounted behind transport wheels | 63092-49 |
| **5.50** | For trailed model - mounted behind transport wheels | 63093-50 |
| **6.50** | For trailed model - mounted behind transport wheels | 63091-49 |

# EXTRA EQUIPMENT - THREE-POINT MOUNTED / TRAILED (CONTINUED)











| Work Width, m | Type / Description | | Weight, kg | Item Number |
|---|---|---|---|---|
| **SPRING-BOARD (ONLY TRAILED MODELS)** | | | | |
| **2.50** | Rigid, 1-section | 1*/2* | 240 | 63390-00 |
| **3.00** | Rigid, 1-section | 1*/2* | 280 | 63391-00 |
| **3.50** | Rigid, 1-section | 1*/2* | 325 | 63396-00 |
| **4.00** | Rigid, 1-section | 1*/2* | 370 | 63392-00 |
| **4.50** | Foldable, 2-section | 1*/2* | 375 | 63592-10 |
| **5.50** | Foldable, 2-section | 1*/2* | 450 | 63593-10 |
| **6.50** | Foldable, 2-section | 1*/2* | 525 | 63594-10 |
| **8.00** | Foldable, 3-section | 1*/2* | 775 | 63595-00 |
| **-** | Edge equipment set for Spring-Board tines | | 11 | 63301-00 |
| **SPRING-BOARD WITH SLICING PLATES (ONLY TRAILED MODELS)** | | | | |
| **2.50** | Rigid, 1-section | 1*/2* | - | 63790-00 |
| **3.00** | Rigid, 1-section | 1*/2* | - | 63791-00 |
| **3.50** | Rigid, 1-section | 1*/2* | - | 63796-00 |
| **4.00** | Rigid, 1-section | 1*/2* | - | 63792-00 |
| **4.50** | Foldable, 2-section | 1*/2* | 280 | 63592-20 |
| **5.50** | Foldable, 2-section | 1*/2* | 325 | 63593-20 |
| **6.50** | Foldable, 2-section | 1*/2* | 525 | 63594-20 |
| **8.00** | Foldable, 3-section | 1*/2* | - | 63895-00 |
| **SPRING-BOARD WITH Ø16 MM LONGFINGER TINES (ONLY TRAILED MODELS)** | | | | |
| **2.50** | Rigid, 1-section - 10 tines | 1*/2* | 240 | 63390-01 |
| **3.00** | Rigid, 1-section - 12 tines | 1*/2* | 201 | 63391-01 |
| **3.50** | Rigid, 1-section - 14 tines | 1*/2* | 232 | 63396-01 |
| **4.00** | Rigid, 1-section - 16 tines | 1*/2* | 264 | 63392-01 |
| **4.50** | Foldable, 2-section - 18 tines | 1*/2* | 256 | 63592-01 |
| **5.50** | Foldable, 2-section - 22 tines | 1*/2* | 305 | 63593-01 |
| **6.50** | Foldable, 2-section - 26 tines | 1*/2* | 354 | 63594-01 |
| **8.00** | Foldable, 3-section - 32 tines | 1*/2* | 564 | 63595-01 |
| **TRANSVERSE LOCKING SYSTEM - CONNECTS THE SPRING-BOARD TINES (ONLY TRAILED MODELS)** | | | | |
| **2.50** | Rigid, 1-section | 1* | - | 63490-00 |
| **3.00** | Rigid, 1-section | 1* | 35 | 63491-00 |
| **3.50** | Rigid, 1-section | 1* | 41 | 63496-00 |
| **4.00** | Rigid, 1-section | 1* | 47 | 63492-00 |
| **4.50** | Foldable, 2-section | 1* | 52 | 63592-30 |
| **5.50** | Foldable, 2-section | 1* | 75 | 63593-30 |
| **6.50** | Foldable, 2-section | 1* | 86 | 63594-30 |
| **8.00** | Foldable, 3-section | 1* | - | 63695-00 |

[1*] *Requires 1 additional double-acting oil outlet.*

[2*] *Drawbar extension is recommended, when the tractor is equipped with twin wheels.*

| SET OF PIVOTING SUPPORT WHEELS, MOUNTED IN FRONT, HEIGHT ADJUSTABLE WHEELS: 2 X 300/55X12- 8 PLY | | | |
|---|---|---|---|
| **Work Width, m** | **Description** | **Weight, kg** | **Item Number** |
| **2.50 - 6.50** | For trailed models. | 140 | 63091-30 |
| **2.50 - 6.50** | For trailed models with Spring-Board | 180 | 63091-35 |
| **8.00** | Incl. cross-drawbar for mounting in the tractor's lift arms (630757034). Cannot be combined with Spring-Board. | 400 | 63095-08 |



| | | TOP-CUTTER (ONLY TRAILED MODELS) | SPRING-BOARD ON TOP-CUTTER BRACKETS (ONLY TRAILED MODELS) |
|---|---|---|---|
| **Work Width, m** | **Type** | **Item Number** | **Item Number** |
| **2,50** | Rigid | 67410-41 | 67410-42 |
| **3,00** | Rigid | 67410-43 | 67410-44 |
| **3,50** | Rigid | 67410-45 | 67410-46 |
| **4,00** | Rigid | 67410-47 | 67410-48 |
| **4,50** | Foldable | 67410-49 | 67410-50 |
| **5,50** | Foldable | 67410-51 | 67410-52 |
| **6,50** | Foldable | 67410-53 | 67410-54 |

# EXTRA EQUIPMENT - THREE-POINT MOUNTED / TRAILED (CONTINUED)

**MOUNTING SET FOR MULTI-SEEDER INCL. STEPS, INCL. MOUNTING ON DISC-ROLLER CONTOUR MAX. 300 KG LOAD IN FINE SEED HOPPER.**

| Work Width, m | Type | Item Number 8 Outlets | Item Number 12 Outlets | Item Number 16 Outlets |
|---|---|---|---|---|
| **2.50** | without Auto-Controller / EC [1*] | 63090-16 | - | - |
| **2.50** | with Auto-Controller / EC [2*] | 63090-17 | - | - |
| **3.00** | without Auto-Controller / EC [1*] | 63091-17 | - | - |
| **3.00** | with Auto-Controller / EC [2*] | 63091-18 | - | - |
| **3.50** | without Auto-Controller / EC [1*] | 63096-16 | - | - |
| **3.50** | with Auto-Controller / EC [2*] | 63096-17 | - | - |
| **4.00** | without Auto-Controller / EC [1*] | 63092-15 | - | - |
| **4.00** | with Auto-Controller / EC [2*] | 63092-23 | - | - |
| **4.50** | without Auto-Controller / EC [1*] | 63092-17 | 63092-24 | 63092-20 |
| **4.50** | with Auto-Controller / EC [2*] | 63092-21 | 63092-25 | 63092-22 |
| **5.50** | without Auto-Controller / EC [1*] | 63093-15 | 63093-23 | 63093-20 |
| **5.50** | with Auto-Controller / EC [2*] | 63093-21 | 63093-24 | 63093-22 |
| **6.50** | without Auto-Controller / EC [1*] | - | 63091-23 | 63091-19 |
| **6.50** | with Auto-Controller / EC [2*] | - | 63091-24 | 63091-22 |
| **8.00** | without Auto-Controller / EC [1*] | - | 63095-23 | 63095-18 |
| **8.00** | with Auto-Controller / EC [2*] | - | 63095-24 | 63095-22 |
| **4.50 - 6.50** | Platform and ladder for Multi-Seeder | - | - | 63099-45 |

*[1*]On trailed models hydraulic lifting of seed wheel is included, which requires 1 additional double-acting oil outlet.*
*[2*]On / Off switch on Multi-Seeder with AC is always mounted on wheel frame.*

**DISTRIBUTOR SET FOR HE-VA FRONT-TANK**

| Work Width, m | Description | Item Number |
|---|---|---|
| **2.50 - 8.00** | Distributor set with 12 outlets for HE-VA Front-Tank for Disc-Roller Contour | 0537701 |