

FRONT-LIFT 55.01 – Integrated Model



- Front-Lift with 5,500 kg lifting capacity with 190 bar.
- Integrated most possible for tractor with respect to design & space requirement.
- Individual lift arms with 4 possible positions: a) free moving b) limited moving c) locked position d) transport position.
- Good for big tractors from 150 HP and up.
- Can be adapted to Front-PTO.

PRICES With adapted side bracket plates: Look in "Tractor Makes/Model List".

| Designation | Weight | Item No. | |
|-----------------------------------------|--------|----------|--|
| 55.01 without adapted side bracket bars | | 66800-00 | |
| Bolt brackets incl. bolts for 55.01 | | 66800-01 | |

STANDARD EQUIPMENT

- Double acting hydr. with air filter on lowering side.
- Cat. 2, DS/ISO 8759/1/2, 825 mm between the lift arms' balls.
- Cleaned and painted with a two-component primer and finally painted in the tractor's colour - two-component.
- Adapted to the individual tractor model.
- Chassis bolts & 5,5 m hydr. hoses with couplings.
- Stop valve device on hydr. hose at tractor connection – the lift can then be locked.
- Quick-coupling for lift arms, cat. 3, with $\varnothing 28$ mm balls cat. 3/2.
- Top link M36 and $\varnothing 25$ mm pin with parking device for the lift arms' balls.
- Parking device for top link.
- **For several models:** direct hydr. connection. Look after * in "Tractor Makes / Model List".

EXTRA EQUIPMENT (Description of extra equipment – look at page 2).

| Designation | Weight | Item No. | |
|---------------------------------------------------------------------------------------------------------|--------|-----------|--|
| Accessory kit from single to double acting front-linkages, mount. | 4 kg | - | |
| Shock absorber kit incl. hoses and fittings, mounted | 4 kg | 66885-00 | |
| Spring suspension kit incl. hoses and fittings, mounted | 16 kg | 66890-00 | |
| Shift-Control Double, EI-shift between Front-Lift and one outlet | 8 kg | 65100-10 | |
| Shift-Control Triple, EI-shift between Front-Lift and two outlets | 14 kg | 65100-12 | |
| Double oil outlet on Front-Lift, with hoses from tractor outlet | 9 kg | 65100-20 | |
| Holders for relief springs per set | 7 kg | 668205001 | |
| Torsion bar | 30 kg | 668003005 | |
| Position stop, electrical | | 66875-00 | |
| MF 6200-8200 & 6400-8400 position detector kit with electronic pushbuttons for lift & lowering function | 3 kg | 65717-xx | |
| MF 6400-8400 electrical pushbuttons for lift & lowering function | | 65818-86 | |
| JD 6020/6030 premium plus/8020+8030 el. pushbuttons f/ lift&low. f. | | 65805-55 | |
| JD 7020/7030 electrical pushbuttons for lift & lowering function | | 65805-80 | |
| Claas Arion, Axion electrical pushbuttons for lift & low. function | | 65744-95 | |