

# FRONT-PAKKER



4.00 m w/800 mm rinas. Sprina-Board



3,00 m m/800/900/800mm rings.



1,5 m m/4,00 m Spring-Board in transport position.

- Specially developed ring profile w/shoulders ensures uniform packing on varying soil types.
- Self governing packer. The pull centre is situated in front of the rings - to ensure free mobility of the machine.
- Automatic centre position when the implement is lifted on the headland.

## PRICES & SPECIFICATIONS

Working Width	Machine Type	Ring Type	No. of Rings	Weight kg	Power Req.,HP	Transp. Width	Item Number
1.50 m	Rigid	700 mm	10	680	15	1.70 m	67033-70
		800 mm	10	890	15	1.75 m	67033-80
1.65 m	Rigid	900 mm	10	1,140	15	1.80 m	67043-90
2.60 m	Rigid	700 mm	16	866	20	2.60 m	67034-70
		800 mm	16	1,230	20	2.60 m	67034-80
		900 mm	14	1,685	20	2.60 m	67044-90
3.00 m	Rigid	700 mm	18	980	25	3.00 m	67035-70
		800 mm	18	1,420	25	3.00 m	67035-80
		900 mm	17	1,940	25	3.00 m	67045-90
		700/800/700mm	18	1,160	25	3.00 m	67235-70
		800/900/800mm	17	1,610	25	3.00 m	67235-80
3.50 m	Rigid	700 mm	22	1,160	30	3.50 m	67037-70
		800 mm	22	1,660	30	3.50 m	67037-80
		900 mm	19	2,120	30	3.50 m	67037-90
		700/800/700mm	22	1,340	30	3.50 m	67238-70
		800/900/800mm	19	1,750	30	3.50 m	67238-80
4.00 m	Rigid	700 mm	24	1,280	35	4.15 m	67036-70
		800 mm	24	1,840	35	4.15 m	67036-80
		900 mm	23	2,415	35	4.15 m	67046-90
		700/800/700mm	24	1,460	35	4.15 m	67236-70
		800/900/800mm	23	2,030	35	4.15 m	67236-80
* 4.00 m	Hydr. folding	700 mm	24	1,430	35	2.55 m	67046-70
		800 mm	24	1,990	35	2.65 m	67046-80
		900 mm	21	2,580	35	2.75 m	67047-90
		700/800/700mm	24	1,610	35	2.55 m	67246-70
		800/900/800mm	21	2,180	35	2.65 m	67246-80
* 5.00 m	Hydr. folding	700 mm	30	1,655	45	2.85 m	67048-70
		800 mm	30	2,350	45	2.95 m	67048-80
		700/800/700mm	30	1,835	45	2.85 m	67248-70
* 6.00 m	Hydr. folding	700 mm	36	1,875	55	2.85 m	67047-70
		800 mm	36	2,695	55	2.95 m	67047-80
		700/800/700mm	36	2,095	55	2.95 m	67247-70

\* The equipment requires 1 double-acting oil outlet.

## STANDARD EQUIPMENT

- Cleaning chains between the rings.
- Packer rings with wide shoulder – unique HE-VA feature.
- Support stand, pins and locking pins.

# FRONT-PAKKER TWIN / PRESS-ROLLER



Press-Roller  
H760, 1.50 m.

1.5 m Front-Pakker  
Twin w/ø 800mm.



- Specially developed ring profile w/shoulders ensures uniform packing on varying soil types.
- Self governing wheel packer. The pull centre is located in front of the wheels to ensure free mobility of the machine.
- Automatic centre position when the tool is lifted on the headland.

## PRICES & SPECIFICATIONS - FRONT-PAKKER TWIN

Working Width	Model	RingType	No. of Rings	Weight kg	Power Req.,HP	Transport Width m	Item Number
1.50 m	Rigid	700-700 mm	15	975	15	1.70	67033-75
		800-800 mm	15	1,185	20	1.75	67033-85
1.65 m	Rigid	900-900 mm	13	1,590	20	1.80	67043-95
2.60 m	Rigid	700-700 mm	21	1,380	20	2.60	67034-75
		800-800 mm	21	1,740	25	2.60	67034-85
3.00 m	Rigid	700-700 mm	24	1,570	25	3.00	67035-75
		800-800 mm	24	2,010	30	3.00	67035-85
3.50 m	Rigid	700-700 mm	30	1,610	35	3.50	67039-75
		800-800 mm	30	2,290	40	3.50	67039-85
* 3.50 m	Hydr.	700-700 mm	29	1,780	35	2.55	67049-75
		800-800 mm	29	2,460	40	2.65	67049-85
4.00 m	Rigid	700-700 mm	34	1,890	40	4.15	67036-75
		800-800 mm	34	2,665	45	4.15	67036-85
* 4.00 m	Hydr.	700-700 mm	32	2,070	40	2.55	67046-75
		800-800 mm	32	2,845	45	2.65	67046-85

\* The machine requires 1 double-acting oil outlet.

## PRICES & SPECIFICATIONS - PRESS-ROLLER H760

- Large wheel diameter ensures proper operation on loose sandy soil.

Working Width	Model	No. of Wheels	Weight kg	Power Req.; HP	Transport Width m	Item Number
1.50 m	Rigid	4	470	20	1.70	67072-00
4.00 m	Rigid	1+4+1	705	35	4.15	67073-00
*4.00 m	Hydr. folding	1+4+1	795	35	2.65	67074-00

\* The machine requires 1 double-acting oil outlet.

## STANDARD EQUIPMENT

- Double-sealed ball bearings and 60 mm shaft.
- Support stand, pins and locking pins.
- Front-Pakker Twin: Cleaning chains between the rings.  
Packer rings with wide shoulder – unique HE-VA feature.
- Press-Roller: Rubber wheels, 10.0/75 x 15,3 – 10 PLY, 760 mm wheel diameter.  
Scrapers between and behind wheels.

EXTRA EQUIPMENT : SEE PAGE 20

## EXTRA EQUIPM.: FRONT-PAKKER, FRONT-PAKKER TWIN & PRESS-ROLLER H760

- 2.60 m, 3.00 m & 3.50 m Front-Harrow & Spring-Board can also be mounted on 1.50/1.65 m models.
- Spring-Board is w/mech. adjustment of the height of the tine row & hydr. adjustment of the preparation degree.
- Transverse locking syst. w/possible individual connection & discon., very easy without use of any tools.
- Stabilization device: is recommended for combination with GPS autosteer.

Designation	Weight	Item No.	
LED marking lights with clear and red glass, rigid models	4 kg	67033-01	
LED marking lights with clear and red glass, 4.00m hydr. model	14 kg	67033-02	
LED marking lights with clear and red glass, 5 + 6.00m hydr.	17 kg	67033-03	
Warning sign set (2 pieces)	6 kg	690160075	
Weight console set – for bolting on of additional weight, 2 pcs.	32 kg	67086-00	
Stabilization device for all models	16 kg	67086-10	
Mech. double change-over valve changes between Spring-Board & hydr. folding.	5 kg	67086-15	
Stone box set (2 pieces)	32 kg	630555009	
Edge equipment for Spring-Board tines	5 kg	63301-00	
Edge equipment for front-harrow	18 kg	67058-00	
<b>FRONT-HARROW – spindle adjustment of working depth, 12x45 mm tines</b>			
12 x 65 mm tines	<b>Additional price pr. m</b>	22 kg	63136-00
2.60 m rigid, 15 tines 2-tine rows, spindle depth control		158 kg	67080-50
3.00 m rigid, 17 tines 2-tine rows, spindle depth control		177 kg	67081-50
3.50 m rigid, 20 tines 2-tine rows, spindle depth control		201 kg	67083-50
4.00 m rigid, 23 tines 2-tine rows, spindle depth control		254 kg	67082-50
4.00 m hydr. folding, 23 tines 2-tine rows, spindle depth cont.		275 kg	67087-50
5.00 m hydr. folding, 29 tines 2-tine rows, spindle depth cont.		330 kg	67091-50
6.00 m hydr. folding, 35 tines 2-tine rows, spindle depth cont.		397 kg	67089-50
<b>SPRING-BOARD – spring tine levelling bar with 10 x 80 mm tines, hydraulic adjustment</b>			
* 2.60 m rigid, w/hydr. depth control, 10 tines		185 kg	67183-00
■ * 3.00 m rigid, w/hydr. depth control f/1.5 / 1.65 m, 12 tines		235 kg	67194-00
* 3.00 m rigid, w/hydr. depth control, 12 tines		235 kg	67184-00
* 3.50 m rigid, w/hydr. depth control, 14 tines		255 kg	67191-00
■ * 4.00 m rigid, w/hydr. depth control f/1.5 / 1.65m, 16 tines		275 kg	67186-00
* 4.00 m rigid, w/hydr. depth control, 16 tines		275 kg	67185-00
▲ * 4.00 m hydr. folding, w/hydr. depth control, 16 tines		460 kg	67188-00
* 5.00 m hydr. folding, w/hydr. depth control, 20 tines		515 kg	67192-00
* 6.00 m hydr. folding, w/hydr. depth control, 24 tines		570 kg	67190-00
<b>SPRING-BOARD with SLICING PLATES – hydraulic adjustment</b>			
* 2.60 m rigid, w/hydr. depth control, 10 tines		185 kg	67383-00
■ * 3.00 m rigid, w/hydr. depth control f/1.5 / 1.65 m, 12 tines		235 kg	67394-00
* 3.00 m rigid, w/hydr. depth control, 12 tines		235 kg	67384-00
* 3.50 m rigid, w/hydr. depth control f/1.5 / 1.65 m, 14 tines		255 kg	67391-00
■ * 4.00 m rigid, w/hydr. depth control f/1.5 / 1.65 m, 16 tines		275 kg	67386-00
* 4.00 m rigid, w/hydr. depth control, 16 tines		275 kg	67385-00
▲ * 4.00 m hydr. folding, w/hydr. depth control, 16 tines		460 kg	67388-00
* 5.00 m hydr. folding, w/hydr. depth control, 20 tines		515 kg	67392-00
* 6.00 m hydr. folding, w/hydr. depth control, 24 tines		570 kg	67390-00
<b>TRANSVERSE LOCKING SYSTEM – connects the Spring-Board tines</b>			
2.60 m, complete set for Spring-Board		30 kg	67283-00
3.00 m, complete set for Spring-Board		35 kg	67284-00
3.50 m, complete set for Spring-Board		41 kg	67286-00
4.00 m, complete set for Spring-Board		47 kg	67285-00
4.00 m, complete set for Spring-Board - hydr. folding		51 kg	67288-00
5.00 m, complete set for Spring-Board - hydr. folding		55 kg	67292-00
6.00 m, complete set for Spring-Board - hydr. folding		71 kg	67290-00

\* Requires 1 add. double-acting oil outlet. ▲ Cannot be mounted on 1.5 / 1.65 m models.

■ 3&4m Spring-Board for mount. on 1.50/1.65m, can manually be changed to transp. width 1.85&2.85m.