

# COMBI-TILLER MKII



6.00 m Combi-Tiller MKII with 11 tines.



- Standard with hydr. three-point linkage behind the machine.
- Good clearance with 420 mm tine staggering.
- Hydr. automatic release system or "Quick-Push" shear bolt stone protection.

## PRICES

For mounting in the linkage of the tractor:

Model	Working Width	Stone Protection	No. of Tines	Weight kg	Row Spacing	Item Number	
Combi-Tiller MKII w/ hydr. three-point linkage and cat. 3 snap-couplings.	* 3.00 m	Quick-Push	5	890	60 cm	64531-01	
	* 3.00 m	Hydr. auto.	5	1,035	60 cm	64531-11	
	* 3.50 m	Quick-Push	6	985	58 cm	64531-21	
	* 3.50 m	Hydr. auto.	6	1,130	58 cm	64531-31	
	* 4.00 m	Quick-Push	7	1,085	57 cm	64531-41	
	* 4.00 m	Hydr. auto.	7	1,230	57 cm	64531-51	
	* 4.00 m	Quick-Push	8	1,170	50 cm	64531-52	
	* 4.00 m	Hydr. auto.	8	1,350	50 cm	64531-53	
Can be used separately or together w/a trailed implement.	**4.00 m	Quick-Push	7	1,310	57 cm	64531-61	
	**4.00 m	Hydr. auto.	7	1,450	57 cm	64531-71	
	**4.00 m	Quick-Push	8	1,395	50 cm	64531-72	
	**4.00 m	Hydr. auto.	8	1,570	50 cm	64531-73	
Incl. 3 x double-acting oil outlets & extension cord for lights.	**4.00 m HD	Quick-Push	7	1,310	57 cm	64531-86	
	**4.00 m HD	Hydr. auto.	7	1,450	57 cm	64531-87	
	**4.00 m HD	Quick-Push	8	1,395	50 cm	64531-88	
	**4.00 m HD	Hydr. auto.	8	1,570	50 cm	64531-89	
	**5.00 m HD	Quick-Push	9	1,570	55,5 cm	64531-94	
	**5.00 m HD	Hydr. auto.	9	1,715	55,5 cm	64531-95	
	**6.00 m HD	Quick-Push	11	2,130	54,5 cm	64531-92	
	**6.00 m HD	Hydr. auto.	11	2,265	54,5 cm	64531-93	
	**6.00 m HD	Quick-Push	12	2,250	50 cm	64531-96	
	**6.00 m HD	Hydr. auto.	12	2,385	50 cm	64531-97	

\*The machine requires 1 double-act. oil outlet.\*\*The machine requires 2 double-act. oil outlets

## STANDARD EQUIPMENT FOR COMBI-TILLER MKII

- Pins, locking pins and depth scale for linkage.
- Point with 200 mm wing shares, mounted on a 25 mm wide tine.
- Linkage with cat. 3 snap-couplings and **cat. 2 distance (870 mm middle – middle)**.

### • 4.00 m hydr. model:


- Three-point linkage with cat. 3 pins and cat. 2 distance.
- Lift with cat. 3 snap-couplings and cat. 2 distance (870 mm middle - middle).

### • HD models 4.00 – 5.00 and 6.00 m:

- 1 set of support wheels, spindle adjustable: 2 pcs. 300/55x14.5.(not for 4,00 models)

- Three-point linkage with cat. 3 pins and cat 3 distance.
- Lift with cat. 3 snap-couplings and cat. 3 distance (1010 mm middle - middle).

## EXTRA EQUIPMENT

Benævnelse		Varenr.	
Linkage with cat. 3 snap-couplings and <b>cat. 3 distance</b> (1010 mm middle - middle) <b>Additional price</b>		64519-35	
One extra set of double-acting hydraulic hoses 3/8", with female quick-acting coupling mounted on the Combi-Tiller MKII.		64519-15	
1 set of support wheels, spindle adjustable: 2 pcs. 200/60 x 14.5 – 10 PLY <b>NB: Please note that the wheels have to be mounted outside the tractor's rear wheels. Standard for models with hydr. folding.</b>		64519-30	
Crossbar/clevis for mounting in the Combi-Tiller MKIIs lift arms for trailed implements for standard <b>cat. 2 distance</b>		64519-31	
Crossbar/clevis for mounting in the Combi-Tiller MKIIs lift arms for trailed implements for <b>cat. 3 distance</b> for HD models.		64519-33	
Point with 120mm wing shares	<b>Price reduction per tine</b>	645000043A	
Point with 350mm wing shares	<b>Additional price per tine</b>	645000063A	
Points 200 mm with hardmetalplate	<b>Additional price per tine</b>	645000044TA	
<b>Easy Draft kit</b> 15 mm tine with 120 mm wearing point "ED" w/ tungsten tip.		Quick-Push stone protection <b>Additional price per tine</b>	64512-06
		Quick-Push stone protection <b>Retro mounting per tine</b>	64512-05
		Hydr. automatic release sys. <b>Additional price per tine</b>	64512-16
		Hydr. automatic release sys. <b>Retro mounting per tine</b>	64512-15

Go to page 70 for selection of tines

## SPECIFICATIONS

- Tine height under the frame: 780 mm
- Tine staggering: 420 mm
- Max. working depth: 400 mm
- Power requirement (extra requirement in relation to Disc-Roller *Contour*): 15 hk per tine+/-
- Length from coupling point to coupling point (centre): 1.550 mm
- Transport width, 4.00 - 6.00 m hydr. foldable models: 2.50 m