

# DISC-SEEDER med Sabre-såskær eller Skive-såskær



3,00 m Disc-Seeder  
m/Sabre-seeding and CTX rubber roller.



3,00 m Disc-Seeder m/Square tube roller and Disc coulters.

- Mechanical Disc-Seed drill, primarily for seeding in a non-ploughed system, but can also be used for seeding in ploughed soil in combination with a front-mounted packer.
- **Sabre-Seeding:** The seeding is done simultaneously with the soil preparation, and the seeds are placed on the shady side of the Sabre-Disc. Hereby, you obtain the advantage that the seeds are placed in 3-6 cm wide bands on firm and clean soil without any hairpin effect. The soil is packed again around the grains by means of the following roller.
- **Disc-Coulters:** Firstly, the soil is prepared with discs in the desirable depth, independent of the seed depth. Then the roller packs the soil again, leaving the soil ready for seeding with double disc-coulters mounted with 50 mm wide depth / packing wheels behind.

## PRICES

Working width	Seed Hopper Volume	Disc-Seeder	Sabre-Seeding		Disc-Coulters	
			Item no.		Item no.	
*3.00 m	1,000 l	ø500 mm Square tube roller	4000100		4001100	
		ø540 mm Packer roller	4000110		4001110	
		ø520 mm CTX rubber roller	4000130		4001130	
		ø600 mm Wave roller	4000140		4001140	
*4.00 m	1,400 l	ø500 mm Square tube roller	4000200		4001200	
		ø540 mm Packer roller	4000210		4001210	
		ø520 mm CTX rubber roller	4000230		4001230	
		ø600 mm Wave roller	4000240		4001240	

\* The machine requires 1 double-acting oil outlet.

## STANDARD EQUIPMENT

- LED lights, pins and locking pins.
- 2 rows of ø510 mm scalloped Sabre-Disc, distance between the discs: 15 cm.
- Hydraulic harrow-mounted marker set for vertical position.
- Infinitely variable oil bath gearbox – with 2 speed ration.
- The seeding from 0.7 kg up to 400 kg/ha be means of the unique "side by side" double dosing roller. By means of shutters you can choose between the coarse roller (grain) or the fine roller (rape).
- Electronic tramline computer with trip- and ha control, tramline control, electronic alarm for empty seed hopper and dosing shaft rotation control, standard mounting: 180 cm tramline spacing middle-middle.
- Platform for inspection and filling.
- Agitator and seed hopper empty indicator.
- **Sabre-Seeding:**
  - 3-6 cm band seeding with 15 cm row distance.

To be continued on next page

- Disc-Coulters:
  - Row distance 12,5 cm
  - Double ø350 mm Disc-Coulters with 50 mm wide depth/packing wheels.
  - Material damper-guard is standard after the roller on a Square tube roller.
  - Parking device for seed drill.

## EXTRA EQUIPMENT

Model	Designation	Item Number		
3.00 m	Long finger after-harrow, fitted behind the roller (Sabre-Seeding)	3403625		
	Long finger after-harrow, f/mounting after the depth/packing wheels	3403620		
4.00 m	Long finger after-harrow, fitted behind the roller (Sabre-Seeding)	3404625		
	Long finger after-harrow, f/mounting after the depth/packing wheels	3404620		
3.00 m & 4.00 m	* Hydraulic lifting of sowing wheel	3260222		
	Visual tramlining	3260150		
	Electrical seed rate control 0% or + 10%	P008612664030		
	* Hydraulic coulters lifting via the seed drill's top link	3260140		
	Wheel track eradicator, 2x2 tines w/250mm wide goosefoot points	3409240		
	Mounting set for Multi-Seeder, incl. mounting on a new Disc-Seeder. NB: Only for model 200-8-EL AC or EC. Prices and information about Multi-Seeder, see page 98.	3 m Sabre-Seeding	3290266	
		4 m Sabre-Seeding	3290267	
		3 m Disc-Coulters	3260266	
		4 m Disc-Coulters	3260267	

\* The equipment requires 1 additional double-acting oil outlet.

## SPECIFICATIONS

Transport width: 3.00 m

Disc-Seeder		Weight empty, kg	Lifting requirement Full seed hopper	Power requirement, HP	Number of Disc-Coulters
3.00 m Sabre-Seeding	ø500 mm Square tube roller	1,650	3,300	100-140	20
	ø450 mm Spiral roller	1,680	3,360	100-140	20
	ø520 mm CTX rubber roller	1,830	3,660	100-140	20
	ø600 mm Wave roller	1,750	3,500	100-140	20
3.00 m Disc-Coulters	ø500 mm Square tube roller	2,270	6,250	120-160	24
	ø540 mm Packer roller	2,550	7,000	120-160	24
	ø520 mm CTX rubber roller	2,450	6,750	120-160	24
	ø600 mm Wave roller	2,370	6,530	120-160	24
4.00 m Sabre-Seeding	ø500 mm Square tube roller	2,220	4,450	120-160	26
	ø450 mm Spiral roller	2,260	4,530	120-160	26
	ø520 mm CTX rubber roller	2,420	4,850	120-160	26
	ø600 mm Wave roller	2,350	4,700	120-160	26
4.00 m Disc-Coulters	ø500 mm Square tube roller	2,900	7,980	140-180	32
	ø540 mm Packer roller	3,190	8,780	140-180	32
	ø520 mm CTX rubber roller	3,090	8,500	140-180	32
	ø600 mm Wave roller	3,010	8,230	140-180	32