

LIFT-ROLLER



3,00 m w/ 510 mm/21" Cambridge.



- Drawbar, free movable up/down.
- 60 mm bearings and shafts, special quality.
- Small lifting requirement – close to the tractor.

PRICES & SPECIFICATIONS

Working Width	Ring Type	No. of Spokes	No. of Rings	Weight kg	Lifting Req., kg	Pow. Req., HP	Item Number
2.60 m	450 mm/18" Cambridge	3	45	790	1,190	35	63073-45
	510 mm/21" Cambridge	3	45	930	1,400	40	63073-51
	510 mm/21" Cambridge	5	45	1,101	1,400	40	63073-46
	560 mm/22.5" Cambridge	9	45	1,160	1,630	45	63073-54
	620 mm/24" Cambridge	10	45	1,250	1,880	45	63073-62
	450/500 mm Star ring	◆	48	980	1,470	45	63073-56
	550/600 mm Star ring	◆	48	1,230	1,850	45	63073-57
	550 mm/22" Cam		16	680	1,020	30	63073-55
	485-530 mm Crosskill		25	730	1,100	40	63073-53
	550-600 mm Crosskill		25	1,050	1,570	40	63073-63
	500 mm 2D-Corrugated	8	31	830	1,250	40	63073-50
	550 mm 2D-Corrugated	9	31	860	1,290	40	63073-59
	600 mm 2D-Corrugated	10	31	880	1,320	45	63073-60
3.00 m	450 mm/18" Cambridge	3	53	900	1,350	45	63074-45
	510 mm/21" Cambridge	3	53	1,060	1,590	55	63074-51
	510 mm/21" Cambridge	5	53	1,261	1,590	55	63074-46
	560 mm/22.5" Cambridge	9	53	1,320	1,910	60	63074-54
	620 mm/24" Cambridge	10	53	1,430	2,150	60	63074-62
	450/500 mm Star ring	◆	56	1,110	1,670	60	63074-56
	550/600 mm Star ring	◆	56	1,400	2,100	60	63074-57
	550 mm/22" Cam		19	820	1,220	40	63074-55
	485-530 mm Crosskill		27	830	1,250	55	63074-53
	550-600 mm Crosskill		27	1,170	1,760	55	63074-63
	500 mm 2D-Corrugated	8	35	920	1,380	55	63074-50
	550 mm 2D-Corrugated	9	35	960	1,440	55	63074-59
	600 mm 2D-Corrugated	10	35	990	1,480	60	63074-60

◆ Cast steel ring.

STANDARD EQUIPMENT

- Three-point mounting for cat.
- Support stand, pins and locking pins.

EXTRA EQUIPMENT

Designation	Weight	Item no.
Lights, complete with wire and socket, mounted	4 kg	63003-01
Stone box set (2 pieces)	32 kg	630555005
Grass-Seeder Kit: 230 mm adjustable plain roller behind the implement, adjustable long finger harrow in front & mounting set f/Multi-Seeder.	For 2.60m	63073-20
	For 3.00m	63074-20