

SWING-ROLLER



- Strong frame construction of sectional tubes.
- Uncomplicated change-over between transport and working position when the tractor is stopped.
- All sections are centre suspended and mutually independent.
- **HE-VA SAT-System:** The weight balance system transfers the weight of the construction (drawbar, cylinder and wheel) on all 5 sections to ensure a uniform soil pressure in the entire working width.
- Compact and low – safe and stable transport.

PRICES & SPECIFICATIONS

Transport width of max. 2.70 m

Working Width	Ring Type	No. of Spokes	No. of Rings	Weight kg	Power Req., HP	Item Number	
*10,20 m	510 mm/21" Cambridge	3	199	6,010	150-180	63097-51	
	510 mm/21" Cambridge	8	199	6,330	150-180	63097-46	
	450/500 mm Star ring	◆	204	6,120	150-180	63097-56	
	485-530 mm Crosskill		105	5,960	150-180	63097-53	
	500 mm 2D-Corrugated	8	125	5,500	150-180	63097-50	
*12,20 m	510 mm/21" Cambridge	3	235	6,680	170-200	63098-51	
	510 mm/21" Cambridge	8	235	7,050	170-200	63098-46	
	450/500 mm Star ring	◆	240	6,750	170-200	63098-56	
	485-530 mm Crosskill		125	6,650	170-200	63098-53	
	500 mm 2D-Corrugated	8	150	6,130	170-200	63098-50	

* Requires 2 double-acting oil outlets.

◆ Cast steel ring

STANDARD EQUIPMENT FOR SWING-ROLLER

- Wheels: 400/60x15.5 – 14 PLY.
- Towing eye, secured by bolts, item no. 630757017, see page 111.
- Adjustable supporting leg with gear.
- Parking device for hydraulic hoses.
- 60 mm shafts, special quality, mounted with double-sealed ball bearings.
- Manual parking and transport protection of the wing sections.
- **HE-VA SAT-System:** Weight balance system on all 5 sections.

EXTRA EQUIPMENT

Designation	Weight kg	Item Number	
LED lights complete with wire and socket, mounted	3	63098-01	
Stone box set (2 pieces)	32	630555001	
Automatic protection of the wing sections during transport	3	63098-05	
Air brakes factory-mounted	18	63098-07	
Hydraulic brakes, factory-mounted	7	63098-08	
Rubber sealed/non-lubricant ball bearings	Add. price per machine	63067-73	
Cast steel rings*			
510mm / 22.5" Cambridge / 500 mm 2D Corrugated rings in cast-steel quality with 8 spokes. Is recommended in a non-ploughed system and in extreme conditions.	+10 kg per m	690150078	
	Add. price per m		

* 8-year warranty on cast steel rings