

VIP-ROLLER



- Compact construction of sectional tubes.
- Low transport height – stable and safe transport.
- Simple transfer between transport and working position.
- Hydraulic system released during transport/storage.
- 60 mm axles, special quality, & double sealed ball bearings.

PRICES & SPECIFICATIONS

Transport width of max. 2.45 m.

Working Width	Ring Type	No. of Spokes	No. of Rings	Weight kg	Power Req., HP	Item Number	
*3.30 m	450 mm/18" Cambridge	3	63	1,410	40-60	63060-45	
	510 mm/21" Cambridge	3	63	1,500	40-60	63060-51	
	510 mm/21" Cambridge	5		1,739	40-60	63060-46	
	560 mm/22.5" Cambridge	9	63	1,830	40-60	63060-54	
	450/500 mm Star ring	◆	66	1,520	40-60	63060-56	
	550 mm/22" Cam		22	1,090	40-60	63060-55	
	485-530 mm Crosskill		33	1,430	40-60	63060-53	
	500 mm 2D-Corrugated	8	41	1,470	40-60	63060-50	
	550 mm 2D-Corrugated	9	41	1,730	40-60	63060-59	
*3.70 m	450 mm/18" Cambridge	3	71	1,530	45-65	63061-45	
	510 mm/21" Cambridge	3	71	1,640	45-65	63061-51	
	510 mm/21" Cambridge	5	71	1,910	45-65	63061-46	
	560 mm/22.5" Cambridge	9	71	2,000	45-65	63061-54	
	450/500 mm Star ring	◆	74	1,670	45-65	63061-56	
	550 mm/22" Cam		25	1,150	45-65	63061-55	
	485-530 mm Crosskill		37	1,570	45-65	63061-53	
	500 mm 2D-Corrugated	8	46	1,610	45-65	63061-50	
	550 mm 2D-Corrugated	9	46	1,900	45-65	63061-59	
*4.10 m	450 mm/18" Cambridge	3	79	1,740	50-70	63062-45	
	510 mm/21" Cambridge	3	79	1,870	50-70	63062-51	
	510 mm/21" Cambridge	5	79	2,170	50-70	63062-46	
	560 mm/22.5" Cambridge	9	79	2,260	50-70	63062-54	
	450/500 mm Star ring	◆	82	1,890	50-70	63062-56	
	550 mm/22" Cam		28	1,330	50-70	63062-55	
	485-530 mm Crosskill		41	1,780	50-70	63062-53	
	500 mm 2D-Corrugated	8	51	1,830	50-70	63062-50	
	550 mm 2D-Corrugated	9	51	2,160	50-70	63062-59	
*4.50 m	450 mm/18" Cambridge	3	87	1,860	60-80	63063-45	
	510 mm/21" Cambridge	3	87	2,020	60-80	63063-51	
	510 mm/21" Cambridge	5	87	2,190	60-80	63063-46	
	560 mm/22.5" Cambridge	9	87	2,450	60-80	63063-54	
	450/500 mm Star ring	◆	90	2,050	60-80	63063-56	
	550 mm/22" Cam		30	1,420	60-80	63063-55	
	485-530 mm Crosskill		45	1,890	60-80	63063-53	
	500 mm 2D-Corrugated	8	57	1,910	60-80	63063-50	
	550 mm 2D-Corrugated	9	57	2,140	60-80	63063-59	

* The machine requires 1 single-acting & 1 double-acting oil outlet.

◆ Cast steel ring.

Working Width	Ring Type	No of Spokes	No. of Rings	Weight kg	Power Req., HP	Item Number	
*5.40 m	450 mm/18" Cambridge	3	105	2,210	70-90	63064-45	
	510 mm/21" Cambridge	3	105	2,450	70-90	63064-51	
	510 mm/21" Cambridge	5	105	2,600	70-90	63064-46	
	560 mm/22.5" Cambridge	9	105	3,020	70-90	63064-54	
	450/500 mm Star ring	♦	108	2,520	70-90	63064-56	
	550 mm/22" Cam		36	1,790	70-90	63064-55	
	485-530 mm Crosskill		54	2,300	70-90	63064-53	
	500 mm 2D-Corrugated	8	69	2,340	70-90	63064-50	
	550 mm 2D-Corrugated	9	69	2,880	70-90	63064-59	
*6.30 m	450 mm/18" Cambridge	3	123	2,640	80-100	63065-45	
	510 mm/21" Cambridge	3	123	2,830	80-100	63065-51	
	510 mm/21" Cambridge	5	123	3,040	80-100	64065-46	
	560 mm/22.5" Cambridge	9	123	3,610	80-100	64065-54	
	450/500 mm Star ring	♦	126	2,890	80-100	63065-56	
	550 mm/22" Cam		42	2,000	80-100	63065-55	
	485-530 mm Crosskill		63	2,670	80-100	63065-53	
	500 mm 2D-Corrugated	8	78	2,730	80-100	63065-50	
	550 mm 2D-Corrugated	9	78	3,140	80-100	63065-59	
*7.30 m	450 mm/18" Cambridge	3	143	3,220	85-105	63066-45	
	510 mm/21" Cambridge	3	143	3,490	100-120	63066-51	
	510 mm/21" Cambridge	5	143	3,720	100-120	63066-46	
	560 mm/22.5" Cambridge	9	143	4,190	100-120	63066-54	
	450/500 mm Star ring	♦	146	3,590	100-120	63066-56	
	550 mm/22" Cam		48	2,520	85-105	63066-55	
	485-530 mm Crosskill		73	3,300	100-120	63066-53	
	500 mm 2D-Corrugated	8	90	3,380	90-110	63066-50	
	550 mm 2D-Corrugated	9	90	3,750	90-110	63066-59	
*8.20 m	450 mm/18" Cambridge	3	161	3,530	100-120	63166-45	
	510 mm/21" Cambridge	3	161	3,790	120-140	63166-51	
	510 mm/21" Cambridge	5	161	3,980	120-140	66166-46	
	450/500 mm Star ring	♦	164	3,820	120-140	63166-56	
	550 mm/22" Cam		55	2,790	100-120	63166-55	
	485-530 mm Crosskill		82	3,610	120-140	63166-53	
	500 mm 2D-Corrugated	8	102	3,690	110-130	63166-50	

*The machine requires 1 single-acting & 1 double-acting oil outlet. ♦ Cast steel ring.

STANDARD EQUIPMENT

- Adjustable jack stand.
- Parking device for hydr. hoses
- Double sealed ball bearings.
- Towing eye, secured by bolts, item no. 630757028, page 111.
- Wheels:
 - 3.30m to 4.50m: 10.0/80 x 12, 10 PLY.
 - 5.40m & 6.30m: 10.0/75 x 15.3, 10 PLY.
 - 7.30m & 8.20m: 11.5/80 x 15.3, 10 PLY.

EXTRA EQUIPMENT

The Spring-Board cannot be mounted on the Vip-Roller.

Designation	Weight	Item no.	
Lights, complete with wire and socket, mounted	3 kg	63060-01	
Mechanical double change-over valve, mounted on drawbar, for tractors with only one double-acting oil outlet	5 kg	690207102	
3.00m Wheel track eradicator set, three-point mounted to the tractor, 6 tines.	200 kg	67701-00	
4.00m Wheel track eradicator set, three-point mounted to the tractor, 8 tines.	280 kg	67702-00	
Stone box set (2 pieces) for 3.3 / 3.7 / 4.1 & 4.5 m	32 kg	630555000	
Stone box set (2 pieces) for 5.4 / 6.3 / 7.3 & 8.2 m	32 kg	630555001	
Air brakes, factory-mounted	18 kg	63098-07	
Hydraulic brakes, factory-mounted	7 kg	63098-08	