

DISC-ROLLER CLASSIC Three-point mounted



- Sabre disc" 510 mm large scalloped disc with specially designed coulter profile - thus ensuring an improved cutting of surface stubble preparation.
- Maintenance-free disc-hubs.
- DSD – Technology: **Depth Synchronised Disc-Aggressiveness**.
- Available with 600 mm V-Profile rings. Makes the Disc-Roller Classic suitable for stubble cultivations, seed bed preparations or land packing after ploughing.
- Available with 600 mm Waveroller that is good for carrying up the machine's weight on light and loose soil.
- Available with 550 mm Square tube roller made of strong sectional tubes.
- This roller is good on loose soil and it is reducing the lifting requirement.

PRICES & SPECIFICATIONS

Working Width	Roller Type / Diameter	No. of Rings	Weight kg	No. of Discs	Power Req., HP	Item Number	
Rigid, 1 section, without hydraulic folding							
2.50m	Square tube roller/550mm		1260	18	90 +	63090-45	
	Waveroller /600mm	20	1560	18	90 +	63090-73	
	V-Profile ring /600mm	16	1780	18	90 +	63090-60	
3.00m	Square tube roller/550mm		1460	22	100 +	63091-45	
	Waveroller /600mm	24	1810	22	100 +	63091-73	
	V-Profile ring /600mm	20	2080	22	100 +	63091-60	
3.50m	Square tube roller/550mm		1670	26	110 +	63096-45	
	Waveroller /600mm	28	2125	26	110 +	63096-73	
	V-Profile ring /600mm	23	2395	26	110 +	63096-60	
4.00m	Square tube roller/550mm		1.880	30	120 +	63092-45	
	Waveroller /600mm	32	2.440	30	120 +	63092-52	
	V-Profile ring /600mm	26	2.710	30	120 +	63092-50	
2 sections, with hydraulic folding							
**4.00m	Waveroller /600mm	32	2760	30	120 +	63092-73	
	V-Profile ring /600mm	26	3120	30	120 +	63092-60	
**5.00 m	Waveroller /600mm	40	3290	38	150 +	63093-73	
	V-Profile ring /600mm	32	3750	38	150 +	63093-60	

** The machine requires two double-acting oil outlets.

STANDARD EQUIPMENT FOR DISC-ROLLER CLASSIC

- Mechanical adjustment of working depth on 1-section models
- Hydraulic adjustment of working depth on 2-section models
- Edge equipment with disc for retain soil on right side.
- Scraper between the rings.
- 60 mm axels fitted with 60 mm double-sealed ball bearings.

EXTRA EQUIPMENT

Designation	Weight kg	Item no.	
LED lights w/wire & socket, mounted on 2.50, 3.00 & 3.50 m rigid	3	63091-01	
LED lights w/wire and socket, mounted on 4.00 & 5.00 m foldable	3	63092-01	
Electrical depth stop for 2.50, 3.00 & 3.50 – rigid	4	63091-85	
Electrical depth stop for 4.00 & 5.00 m – foldable	8	63092-85	
Hydr. adjustment of working depth and disc angle for 2,50 – 4,00 rigid models	-	63092-92	
Material damper guard 2.50 m 1 section	50	63090-98	
Material damper guard 3.00 m 1 section	60	63091-98	
Material damper guard 3.50 m 1 section	70	63096-98	
Material damper guard 4.00 m 2 sections	80	63092-98	
Material damper guard 5.00 m 2 sections	100	63093-98	
Trailed kit for 2.50, 3.00 & 3,50 m rigid models, 11,5/80x15.3	550	63091-55	
Trailed kit for 4.00 & 5.00 m foldable models, 400/60x15.3	560	63092-55	
Rubber sealed/non-lubricant ball bearings(2,50-3,50m)	Add. price/set	-	63090-02
Rubber sealed/non-lubricant ball bearings(4,00-5,00m)	Add. price/set	-	63090-04
Mounting set f/Multi-Seeder, incl. mounting on a new Disc-Roller. Max. 200 kg seeds in the seed hopper. Prices and info. about Multi-Seeder, please look at page 98.	Models	8 outlets	
	2.50 m rigid		63090-12
	3.00 m rigid		63091-12
	3.50 m rigid		63096-12
	4,00 m rigid		63092-12
	4.00 m foldable		63092-16
	5.00 m foldable		63093-16

DISC-ROLLER CLASSIC Trailed



5,00 m w/V-Profile ring & material-damper guard.



- “Sabre disc” 510 mm large scalloped disc with specially designed coulter profile – thus ensuring an improved cutting of surface stubble preparation.
- Maintenance-free disc-hubs.
- DSD – Technology: **Depth Synchronised Disc-Aggressiveness**.
- Available with 600 mm V-Profile rings where you have the most versatility implement with a high own weight. Good for stubble cultivations, seed bed preparations or land packing after ploughing.
- Available with 600 mm Waveroller that is good for carrying up the machine’s weight on light and loose soil.

PRICES & SPECIFICATIONS

Working Width	Roller Type / Diameter	No. of Rings	Weight kg	No. of Discs	Power Req., HP	Item Number	
Rigid, 1 section, without hydraulic folding							
3.00 m	Waveroller /600mm	24	2360	22	100 +	63091-72	
	V-Profile ring /600mm	20	2630	22	100 +	63091-64	
3.50 m	Waveroller /600mm	28	2670	26	110 +	63096-72	
	V-Profile ring /600mm	23	2945	26	110 +	63096-64	
4.00 m	Waveroller /600mm	32	2990	30	120 +	63092-47	
	V-Profile ring /600mm	26	3260	26	120 +	63092-48	
2 sections, with hydraulic folding							
***4.00 m	Waveroller /600mm	32	3320	30	120 +	63092-72	
	V-Profile ring /600mm	26	3680	30	120 +	63092-65	
***5.00 m	Waveroller /600mm	40	3850	38	150 +	63093-72	
	V-Profile ring /600mm	32	4300	38	150 +	63093-65	

***The machine requires three double-acting oil outlets

STANDARD EQUIPMENT

- Mechanical adjustment of working depth on 1-section models
- Hydr. adjustment of working depth on 2-section models
- Adjustable drawbar height with parking device for hydraulic hoses.
- Edge equipment with disc for retain soil on right side.
- Scraper between the rings.
- 60 mm axels, fitted with 60 mm double-sealed ball bearings on all models.
- Wheel mounting:
 - 3.00-3,50 m, 1 section: 11.5/80x 15.3 - 10 PLY.
 - 4,00-5,00 m 2 sections: 400/60 x 15.5 - 14 PLY.
- Pivotal towing eye, secured by bolts: 3.00 – 5.00 m, item no. 630757028, look at page 111.

EXTRA EQUIPMENT FOR DISC-ROLLER CLASSIC

Designation		Weight	Item no.	
LED lights w/wire & socket, mounted on 2.50, 3.00 & 3.50 m rigid		3	63091-01	
LED lights w/wire and socket, mounted on 4.00 & 5.00 m foldable		3	63092-01	
Electrical depth stop for 3.00 m - 4.00 m – rigid		4 kg	63091-85	
Electrical depth stop for 4.00 m - 5.00 m – foldable		8 kg	63092-85	
Drawbar extension, 300 mm for bolting on for 3.00 m – 5.00 m		25 kg	63091-95	
Air brakes complete 3.00 m - 5.00 m		18 kg	63093-96	
Hydraulic brakes 3.00 m - 5.00 m		7 kg	63093-94	
Hydr. adjustment of working depth and disc angle for 2,50 – 4,00 rigid models		-	63093-93	
Material damper guard 3.00 m 1 section		60 kg	63091-98	
Material damper guard 3.50 m 1 section		70 kg	63096-98	
Material damper guard 4.00 m 2 sections		80 kg	63092-98	
Material damper guard 5.00 m 2 sections		100 kg	63093-98	
Rubber sealed/non-lubricant ball bearings(2,50-3,50m) Add. price/set		-	63090-02	
Rubber sealed/non-lubricant ball bearings(4,00-5,00m) Add. price/set		-	63090-04	
Working Width	Weight	** Spring-Board	**Spring-Board w/slicing plates	Transverse Locking System
*3.00 m rigid, 1 section	280 kg	63391-00	63791-00	63491-00
*3.50 m rigid, 1 section	325 kg	63396-00	63796-00	63496-00
*4.00 m hydr., 1- and 2-sections	375 kg	63592-00	63892-00	63692-00
*5.00 m hydr., 2 sections	450 kg	63593-00	63893-00	63693-00
Edge equipment for Spring-Board tines, 5 kg				63301-00
Recommendable Set of pivoting support wheels, mounted in front, height adjustable. Wheels: 2x300/65x12 - 8 PLY			Weight	Item no.
For 3.00 - 5.00 m trailed models			140 kg	63091-07
For 3.00 - 5.00 m trailed models w/Spring-Board			180 kg	63091-08
* Mounting set for Multi-Seeder, incl. mounting on a new Disc-Roller. The mounting set includes hydraulic lifting of driving wheel for turn on/off of seeding. Max. 200 kg seeds in the seed hopper. Prices & info. about Multi-Seeder, please look at page 98.	Models	8 outlets	16 outlets	
	3.00 m rigid	63091-14		
	3.50 m rigid	63096-14		
	4,00 m rigid	63092-14		
	4.00 - 5.00m foldable	63092-18		
	4.00 - 5.00m foldable		63092-19	

* The equipment requires one additional double-acting oil outlet.

** Drawbar extension is recommended, when the tractor is equipped with twin wheels.