

# DISC-ROLLER XL CONTOUR

Three-point mounted



- Sabre disc" 610 x 6 mm large scalloped disc with specially designed coulter profile – thus ensuring an improved cutting of surface stubble preparation.
- Maintenance-free disc-hubs.
- "DSD - Technology": Depth Synchronized Disc-Aggressiveness.

## PRICES & SPECIFICATIONS, 1-section

Transport width = model designation

Mo-del	Roller type / Diameter	No. of rings	Weight kg	No. of disc	Power req., HP	Working width m	Item number
*2.50 m	Square tube roller / 550 mm	-	1,260	18	80 +	2.25	6301000
	Wave roller / 600 mm	16		18	80 +	2.25	6301001
	U-Profile / 600 mm	16		18	90 +	2.25	6301002
	V-Profile / 600 mm	16	1,780	18	90 +	2.25	6301003
	V-Profile / 700 mm	16		18	90 +	2.25	6301004
	Twin U-Profile 600-600 mm	16		18	90 +	2.25	6301005
	Twin V-Profile 600-600 mm	16		18	90 +	2.25	6301006
	Twin V-Profile 700-700 mm	16		18	90 +	2.25	6301007
*3.00 m	Square tube roller / 550 mm	-	1,460	22	90 +	2.75	6301100
	Wave roller / 600 mm	20		22	90 +	2.75	6301101
	U-Profile / 600 mm	20		22	100 +	2.75	6301102
	V-Profile / 600 mm	20	2,080	22	100 +	2.75	6301103
	V-Profile / 700 mm	20	2,260	22	100 +	2.75	6301104
	Twin U-Profile 600-600 mm	20		22	100 +	2.75	6301105
	Twin V-Profile 600-600 mm	20		22	100 +	2.75	6301106
	Twin V-Profile 700-700 mm	20		22	100 +	2.75	6301107
*3.50 m	Square tube roller / 550 mm	-	1,670	26	100 +	3.25	6301200
	Wave roller / 600 mm	23		26	100 +	3.25	6301201
	U-Profile / 600 mm	23		26	110 +	3.25	6301202
	V-Profile / 600 mm	23	2,395	26	110 +	3.25	6301203
	V-Profile / 700 mm	23	2,605	26	110 +	3.25	6301204
	Twin U-Profile 600-600 mm	23		26	110 +	3.25	6301205
	Twin V-Profile 600-600 mm	23		26	110 +	3.25	6301206
	Twin V-Profile 700-700 mm	23		26	110 +	3.25	6301207
*4.00 m	Square tube roller / 550 mm	-	1,880	30	110 +	3.75	6301300
	Wave roller / 600 mm	26		30	110 +	3.75	6301301
	U-Profile / 600 mm	26		30	120 +	3.75	6301302
	V-Profile / 600 mm	26	2,710	30	120 +	3.75	6301303
	V-Profile / 700 mm	26	2,950	30	120 +	3.75	6301304
	Twin U-Profile 600-600 mm	26		30	120 +	3.75	6301305
	Twin V-Profile 600-600 mm	26		30	120 +	3.75	6301306
	Twin V-Profile 700-700 mm	26		30	120 +	3.75	6301307

\* Requires 1 double-acting oil outlet.

## STANDARD EQUIPMENT

- Hydraulic adjustment of working depth.
- Edge equipment with disc for retain soil on right side.
- Scraper between the rings.
- 60 mm axels fitted with 60 mm double-sealed ball bearings.

# DISC-ROLLER XL CONTOUR Trailed



- Sabre disc" 610 x 6 mm large scalloped disc with specially designed coulter profile – thus ensuring an improved cutting of surface stubble preparation.
- Maintenance-free disc-hubs.
- "DSD - Technology": **Depth Synchronized Disc-Aggressiveness**.

## PRICES & SPECIFICATIONS

### Trailed models – 1-section

Transport width = model designation

Model	Roller type / Diameter	No. of rings	Weight kg	No. of disc	Power req., HP	Working widthm	Item number
**2.50 m	Wave roller / 600 mm	16		18	80 +	2.25	6301021
	U-Profile / 600 mm	16		18	90 +	2.25	6301022
	V-Profile / 600 mm	16	2,330	18	90 +	2.25	6301023
	V-Profile / 700 mm	16	2,510	18	90 +	2.25	6301024
	Twin U-Profile 600-600 mm	16	2,320	18	90 +	2.25	6301025
	Twin V-Profile 600-600 mm	16	2,610	18	90 +	2.25	6301026
	Twin V-profile 700-700 mm	16		18	90 +	2.25	6301027
**3.00 m	Wave roller / 600 mm	20		22	100 +	2.75	6301121
	U-Profile / 600 mm	20		22	100 +	2.75	6301122
	V-Profile / 600 mm	20	2,630	22	100 +	2.75	6301123
	V-Profile / 700 mm	20	2,810	22	100 +	2.75	6301124
	Twin U-Profile 600-600 mm	20	2,620	22	100 +	2.75	6301125
	Twin V-Profile 600-600 mm	20	2,910	22	100 +	2.75	6301126
	Twin V-profile 700-700 mm	20		22	100 +	2.75	6301127
**3.50 m	Wave roller / 600 mm	23		26	100 +	3.25	6301221
	U-Profile / 600 mm	23		26	110 +	3.25	6301222
	V-Profile / 600 mm	23	2,945	26	110 +	3.25	6301223
	V-Profile / 700 mm	23	3,155	26	110 +	3.25	6301224
	Twin U-Profile 600-600 mm	23	2,930	26	110 +	3.25	6301225
	Twin V-Profile 600-600 mm	23	3,240	26	110 +	3.25	6301226
	Twin V-profile 700-700 mm	23		26	110 +	3.25	6301227
**4.00 m	Wave roller / 600 mm	26		30	110 +	3.75	6301321
	U-Profile / 600 mm	26		30	120 +	3.75	6301322
	V-Profile / 600 mm	26	3,260	30	120 +	3.75	6301323
	V-Profile / 700 mm	26	3,500	30	120 +	3.75	6301324
	Twin U-Profile 600-600 mm	26	3,240	30	120 +	3.75	6301325
	Twin V-Profile 600-600 mm	26	3,570	30	120 +	3.75	6301326
	Twin V-profile 700-700 mm	26		30	120 +	3.75	6301327

\*\* Requires 2 double-acting oil outlets.

## Trailed models – 2 & 3-sections

Transport width:

model 4,50: 2,42 m

model 5,50 / 6,50: 2,62 m


Model	Roller type / Diameter	No. of rings	Weight kg	No. of disc	Power req., HP	Working width m	Item number
<b>2-section with hydraulic folding</b>							
***4.50 m	Wave roller / 600 mm	30		34	130 +	4.25	6301421
	U-Profile / 600 mm	30		34	140 +	4.25	6301422
	V-Profile / 600 mm	30	4,030	34	140 +	4.25	6301423
	V-Profile / 700 mm	30		34	140 +	4.25	6301424
	Twin U-Profile 600-600 mm	30	4,010	34	140 +	4.25	6301425
	Twin V-Profile 600-600 mm	30	4,340	34	140 +	4.25	6301426
	Twin V-profile 700-700 mm	30		34	140 +	4.25	6301427
***5.50 m	Wave roller / 600 mm	36		42	160 +	5.25	6301521
	U-Profile / 600 mm	36		42	170 +	5.25	6301522
	V-Profile / 600 mm	36	4,770	42	170 +	5.25	6301523
	V-Profile / 700 mm	36		42	170 +	5.25	6301524
	Twin U-Profile 600-600 mm	36	4,740	42	170 +	5.25	6301525
	Twin V-Profile 600-600 mm	36	5,090	42	170 +	5.25	6301526
	Twin V-profile 700-700 mm	36		42	170 +	5.25	6301527
<b>3-section with hydraulic folding (2 disc sections and 3 roller sections)</b>							
***6.50 m	Wave roller / 600 mm	42		50	190 +	6.25	6301621
	U-Profile / 600 mm	42		50	200 +	6.25	6301622
	V-Profile / 600 mm	42	5,510	50	200 +	6.25	6301623
	V-Profile / 700 mm	42		50	200 +	6.25	6301624
	Twin U-Profile 600-600 mm	42	5,990	50	200 +	6.25	6301625
	Twin V-Profile 600-600 mm	42	5,860	50	200 +	6.25	6301626
	Twin V-profile 700-700 mm	42		50	200 +	6.25	6301627
***7.50 m	Wave roller / 600 mm	48		58	190 +	7.25	6301721
	U-Profile / 600 mm	48		58	240 +	7.25	6301722
	V-Profile / 600 mm	48	5,510	58	240 +	7.25	6301723
	V-Profile / 700 mm	48		58	240 +	7.25	6301724
	Twin U-Profile 600-600 mm	48	5,990	58	240 +	7.25	6301725
	Twin V-Profile 600-600 mm	48	5,860	58	240 +	7.25	6301726
	Twin V-profile 700-700 mm	48		58	240 +	7.25	6301727

\*\*\* Requires 3 double-acting oil outlets.

## STANDARD EQUIPMENT

- **HE-VA SAT-System** on models with 2-sections: hydr.adjustable weight transfer system ensuring equal weight transfer in the total working width.
- Hydr. adjustment of the working depth, at the same time used for lifting of “disc” on headland
- Adjustable drawbar height with distance clips and parking device for hydraulic hoses.
- Adjustable edge disc for retain soil on right side.
- Scraper between the rings, only on Single V & U-Profile roller as well as Wave roller.
- 60 mm axels, fitted with 60 mm double-sealed ball bearings on all models.
- Wheel mounting:
  - 2.50 -4.50 m 400/60 x 15,5 – 14 PLY
  - 5.50, 6.50 & 7.50 m: 520/50 – 17 SG Flotation
- Pivotal towing eye, secured by bolts:
  - 2.50 – 4.00 m, item no. 630757028, see page 111
  - 4.50 – 7,5.00 m, item no. 630757017, see page 111


## EXTRA EQUIPMENT – DISC-ROLLER XL *Contour*

Designation		Weight	Item no.		
* <b>In line - system</b> for all 1- and 2-sections models. Hydraulic adjustment of the machines parallelism with the soil surface during work from tractor cab – by means of Memory cylinder.		-	6301956		
LED lights w/wire and socket, for 1-section three-point mounted models		3 kg	63090-01		
LED lights w/wire and socket, for 1-sections trailed models		3 kg	64512-70		
LED lights w/wire and socket, for 2-section trailed models		3 kg	3401951		
LED lights w/wire and socket, for 3-sections trailed models		3 kg	6301939		
HPV-Controller: El-hydr. operation of 4 functions		7 kg	3409430		
Electrical depth stop for 2.50 – 4.00 m		4 kg	6301945		
Electrical depth stop for 4.50 – 5.50 m		4 kg	6301946		
Electrical depth stop for 6.50 – 7.50 m		4 kg	6301947		
Drawbar extension, 300 mm M16 for bolting on for 2.50 – 4.00 m		25 kg	6301950		
Drawbar extension 400 mm M20 for 4.50 – 7.50 m		31,5 kg	6301951		
Wheel 500/50x17-18 PLY f/ 3.50, 4.00 & 4.50 m		<b>Add. price per set</b>	3409750		
Trailed kit for 2.50 & 4.00 m rigid models, 400/60x15,5			6301910		
Air brakes complete 2.50 - 5.50 m		18 kg	6301900		
Air brakes complete 6.50 - 7.50 m		18 kg	6301901		
Hydraulic brakes 2.50 - 5.50 m		7 kg	6301905		
Hydraulic brakes 6.50 - 7.50 m		7 kg	6301906		
Material damper guard 2.50 m 1-section		50 kg	63090-98		
Material damper guard 3.00 m 1-section		60 kg	63091-96		
Material damper guard 3.50 m 1-section		70 kg	63096-96		
Material damper guard 4.00 m 1-section		80 kg	63092-96		
Material damper guard 4.50 m 2-sections		105 kg	63092-97		
Material damper guard 5.50 m 2-sections		120 kg	63093-97		
Material damper guard 6.50 m 2-sections		125 kg	6301634		
Material damper guard 7.50 m 2-sections		160 kg	6301734		
<p><b>Long finger- after harrow, behind the roller</b></p> <p>Spindle adjustment of the working depth with the possibility of weight transfer. Mounted behind the transport wheels on the trailed models.</p> 		<b>Working width</b>	<b>Three-point mounted models</b>	<b>Trailed models</b>	
			<b>Item no.</b>	<b>Item no.</b>	
		2.50 m	6301035	6301036	
		3.00 m	6301135	6301136	
		3.50 m	6301235	6301236	
		4.00 m	6301335	6301336	
		4.50 m		6301436	
		5.50 m		6301536	
		6.50 m		6301636	
7.50 m		6301736			
<b>Trailed models: Working width</b>	<b>Weight</b>	<b>▲ Spring-Board</b>		<b>▲ Spring-Board w/slicing plates</b>	<b>Transverse locking sys. f/Spring-Board</b>
		<b>Item no.</b>		<b>Item no.</b>	<b>Item no.</b>
* 2.50 m fast, 1-sect.	240 kg	6301030		6301031	63490-00
* 3.00 m fast, 1- sect.	280 kg	6301130		6301131	63491-00
* 3.50 m fast, 1- sect.	325 kg	6301230		6301231	63496-00
* 4.00 m fast, 1- sect.	370 kg	6301330		6301331	63492-00
* 4.50 m hydr.,2-sect.	375 kg	6301430		6301431	63592-30
* 5.50 m hydr.,2-sect.	450 kg	6301530		6301531	63593-30
* 6.50 m hydr.,2-sect.	525 kg	6301630		6301631	6301632
* 7.50 m hydr.,2-sect.	775 kg	6301730		6301731	6301732
Edge equipment for Spring-Board tines					6301960
570 x 5 mm "Sabre discs" HD aggressive					<b>Add. price per m.</b> 6301961

\* The equipment requires 1 additional double-acting oil outlet.

▲ Drawbar extension is recommended, when the tractor is equipped with twin wheels.

## EXTRA EQUIPMENT – DISC-ROLLER XL *Contour*

Trailed models: ▲ Spring-Board w/ø16 mm Long finger tines		No. of tines	Weight kg	Item number	
	* 2.50 m rigid, 1-section	10	174 kg	6301033	
	* 3.00 m rigid, 1-section	12	201 kg	6301133	
	* 3.50 m rigid, 1-section	14	232 kg	6301233	
	* 4.00 m rigid, 1-section	16	264 kg	6301333	
	* 4.50 m hydr., 2-sections	18	256 kg	6301433	
	* 5.50 m hydr., 2-sections	22	305 kg	6301533	
	* 6.50 m hydr., 2-sections	26	354 kg	6301633	
	* 7.50 m hydr., 2-sections	32	564 kg	6301733	

\* The equipment requires 1 additional double-acting oil outlet.

▲ Drawbar extension is recommended, when the tractor is equipped with twin wheels.

Set of pivoting support wheels, mounted in front, height adjustable. Wheels: 2x300/65x12 - 8 PLY				Weight kg	Item no.	
For 2.50 – 6.50 m trailed models.				140	6301916	
For 2.50 – 7.50 m trailed models w/Spring-Board:				180	6301917	
Mounting set for Multi-Seeder incl. mounting on a new Disc- Roller XL <i>Contour</i> . Max. 200 kg seeds in the seed hopper. Prices & info. about Multi- Seeder on page 98.	Work. width	* Without AC / EC		With AC / EC		DKK
		Item no. 8 outlets	Item no. 16 outlets	Item no. 8 outlets	Item no. 16 outlets	
	2.50 m	6301037		6301039		
	3.00 m	6301137		6301139		
	3.50 m	6301237		6301239		
	4.00 m	6301337		6301339		
	4,50 m	6301437		6301439		
	5.50 m	6301537		6301539		
6.50 m		6301638		6301640		
7.50 m		6301738		6301740		

\* On trailed models: incl. hydr. Lifting of driving wheel for turn on/off of seeding, which requires 1 additional double-acting oil outlet.

Model	Item no.	
Rubber sealed/non-lubricant ball bearings, single roller (2,50–3,50 m)	<b>Add. price per set</b>	63090-03
Rubber sealed/non-lubricant ball bearings, double roller (2,50-3,50 m.)	<b>Add. price per set</b>	63090-05
Rubber sealed/non-lubricant ball bearings, single roller (4,00 m)	<b>Add. price per set</b>	63090-05
Rubber sealed/non-lubricant ball bearings, double roller (4,00 m)	<b>Add. price per set</b>	63090-08
Rubber sealed/non-lubricant ball bearings, single roller (4,50 – 5,50 m)	<b>Add. price per set</b>	63090-05
Rubber sealed/non-lubricant ball bearings, double roller (4,50 – 5,50 m)	<b>Add. price per set</b>	63090-08
Rubber sealed/non-lubricant ball bearings, single roller (6,50 – 7,50 m)	<b>Add. price per set</b>	63090-09
Rubber sealed/non-lubricant ball bearings, double roller (6,50 – 7,50 m)	<b>Add. price per set</b>	63090-11