

KING-ROLLER



King-Roller 15,30 m. mounted with 620mm/24" Cambridge rings.



- Strong frame construction of sectional tubes.
- Uncomplicated change-over between transport & working position when the tractor is stopped.
- All sections are centre suspended & mutually independent.
- **HE-VA SAT-System:** The weight balance system transfers the weight of the construction (drawbar, cylinder & wheel) on all 5 sections to ensure a uniform soil pressure in the entire working width.
- Compact & low – safe & stable transport.

PRICES & SPECIFICATIONS

Transport width: 3.00 m

Working width	Ring type	No of Spokes	No. of Rings	Weight kg	Power Req., HP	Item Number
12.30 m	510 mm/21" Cambridge	8	236	7708	170-200	63067-46
	560 mm/22.5 Cambridge	9	236	8593	170-200	63067-54
	620 mm/24" Cambridge	10	236	9360	190-220	63067-62
	450/500 mm Star ring	◆	244	7414	170-200	63067-56
	550/600 mm Star ring	◆	244	8683	190-220	63067-58
	485-530 mm Crosskill		125	7668	170-200	63067-53
	550-600 mm Crosskill		125	9043	170-200	63067-63
	500 mm 2D-Corrugated	8	150	7168	170-200	63067-50
	550 mm 2D-Corrugated	9	150	7310	180-210	63067-59
	600 mm 2D-Corrugated	10	150	8218	180-210	63067-60
15.30 m	510 mm/21" Cambridge	8	292	9260	180-230	63068-46
	560 mm/22.5 Cambridge	9	292	10931	180-230	63068-54
	620 mm/24" Cambridge	10	292	11880	200-250	63068-62
	450/500 mm Star ring	◆	302	8800	200-250	63068-56
	550/600 mm Star ring	◆	302	10370	200-250	63068-58
	485-530 mm Crosskill		153	8380	180-230	63068-53
	550-600 mm Crosskill		153	10068	180-230	63068-63
	500 mm 2D-Corrugated	8	187	7925	180-230	63068-50
	550 mm 2D-Corrugated	9	187	8680	190-240	63068-59
	600 mm 2D-Corrugated	10	187	9323	190-240	63068-60
16.30 m	510 mm/21" Cambridge	8	306	10241	190-240	63069-46
	560 mm/24" Cambridge	9	306	11365	210-260	63069-54
	620 mm/24" Cambridge	10	306	12360	210-260	63069-62
	450/500 mm Star ring	◆	316	9817	190-240	63069-56
	550/600 mm Star ring	◆	316	11460	210-260	63069-58
	485-530 mm Crosskill		163	9340	190-240	63069-53
	550-600 mm Crosskill		163	11130	190-240	63069-63
	500 mm 2D-Corrugated	8	199	9510	190-240	63069-50
	550 mm 2D-Corrugated	9	199	9650	200-250	63069-59
	600 mm 2D-Corrugated	10	199	10360	200-250	63069-60

¹Requires 3 double-acting oil outlets

◆ Cast steel ring, 8-year breakage warranty

Working Width	Ring Type	No of Spokes	No. of Rings	Weight kg	Power Req., HP	Item Number
18.30 m	510 mm/21" Cambridge	8	346	10.818	210-260	63071-46
	560 mm/22.5 Cambridge	9	346	12.675	230-280	63071-54
	620 mm/24" Cambridge	10	346	13.800	230-280	63071-62
	450/500 mm Star ring	♦	356	11.015	210-260	63071-56
	550/600 mm Star ring	♦	356	12.866	230-280	63071-58
	485-530 mm Crosskill		183	10.752	210-260	63071-53
	550-600 mm Crosskill		183	12.765	210-260	63071-63
	500 mm 2D-Corrugated	8	223	10.088	210-260	63071-50
	550 mm 2D-Corrugated	9	223	10.834	220-270	63071-59
	600 mm 2D-Corrugated	10	223	11.649	220-270	63071-60
20.30 m	510 mm/21" Cambridge	8	386	13.600	220-280	63070-46
	560 mm/22.5 Cambridge	9	386	14.280	240-300	63070-54
	450/500 mm Star ring	♦	396	12.618	220-280	63070-56
	485-530 mm Crosskill		203	13.494	220-280	63070-53
	500 mm 2D-Corrugated	8	248	12.770	220-280	63070-50
	550 mm 2D-Corrugated	9	248	12.944	240-300	63070-59

¹Requires 3 double-acting oil outlets.

♦ Cast steel ring, 8-year breakage warranty

STANDARD EQUIPMENT

- Wheels:
 - 550/45 x 22.5 - 16 PLY f/12.30 + 15.30 m
 - 560/45 R 22.5 – 152D f/16.30 + 18.30 + 20.30 m
- Pivotal towing eye, secured by bolts, item no. 630757046
- Hydraulic supporting leg.
- Parking device for hydraulic hoses.
- 60 mm shafts, special quality, mounted w/double-sealed ball bearings.
- Automatic lock system of the wing sections during transport.
- **HE-VA SAT-System:** Weight balance system on all 5 sections.
- Support bearings on all sections.

EXTRA EQUIPMENT

Designation	Weight	Item No.
♦ Cast steel rings		
510 mm/21" Cambridge / 500 mm 2D Corrugated rings in cast-steel quality with 8 points. Recommended in a non-ploughed system & in extreme conditions. Additional price per meter	+8 kg per m	690150078
560 mm/22.5" Cambridge / 550 mm 2D Corrugated rings in cast-steel quality with 9 points. Recommended in a non-ploughed system & in extreme conditions. Additional price per meter	+10 kg per m	690150077
620 mm/24" Cambridge / 600 mm 2D Corrugated rings in cast-steel quality with 10 points. Recommended in a non-ploughed system & in extreme conditions. Additional price per meter	+10 kg per m	690150118
LED lights complete with wire & socket, mounted	3 kg	63067-33
Air brakes, Tristop, factory-mounted for 12.30 – 15.30 models	18 kg	63067-35
Air brakes, Tristop, factory-mounted for 16.30 – 20.30 models	18 kg	63067-36
Hydr. Brakes, factory-mounted for 12.30 – 15.30 models	7 kg	63067-37
Hydr. Brakes, factory-mounted for 16.30 – 20.30 models	7 kg	63067-41
Stone box set (2 pieces)	32 kg	630555008
Mounting set f/Multi-Seeder, incl. mount. On a new King-Roller. Max. 200 kg seeds in fine seed hopper.	12.3m, 200 l	63067-15
	12.3m, 410 l	63067-20
	15.3m, 16.3m, 18.3 + 20.3m	-
Platform with railing & ladder for mounting set		63099-56
Rubber sealed/non-lubricant ball bearings	Add. price per machine	63067-73

♦ Cast steel ring, 8-year breakage warranty