

# COMBI-TILLER MKI



3,00 m three-point hitched Combi-Tiller MKI with 3,00 m three-point hitched Disc-Roller *Contour*.

- Infinitely variable depth control via a tine mounting from  $\pm 50$  till max. 400 mm or via the tractor's hydraulic system.
- Solid frame construction, 180x180x8 mm sectional tubes.
- Tine bracket bolted on, making it possible to change the tine spacing.
- Max. weight of mounted machine after the Combi-Tiller MKI: 4 tonnes

## PRICES

Model	Working width	No. of Tines	Weight kg	Row spacing cm	Item Number
Combi-Tiller MKI w/three-point linkage f/combination w/a lift mounted Disc-Roller <i>Contour</i> . Incl. 1 set of hydr. extension hoses, extension cord f/lights & spec. supporting legs f/Disc-Roller <i>Contour</i> .	2.50 m	4	505	57.5	64511-23
	3.00 m	5	560	56.0	64511-33
	3.00 m	6	595	46.7	64511-43
	3.50 m	6	615	55.0	64511-53
	3.50 m	7	650	47.1	64511-63
	4.00 m	7	670	54.3	64511-73
	4.00 m	8	705	47.5	64511-83
Combi-Tiller MKI with three-point linkage for combination w/several lift mounted & trailed implements. E.g. bed formers for potatoes or trailed drill units.	2.50 m	3	470	83.3	64511-22
	2.50 m	4	515	62.5	64511-24
	3.00 m	5	570	60.0	64511-34
	3.00 m	6	605	50.0	64511-44
	3.50 m	5	590	70.0	64511-54
	3.50 m	6	625	58.3	64511-55
	3.50 m	7	660	50.0	64511-64
	4.00 m	7	680	57.1	64511-74
	4.00 m	8	715	50.0	64511-84
<b>Extra equipment:</b> 1 set of support wheels, adjustable by spindles. <b>N.B.</b> Can't be mounted with twin wheels.					64519-30
Point with 120mm wing shares			<b>Price reduction per tine</b>		645000043A
Point with 350mm wing shares			<b>Additional price per tine</b>		645000063A
Points 200 mm with hard metal plate			<b>Additional price per tine</b>		645000044TA
Tine for retro mounting complete, short tine holder					64511-90
Tine for retro mounting complete, long tine holder					64511-91
<b>Easy Draft kit.</b> 15 mm tine w/120 mm wearing point "ED" with tungsten tip.			<b>Add. price per tine</b>		64511-15
			<b>Retro mount. per tine</b>		64511-18

## STANDARD EQUIPMENT

- Pins & locking pins.
- Shear bolt stone protection.
- Supporting leg.
- Point with 200 mm wing shares mounted with 25 wide tine.
- The tines can be adjusted in the tine spacing
- Top link

## SPECIFICATIONS

- Frame clearance: 560 – 860 mm
- Max. working depth: 400 mm
- Length from coupling point to coupling point (centre): 750 mm
- Tine staggering: 160 mm
- Power requirement (extra requirement in relation to Disc-Roller *Contour*): 25 hp per tine