

COMBI-SEEDER VF / VB (roller in front / roller behind)



4.00 m Combi-Seeder VF with disc coulters



Tramline computer



3.00 m Combi-Seeder VB

- Precise adjustment of harrow and seeding depth, adjustable on the roller and coulters pressure.
- VB – models have 4 rows of harrow tines with a row spacing of 12.5 cm.
- VB – models leave the field packed with a good structure.
- VF – models have only 10 cm row spacing for stronger preparation.
- VF – models are mounted with Spring-Board levelling plate, and the roller packs the soil before seeding.
- Funnel-shaped outlet – less seed in the machine (for till-seeding).
- Seeding w/half working width, switched off when disengaging half sowing axle.
- The seeds will run out from the bottom of the hopper – better distribution when operating in broken ground.
- Strong two-piece distribution plates (stainless steel + strong nylon) mounted on bushes.
- Infinitely variable calibration 1.5 (rape) - 400 kg/ha.
- 300 mm row spacing for seed coulters – ensures a better clearance.

MACHINES

COMBI-SEEDER VF - ROLLER IN FRONT					DISC COULTERS			TOWAGE COULTERS		
Work Width, m	Seed Hopper Volume, L	Type	No. of Coulters/Tines	Power Req., HP	Lifting Req., kg	Weight (empty), kg	Item Number	Lifting Req., kg	Weight (empty), kg	Item Number
3.00	1,000	Ø500 mm Square tube roller (□ -tube)	24/30	80-110	5,100	1,850	3223506	4,000	1,465	3223503
3.00	1,000	Ø540 mm Packer roller	24/30	90-120	6,100	2,235	3223507	4,700	1,720	3223504
3.00	1,000	Ø600 mm V-Profile roller	24/30	90-120	6,500	2,365	3223511	5,100	1,850	3223510
4.00	1,400	Ø500 mm Square tube roller (□ -tube)	32/40	100-140	6,400	2,340	3224506	5,200	1,865	3224503
4.00	1,400	Ø540 mm Packer roller	32/40	110-150	7,200	2,620	3224507	5,900	2,150	3224504
4.00	1,400	Ø600 mm V-Profile roller	32/40	110-150	7,750	2,820	3224511	6,450	2,350	3224510

COMBI-SEEDER VB - ROLLER BEHIND					TOWAGE COULTERS		
Work Width, m	Seed Hopper Volume, L	Type	No. of Coulters/Tines	Power Req., HP	Lifting Req., kg	Weight (empty), kg	Item Number
3.00	1,000	Ø500 mm Strong tube roller (O-tube) and Ø260 mm roller in front of seed coulters	24 / 24	90-120	4,000	1,800	4289932
3.00	1,000	Ø500 mm Strong tube roller (O-tube) and longfinger afterharrow in front of seed coulters	24 / 24	90-120	4,150	1,890	4289933
4.00	1,400	Ø500 mm Strong tube roller (O-tube) and Ø260 mm roller in front of seed coulters	32 / 32	110-150	4,900	2,200	4289942
4.00	1,400	Ø500 mm Strong tube roller (O-tube) and longfinger afterharrow in front of seed coulters	32 / 32	110-150	5,200	2,320	4289943

*All machines require 1 double-acting oil outlet.

STANDARD EQUIPMENT

- LED lights, pins and locking pins.
- Hydraulic marker set for vertical position – mounted on the harrow.
- Platform for inspection and filling.
- Infinitely variable oil bath gearbox – with 2 speed ratio.
- Strong edge tines for retain soil/edge equipment fitted in front of the roller.
- Disc coulters with max. 25 kg disc pressure
- Agitator and seed hopper empty indicator.
- Parking device for seed drill
- Electronic tramline computer with trip and ha control, optional tramline valves for 2 or 3 seed coulters per side – standard mounting: 175 cm track spacing
- Electronic alarm for empty seed hopper and dosing shaft rotation control.

Only VF:

- After-harrow model "Standard" (for towage coulters)
- 3 rows 10x32 mm tines.
- Spring-Board levelling bar - height adjustable via spindles.
- Disc coulters have as standard depth/packing wheels and material damper guard.
- Disc coulters with 350 mm discs and coulters pressure up to max. 50 kg per unit.

Only VB:

- 4 rows 10x32 mm tines
- Spring-loaded levelling bar w/tines, height - and angle adjustable via spindles.

EXTRA EQUIPMENT

Work Width, m	Description	Weight, kg	Item Number	
3.00	12 x 32 mm harrow tine (Additional price)	9	4299633	
3.00	Material damper guard with steel plate behind the roller, only for VF models	60	3260303	
4.00	12 x 32 mm harrow tine (Additional price)	12	4299634	
4.00	Material damper guard with steel plate behind the roller, only for VF models	80	3260304	
3.00 / 4.00	Hydraulic system for adjustment of levelling bar, only for VB-models	37	3229440	
3.00 / 4.00	Long tine eradicator for levelling bar, 5 cm longer. Only for VB models (Additional price each)	2	1034530	
3.00 / 4.00	Hydraulic lifting of sowing wheel	1*	12	3260222
3.00 / 4.00	Hydraulic coulters lifting via the seed drill's top link	1*	3	3260140
3.00 / 4.00	Visual tramlining in connection with tramline system – only for "VF"-models	35	3260150	
3.00 / 4.00	Hydraulic coulters pressure control, only for towage coulters	1*	7	3260130
3.00 / 4.00	Electrical seed rate control 0% or + 10%	3	P008612664030	

*The equipment requires 1 additional double-acting oil outlet.

MOUNTING SET FOR MULTI-SEEDER, INCL. MOUNTING ON A NEW COMBI-SEEDER. NB: ONLY FOR MODEL 200-8-EL/HY AC OR EC. PRICES AND INFORMATION ABOUT MULTI-SEEDER

Work Width, m	Weight, kg	Item Number
COMBI-SEEDER VF		
3.00	30	3260266
4.00	30	3260267
COMBI-SEEDER VB		
3.00	30	4290266
4.00	30	4290267