

KULTI-DAN



6.40 m Kulti-Dan with levelling board and longfinger-afterharrow



Kulti-Dan with combi-afterharrow

- Flexible seedbed harrow – can be trailed in working position by means of flex-pull.
- Great variety of equipment – the harrow can be adapted to all soil types.
- Rotor crumbler 315 mm - mounted with ball bearings (extra equipment).
- No clogging – approx. 40 cm bar spacing.
- Row spacing: 10 cm – optionally 8 cm.
- Small transport width: 2.40 m or 3.00 m.
- Adjustable tine angle in 4 different angles as required.

MACHINES

Work Width, m	Type	Power Req., HP	No. of Tines	No. of Tines per Section	Weight, kg	Item Number
2.20	Standard, rigid	25-35	22	22	370	2821000
2.80	Standard, rigid	35-45	28	28	423	2831000
3.40	Standard, manual folding	45-55	34	6 + 22 + 6	556	2834000
4.00	Standard, manual folding	50-60	40	6 + 28 + 6	609	2840000
4.60	Standard, hydraulic folding	^{1*} 60-75	46	12 + 22 + 12	761	2846000
5.20	Standard, hydraulic folding	^{1*} 70-90	52	12 + 28 + 12	819	2852000
5.80	Standard, hydraulic folding	^{1*} 80-90	58	18 + 22 + 18	897	2858000
6.40	Standard, hydraulic folding	^{1*} 80-100	64	18 + 28 + 18	955	2864000
7.00	Standard, hydraulic folding	^{1*} 90-110	70	21 + 28 + 21	1,013	2870000

^{1*}Requires 1 single-acting oil outlet

STANDARD EQUIPMENT

- 4 rows of harrow tines, 10x32 mm.
- Depth wheel with scraper:
 - 2.20 m to 4.00 m: 2 pcs. of 6.00 x 12.
 - 4.60 m to 7.00 m: 4 pcs. of 6.00 x 12.
- Manual folding on 3.40 and 4.00 m models from working position to transport position.
- Hydraulic folding from working position to transport position on 4.60-7.00 m models.
- Quick coupling with loose carrying shaft.
- The working angle of the tine is adjustable in 4 positions.
- Support stand, pins and locking pins.

EXTRA EQUIPMENT

- Levelling bar with adjustable working depth and spring stone protection.
- Long finger after-harrow is with adjustable depth and angle adjustment.
- Rotor crumbler with spring loaded weight transfer from the harrow.
- Flex-pull: Telescopic pull to a draw-bar during operation, pushed towards the tractor and locked before the harrow is lifted.
- Swing-pull: The tractor can turn in relation to the harrow during operation (loose drive bar).

Work Width, m	Description	Weight, kg	Item Number	
2.20	Levelling bar, complete with clamps	41	2894210	
2.20	Long finger after-harrow, complete with clamps	49	2897210	
2.20	Rotor crumbler, complete with clamps	135	2882211	
2.20	Combi-after-harrow, with complete clamps	160	2898821	
2.20	Double rotor crumbler, complete with clamps	195	2885211	
2.80	Levelling bar, complete with clamps	47	2894310	
2.80	Long finger after-harrow, complete with clamps	64	2897310	
2.80	Rotor crumbler, complete with clamps	158	2882311	
2.80	Combi-after-harrow, with complete clamps	189	2898831	
2.80	Double rotor crumbler, complete with clamps	231	2885311	
3.40	Levelling bar, complete with clamps	73	2894340	
3.40	Long finger after-harrow, complete with clamps	94	2897340	
3.40	Rotor crumbler, complete with clamps	235	2882341	
3.40	Combi-after-harrow, with complete clamps	275	2898834	
3.40	Double rotor crumbler, complete with clamps	328	2885341	
4.00	Levelling bar, complete with clamps	79	2894400	
4.00	Long finger after-harrow, complete with clamps	109	2897400	
4.00	Rotor crumbler, complete with clamps	258	2882401	
4.00	Combi-after-harrow, with complete clamps	304	2898840	
4.00	Double rotor crumbler, complete with clamps	362	2885401	
4.60	Levelling bar, complete with clamps	83	2894460	
4.60	Long finger after-harrow, complete with clamps	108	2897460	
4.60	Rotor crumbler, complete with clamps	271	2882461	
4.60	Combi-after-harrow, with complete clamps	321	2898846	
4.60	Double rotor crumbler, complete with clamps	388	2885461	
5.20	Levelling bar, complete with clamps	89	2894520	
5.20	Long finger after-harrow, complete with clamps	123	2897520	
5.20	Rotor crumbler, complete with clamps	294	2882521	
5.20	Combi-after-harrow, with complete clamps	350	2898852	
5.20	Double rotor crumbler, complete with clamps	415	2885521	
5.80	Levelling bar, complete with clamps	115	2894580	
5.80	Long finger after-harrow, complete with clamps	138	2897580	
5.80	Rotor crumbler, complete with clamps	318	2882581	
5.80	Combi-after-harrow, with complete clamps	380	2898858	
5.80	Double rotor crumbler, complete with clamps	450	2885581	
6.40	Levelling bar, complete with clamps	121	2894640	
6.40	Long finger after-harrow, complete with clamps	153	2897640	
6.40	Rotor crumbler, complete with clamps	341	2882641	
6.40	Combi-after-harrow, with complete clamps	409	2898864	
6.40	Double rotor crumbler, complete with clamps	490	2885641	
7.00	Levelling bar, complete with clamps	135	2894700	
7.00	Long finger after-harrow, complete with clamps	168	2897700	
7.00	Rotor crumbler, complete with clamps	398	2882701	
7.00	Combi-after-harrow, with complete clamps	460	2898870	
7.00	Double rotor crumbler, complete with clamps	535	2885701	
-	Flexible draw-bar for trailing in working position	155	2896400	
-	Pivot flex angle draw-bar – not for 5.80 / 6.40 / 7.00 m	62	2896500	
-	Hydr. folding for 22 tine centre-section models	1*	25	2892200
-	Hydr. folding for 28 tine centre-section models	1*	30	2892300
-	6 tine extension set, without hydraulic system	186	2802000	
-	12 tine extension set, without hydraulic system	366	2804000	
-	18 tine extension set, without hydraulic system	502	2806000	
-	Stronger tine 12x32 mm (Additional price per working width m)	36	2896800	
-	8 cm tine spacing (Additional price per working width m)	7.50	2896880	
-	Goose foot point 100 x 4 mm (Additional price per m)	-	2896820	
-	LED lights for machines with levelling bar/long finger after-harrow	-	2896390	
-	LED lights for machines with rotor crumbler/combi-after-harrow/double rotor crumbler	-	2896391	

*Requires 1 single-acting oil outlet