


LIFT-ROLLER



3.00 m with 510 mm/21" Cambridge.



- Draw-bar, free movable up/down.
- 60 mm bearings and shafts, special quality.
- Small lifting requirement – close to the tractor.

MACHINES

Work Width, m	Ring Type	No. of Rings	No. of Spokes	Power Req., HP	Lifting Req., kg	Weight, kg	Item Number
2.60	510 mm/21" Cambridge	45	3	40	1,400	930	63073-51
2.60	510 mm/21" Cambridge	45	8	40	1,400	1,101	63073-46
2.60	560 mm/22.5" Cambridge	45	9	45	1,630	1,160	63073-54
2.60	620 mm/24" Cambridge	45	10	45	1,880	1,250	63073-62
2.60	450/500 mm Star ring	• 42	-	45	1,470	980	63073-56
2.60	550/600 mm Star ring	• 42	-	45	1,850	1,230	63073-57
2.60	550 mm Cam ring	16	-	30	1,020	680	63073-55
2.60	485-530 mm Crosskill	25	-	40	1,100	730	63073-53
2.60	550-600 mm Crosskill	25	-	40	1,570	1,050	63073-63
2.60	500 mm 2D-Corrugated	31	8	40	1,250	830	63073-50
2.60	550 mm 2D-Corrugated	31	9	40	1,290	860	63073-59
2.60	600 mm 2D-Corrugated	31	10	45	1,320	880	63073-60
3.00	510 mm/21" Cambridge	53	3	55	1,590	1,060	63074-51
3.00	510 mm/21" Cambridge	53	8	55	1,590	1,261	63074-46
3.00	560 mm/22.5" Cambridge	53	9	60	1,910	1,320	63074-54
3.00	620 mm/24" Cambridge	53	10	60	2,150	1,430	63074-62
3.00	450/500 mm Star ring	• 50	-	60	1,670	1,110	63074-56
3.00	550/600 mm Star ring	• 50	-	60	2,100	1,400	63074-57
3.00	550 mm Cam ring	19	-	40	1,220	820	63074-55
3.00	485-530 mm Crosskill	27	-	55	1,250	830	63074-53
3.00	550-600 mm Crosskill	27	-	55	1,760	1,170	63074-63
3.00	500 mm 2D-Corrugated	35	8	55	1,380	920	63074-50
3.00	550 mm 2D-Corrugated	35	9	55	1,440	960	63074-59
3.00	600 mm 2D-Corrugated	35	10	60	1,480	990	63074-60

- Steel cast ring, 8 year breakage warranty

STANDARD EQUIPMENT

- Three-point mounting for cat. 2
- Support stand, pins and locking pins.

EXTRA EQUIPMENT



Description	Weight, kg	Item Number
Set of reflective warning boards (2 pieces)	-	67055-74
LED lights, complete with wire and socket, mounted	4	63003-01
Stone box set (2 pieces)	32	630555005

GRASS-SEEDER KIT

Work Width, m	Description	Item Number
2.60	230 mm adjustable plain roller behind the implement, adjustable longfinger harrow in front and mounting set for Multi-Seeder	63073-20
3.00	230 mm adjustable plain roller behind the implement, adjustable longfinger harrow in front and mounting set for Multi-Seeder	63074-20