


COMBI-TILLER PTO



4.00 m Combi-Tiller PTO with 5 tines.



Combi-Tiller PTO, hydr.

- Depth regulation in steps through mounting of tines from ± 50 to max. 400 mm or through the lift of the tractor.
- Solid frame construction, 180x180x8 mm sectional tubes.
- Max. weight of mounted machine after the Combi-Tiller PTO: 4 tonnes
- Frame clearance: 560 – 860 mm
- Max. working depth: 400 mm
- Length from coupling point to coupling point (centre): 790 mm
- Length from coupling point to coupling point (centre) on hydr. models: 920 mm

MACHINES

COMBI-TILLER PTO WITH TUNNEL FOR THROUGH POWER TAKE-OFF SHAFT

Work Width, m	Stone Protection	No. of Tines	Row Spacing, cm	Power Req., HP	Weight, kg	Item Number
2.50	Shear bolt	4	57.5 cm	100	560	64514-01
2.50	Hydraulic auto release	4	57.5 cm	100	690	64514-02
3.00	Shear bolt	4	75.0 cm	100	620	64514-05
3.00	Hydraulic auto release	4	75.0 cm	100	750	64514-06
3.50	Shear bolt	6	58.3 cm	150	760	64514-10
3.50	Hydraulic auto release	6	58.3 cm	150	930	64514-11
4.00	Shear bolt	6	66.6 cm	150	820	64514-15
4.00	Hydraulic auto release	6	66.6 cm	150	990	64514-16

STANDARD EQUIPMENT

- Pins and locking pins.
- Supporting leg.
- Point with 200 mm wing shares mounted with 25 wide tine.
- Top link
- Three-point linkage with cat. 3 pins and cat. 2 distance.

EXTRA EQUIPMENT

Description	Item Number
LED lights with wire and socket	64509-01
Set of reflective warning boards (2 pieces)	67055-74
Square tube roller incl. frame - for retro mounting on 2.50 m Combi-Tiller PTO	64514-20
Square tube roller incl. frame - for retro mounting on 3.00 m Combi-Tiller PTO	64514-21
Square tube roller incl. frame - for retro mounting on 3.50 m Combi-Tiller PTO	64514-22
Square tube roller incl. frame - for retro mounting on 4.00 m Combi-Tiller PTO	64514-23
Point with 120 mm wing shares (Price reduction per tine)	64500043A
Points 120 mm with hard metal plate (Additional price per tine)	64500043TA
Point with 350 mm wing shares (Additional price per tine)	64500063A
Points 200 mm with hard metal plate (Additional price per tine)	64500044TA
Easy-Draft kit. 15 mm tine w/120 mm wear point. ED with hard metal plate. Max working depth: 250 mm (Additional price per tine)	64511-15
Easy-Draft kit. 15 mm tine w/120 mm wear point. ED with hard metal plate. Max working depth: 250 mm (Retro mounting per tine)	64511-18
120 mm wear point for Easy-Draft, with hard metal plate in center + wings (Additional price per tine)	64500056TA
200 mm wear point for Easy-Draft, with hard metal plate in center (Additional price per tine)	64500054A
200 mm wear point for Easy-Draft, with hard metal plate in center + wings (Additional price per tine)	64500054TA
Tine reinforcement, hard metal 60x15x15 mm incl. factory-mounting on new tine. (Additional price per tine)	645000083
Lift with cat. 3 pins and cat. 3 distance.	64514-25

^{1*} Only relevant for Combi-Tiller PTO with hydr. auto-release system