

SUB-TILLER ECO





3.00 m with hydraulic auto-release system, 4 tines, Square tube roller and hydr. depth control.





3.00 m. with hydraulic auto-release system and 4 tines.

- Tine height under the frame 820 mm.
- Max. working depth 600 mm.
- Good clearance with a frame height of 820 mm.
- Strong frame construction, 180x180x8 mm sectional tubes.
- 3 stone protection types: Shear bolt, Quick-Push or Hydraulic automatic.
- Infinitely variable tine spacing, depending on the models and number of tines.
- For machines with roller:
 - Hydr. depth control for Square Tube Roller and V-Profile Roller. (Requires one double-acting oil outlet)

MACHINES

Work Width, m	Stone Protection	No. of Tines	Standard Row Spacing, cm			
				Without Roller	Square Tube Roller Ø550 mm	V-Profile Roller Ø600 mm
				Item Number	Item Number	Item Number
2.50	Quick-Push	2	180	64541-01	64542-01	64543-01
2.50	Quick-Push	3	90	64541-02	64542-02	64543-02
2.50	Hydr. auto.	2	180	64541-06	64542-06	64543-06
2.50	Hydr. auto.	3	90	64541-07	64542-07	64543-07
3.00	Quick-Push	2	200	64541-11	64542-11	64543-11
3.00	Quick-Push	3	100	64541-12	64542-12	64543-12
3.00	Quick-Push	4	75	64541-13	64542-13	64543-13
3.00	Hydr. auto.	2	200	64541-16	64542-16	64543-16
3.00	Hydr. auto.	3	100	64541-17	64542-17	64543-17
3.00	Hydr. auto.	4	75	64541-18	64542-18	64543-18
3.50	Quick-Push	5	70	64541-20	64542-20	64543-20
3.50	Hydr. auto.	5	70	64541-26	64542-26	64543-26

Work Width, m	Stone Protection	No. of Tines	Total Tine Spacing between Outer Tines, cm	Power Req., HP	Max HP			
						Without Roller	Square Tube Roller Ø550 mm	V-Profile Roller Ø600 mm
						Weight, kg		
2.50	Quick-Push	2	195	60-100	250	500	860	1,375
2.50	Quick-Push	3	195	90-120	250	580	940	1,445
2.50	Hydr. auto.	2	195	60-100	250	540	900	1,405
2.50	Hydr. auto.	3	195	90-120	250	630	990	1,495
3.00	Quick-Push	2	245	60-100	250	520	930	1,550
3.00	Quick-Push	3	245	90-120	250	600	1,010	1,630
3.00	Quick-Push	4	245	110-160	250	680	1,090	1,710
3.00	Hydr. auto.	2	245	60-100	250	580	990	1,610
3.00	Hydr. auto.	3	245	90-120	250	690	1,100	1,720
3.00	Hydr. auto.	4	245	110-160	250	810	1,220	1,840
3.50	Quick-Push	5	295	130-200	250	780	1,260	1,980
3.50	Hydr. auto.	5	295	130-200	250	900	1,380	2,100

*All models require 1 double-acting oil outlet

IMPORTANT: If a change of stated row spacing is wanted, please inform when placing an order.

STANDARD EQUIPMENT

- Hydr. depth control incl. depth scale for Square Tube Roller and V-Profile Roller.
- Three-point linkage with cat. 3 pins and cat. 2 distance.
- Supporting leg on machines without roller.
- For Quick-push stone protection: 8 steps per bolt.
- Scraper between the V-Profile rings.
- Points with 200 mm wing shares, mounted on 25 mm wide tine.

EXTRA EQUIPMENT

Description	Weight, kg	Item Number
Points with 120 mm wing shares (Price reduction per tine)	-	645000043A
Points 120 mm with hard metal plate (Additional price per tine)	-	645000043TA
Points with 350 mm wing shares (Additional price per tine)	-	645000063A
Points 200 mm with hard metal plate (Additional price per tine)	-	645000044TA
Easy-Draft kit. 15 mm tine w/120 mm wear point. ED with hard metal plate. Max working depth: 250 mm. Quick-Push stone protection (Additional price per tine)	-	64509-12
Easy-Draft kit. 15 mm tine w/120 mm wear point. ED with hard metal plate. Max working depth: 250 mm. Hydraulic auto release (Additional price per tine)	-	64509-09
Cat.II pins for three-point mounting	-	64509-08
Check valve (pilot-controlled) for hydr. depth control	-	64543-85
Set of reflective warning boards (2 pieces)	-	67055-74
LED lights complete w/wire and socket	3	64509-01
Tine for retro mounting complete, Quick-Push stone protection	85	64543-98
Tine for retro mounting complete, Hydr. stone protection	121	64543-99
Tine reinforcement, hard metal 60x25x15 mm incl. factory fitting on new tine. Recommended when tilling > 350 mm. (Additional price per tine)	-	645000085
Return circuit from release system. Recommended for difficult, rocky, extreme conditions. (Price per tine)	-	64509-54