


# RONDO-DAN



- Ideal for round bales of straw, hay, silage and similar materials.
- The three-point mounted bale-spikes collect the bale and place it on the unwinder table. Then it is used as quick-coupler for the table.
- Efficient for use in large barns, hen houses, feed alleys and on fields.
- Dustless and careful treatment of the straws.
- Model H + V has a roller on both sides and is able to unwind either to the right or to the left. The unwinding is controlled by the double-acting oil outlet on the tractor.

## MACHINES

Work Width, m	Model	Description	Unwinder Direction	Lifting Req., kg	Max. Weight of Bale, kg	Max. Bale Diameter, m	Max. Bale Width, m	Length, m	Weight, kg	Item Number
2.15	H	Rondo-Dan, complete with unwinding to the right	Right	1,100	850	1.80	1.50	2.00	577	2900201
2.15	V	Rondo-Dan, complete with unwinding to the left	Left	1,100	850	1.80	1.50	2.00	577	2900206
2.25	H + V	Rondo-Dan, complete w/ unwinding to the right or left	Right + left	1.200	850	1.80	1.50	2.00	660	2900211

## STANDARD EQUIPMENT

- Hydraulic motor with 35 mm shafts and claw coupling to the table.
- Unwinding roller with 5 tines.
- Safety railing around the platform.
- Three-point mounting with two integrated spikes.
- Pins and locking pins.



## EXTRA EQUIPMENT

Description	Item Number
Hydr. operation of the locking pawl for the unwinder table.	2900900
Quick-Change for EURO coupling. Three-point mounting	2900910
Quick-Change for New Holland. Three-point mounting	2900911
Quick-Change for JCB. Three-point mounting	2900912
Quick-Change for Manitou. Three-point mounting	2900913

<sup>1\*</sup>The equipment requires 1 additional double-acting oil outlet.