

FRONT-LIFT 25.01 - INTEGRATED



- Front-Lift with 2,500 kg lifting capacity with 190 bar.
- Integrated most possible for tractor with respect to design and space requirement.
- Individual lift arms with 4 possible positions: a) free moving b) limited moving c) locked position d) transport position.
- Good for 4 and 6 cylinder tractors with approx. 70 HP to 130 HP.
- Can be adapted to Front-PTO.

Type / Designation	Weight, kg	Item Number
25.01 without adapted side bracket bars	-	66500-00
Bolt brackets incl. bolts for 25.01	-	66500-01

STANDARD EQUIPMENT

- Single acting hydr. with air filter on lowering side.
- Cat. 2, DS/ISO 8759/1/2, 825 mm between the lift arms' balls.
- Cleaned and painted with a two-component primer and finally painted in the tractor's colour - also two-component.
- Adapted to the individual tractor model.
- Chassis bolts and 5.5 m hydr. hoses with couplings.
- Stop valve device on hydr. hose at tractor connection – the lift can then be locked.
- Quick-coupling for lift arms, cat. 2 with Ø28 mm balls.
- Top link M30 and Ø25 mm pin with parking device for the lift arms' balls.
- Parking device for top link.

EXTRA EQUIPMENT

Type / Designation	Weight, kg	Item Number
Accessory kit from single to double acting front-linkages, mount.	4	66595-00
Shock absorber kit incl. hoses and fittings, mounted	4	66585-00
Spring suspension kit incl. hoses and fittings, mounted	16	66590-00
Shift-Control Double, EI-shift between Front-Lift and one outlet	8	65100-10
Shift-Control Triple, EI-shift between Front-Lift and two outlets	14	65100-12
Double oil outlet on Front-Lift, with hoses from tractor outlet	9	65100-20
Holder for relief springs (per set)	7	667005001
Torsion bar	30	667003023
Quick coupling, cat. 3, with Ø28 mm or Ø36 mm balls	11	690106055