

FRONT-LIFT 21.01 - STANDARD



- Front-Lift with 2,100 kg lifting capacity with 175 bar.
- Short lift arms with 2 possible cylinder positions - providing a big lifting area.
- Good for tractors with 40 HP to 120 HP.
- Is not adapted to Front-PTO system.
- The Front-Lift is as standard supplied without "side bracket bars", however adapted side bracket bars can after option be supplied and made for almost all tractor models.

Type / Designation	Weight, kg	Item Number
21.01 single acting oil outlet, without side bracket bars	165	66050-00
Multi-Purpose side bracket bars, not adapted to lift, 2m long	100	66900-00

STANDARD EQUIPMENT

- Single acting hydr. with air filter on lowering side.
- Cat. 2 DS/ISO 8759/1/2. 825 mm between the lift arms' coupling points.
- Cleaned and painted with a two-component primer and finally painted in grey-black colour. If the lift is ordered with adapted side bracket bars, the lift will be painted in the tractor's colour.
- 5.5 m hydr. hoses with couplings.
- Stop valve device on hydr. hose at tractor connection – the lift can then be locked.
- Quick-coupling for lift-arms, cat. 2-S with Ø28 mm balls.
- Top link M30 and Ø25 mm balls and pins.
- Bolts for side bracket bars – for mounting on the front-lift.
- When ordering the lift with adapted side bracket bars, chassis bolts are included.

EXTRA EQUIPMENT

Type / Designation	Weight, kg	Item Number
Accessory kit from single to double acting front-linkages, mount.	4	66095-00
Shock absorber kit incl. hoses and fittings, mounted	4	66050-01
Spring suspension kit incl. hoses and fittings, mounted	16	66051-01
Shift-Control Double, EI-shift between Front-Lift and one outlet	8	65100-10
Shift-Control Triple, EI-shift between Front-Lift and two outlets	14	65100-12
Double oil outlet on Front-Lift, with hoses from tractor outlet	9	65100-20
Lights mounted on Front-Lift 60/55w	-	690148001