

KING-ROLLER



King-Roller 15.30 m. mounted with 620 mm/24" Cambridge rings.



- Strong frame construction of sectional tubes.
- Uncomplicated change-over between transport and working position when the tractor is stopped.
- All sections are centre suspended and mutually independent.
- HE-VA SAT-System: The weight balance system transfers the weight of the construction (drawbar, cylinder and wheel) on all 5 sections to ensure a uniform soil pressure in the entire working width.
- Compact and low – safe and stable transport.
- Transport width of max. 3.00 m.

MACHINES

Work Width, m	Ring Type		No. of Rings	No. of Spokes	Power Req., HP	Weight, kg	Item Number
12.30	510 mm/21" Cambridge	1*	236	8	170-200	7,708	63067-46
12.30	560 mm/22.5" Cambridge	1*	236	9	190-220	8,593	63067-54
12.30	620 mm/24" Cambridge	1*	236	10	190-220	9,360	63067-62
12.30	450/500 mm Star ring	•/1*	224	-	170-200	7,414	63067-56
12.30	550/600 mm Star ring	•/1*	224	-	190-200	8,683	63067-58
12.30	485-530 mm Crosskill	1*	125	-	170-200	7,668	63067-53
12.30	550-600 mm Crosskill	1*	125	-	170-200	9,043	63067-63
12.30	500 mm 2D-Corrugated	1*	150	8	170-200	7,168	63067-50
12.30	550 mm 2D-Corrugated	1*	150	9	180-210	7,310	63067-59
12.30	600 mm 2D-Corrugated	1*	150	10	180-210	8,218	63067-60
15.30	510 mm/21" Cambridge	1*	292	8	180-230	9,260	63068-46
15.30	560 mm/22.5" Cambridge	1*	292	9	200-250	10,931	63068-54
15.30	620 mm/24" Cambridge	1*	292	10	200-250	11,880	63068-62
15.30	450/500 mm Star ring	•/1*	282	-	180-230	8,800	63068-56
15.30	550/600 mm Star ring	•/1*	282	-	200-250	10,370	63068-58
15.30	485-530 mm Crosskill	1*	153	-	180-230	8,380	63068-53
15.30	550-600 mm Crosskill	1*	153	-	180-230	10,068	63068-63
15.30	500 mm 2D-Corrugated	1*	187	8	180-230	7,925	63068-50
15.30	550 mm 2D-Corrugated	1*	187	9	190-240	8,680	63068-59
15.30	600 mm 2D-Corrugated	1*	187	10	190-240	9,323	63068-60
16.30	510 mm/21" Cambridge	1*	306	8	190-240	10,241	63069-46
16.30	560 mm/22.5" Cambridge	1*	306	9	210-260	11,365	63069-54
16.30	620 mm/24" Cambridge	1*	306	10	210-260	12,360	63069-62
16.30	450/500 mm Star ring	•/1*	296	-	190-240	9,817	63069-56
16.30	550/600 mm Star ring	•/1*	296	-	210-260	11,460	63069-58
16.30	485-530 mm Crosskill	1*	163	-	190-240	9,340	63069-53
16.30	550-600 mm Crosskill	1*	163	-	190-240	11,130	63069-63
16.30	500 mm 2D-Corrugated	1*	199	8	190-240	9,510	63069-50
16.30	550 mm 2D-Corrugated	1*	199	9	200-250	9,650	63069-59
16.30	600 mm 2D-Corrugated	1*	199	10	200-250	10,360	63069-60
18.30	510 mm/21" Cambridge	1*	346	8	210-260	10,818	63071-46
18.30	560 mm/22.5" Cambridge	1*	346	9	230-280	12,675	63071-54
18.30	620 mm/24" Cambridge	1*	346	10	230-280	13,800	63071-62
18.30	450/500 mm Star ring	•/1*	328	-	210-260	11,015	63071-56
18.30	550/600 mm Star ring	•/1*	328	-	230-280	12,866	63071-58
18.30	485-530 mm Crosskill	1*	183	-	210-260	10,752	63071-53
18.30	550-600 mm Crosskill	1*	183	-	210-260	12,765	63071-63
18.30	500 mm 2D-Corrugated	1*	223	8	210-260	10,088	63071-50
18.30	550 mm 2D-Corrugated	1*	223	9	220-270	10,834	63071-59
18.30	600 mm 2D-Corrugated	1*	223	10	220-270	11,649	63071-60
20.30	510 mm/21" Cambridge	1*	386	8	220-280	13,600	63070-46
20.30	560 mm/22.5" Cambridge	1*	386	9	240-300	14,280	63070-54
20.30	450/500 mm Star ring	•/1*	376	-	220-280	12,618	63070-56
20.30	485-530 mm Crosskill	1*	203	-	220-280	13,494	63070-53
20.30	500 mm 2D-Corrugated	1*	248	8	220-280	12,770	63070-50
20.30	550 mm 2D-Corrugated	1*	248	9	240-300	12,944	63070-59

*Requires 3 double-acting oil outlets

* Steel cast ring, 8 year breakage warranty

STANDARD EQUIPMENT

- Wheels:
 - 550/45x22.5 – 16 PLY f/ 12.30 + 15.30.
 - 560/45 R 22.5 – 152D f/ 16.30 + 18.30 + 20.30 m.
- 60 mm shafts, special quality, mounted w/triple-sealed ball bearings.
- Pivotal towing eye, secured by bolts, item no. 630757046.
- Hydraulic supporting leg.
- Parking device for hydraulic hoses.
- Automatic lock system of the wing sections during transport.
- HE-VA SAT-System: Weight balance system on all 5 sections.
- Support bearings on all sections.

EXTRA EQUIPMENT

Description	Weight, kg	Item Number
Model report for individual acceptance of the roller (including air brake system and lighting) From a support load of 4 tons on the lower link. (630757034) required (not included in the price) Complies with regulation in Germany only. (Additional price)	-	63080-38
LED lights complete with wire and socket, mounted	3	63067-33
Air brakes, Tristop, factory-mounted for 12.30 – 15.30 models	18	63067-35
Air brakes, Tristop, factory-mounted for 16.30 – 20.30 models	18	63067-36
Hydr. Brakes, factory-mounted for 12.30 – 15.30 models	7	63067-37
Hydr. Brakes, factory-mounted for 16.30 – 20.30 models	7	63067-41
Dual brakes, both air and hydraulic, factory-mounted on 12.30 and 15.30 m	25	63067-39
Dual brakes, both air and hydraulic, factory-mounted on 16.30 - 20.30 m	25	63067-38
Stone box set (2 pieces)	32	630555008
Rubber sealed/non-lubricant ball bearings (Additional price per machine)	-	63067-73

CAST STEEL RINGS		
Description	Weight, kg	Item Number
510 mm/21" Cambridge / 550 mm 2D-Corrugated. Steel cast quality. 8 spokes. Recommended in a non-ploughed syst. and in extreme conditions. (Add. price per m)	+ 8 per m	690150078
560 mm/22.5" Cambridge / 550 mm 2D-Corrugated. Steel cast quality. 9 spokes. Recommended in a non-ploughed syst. and in extreme conditions. (Add. price per m)	+ 10 per m	690150077
620 mm/24" Cambridge / 600 mm 2D-Corrugated. Steel cast quality. 10 spokes. Recommended in a non-ploughed syst. and in extreme conditions. (Add. price per m)	+ 10 per m	690150118

**8 YEAR WARRANTY ON
STEEL CAST RINGS**

MOUNTING SET FOR MULTI-SEEDER ON A NEW KING-ROLLER. - MAX. 300 KG LOAD IN THE FINE SEED HOPPER. PRICES AND INFO ON MULTI-SEEDER	
Description	Item Number
12.30 m - 200 L	63067-15
12.30 m - 410 L	63067-20
15.30 / 16.30 / 18.30 / 20.30 m	-
Platform with railing and ladder for mounting set	63099-56



¹Requires 1 double-acting oil outlet

WHEEL TRACK ERADICATOR SET, HYDRAULICALLY ADJUSTABLE	
Description	Item Number
Wheel track eradicator set with 4 pcs. 65x12 tines	¹ 63067-75

NOTE!

If a wheel track eradicator is wanted for retrofitting, please notify us of equipment on the roller!



Wheel track eradicator frame for lift.

WHEEL TRACK ERADICATOR FRAME FOR LIFT	
Description	Item Number
3.00 m. three-point mounted, 6 tines (65x12 mm)	67701-00
4.00 m. three-point mounted, 8 tines (65x12 mm)	67702-00