

# LIFT-ROLLER



3.00 m with 510 mm/21" Cambridge.



- Drawbar, free movable up/down.
- 60 mm bearings and shafts, special quality.
- Small lifting requirement – close to the tractor.

## MACHINES

| Work Width, m | Ring Type              | No. of Rings | No. of Spokes | Power Req., HP | Lifting Req., kg | Weight, kg | Item Number |
|---------------|------------------------|--------------|---------------|----------------|------------------|------------|-------------|
| 2.60          | 510 mm/21" Cambridge   | 45           | 3             | 40             | 1,400            | 930        | 63073-51    |
| 2.60          | 510 mm/21" Cambridge   | 45           | 8             | 40             | 1,400            | 1,101      | 63073-46    |
| 2.60          | 560 mm/22.5" Cambridge | 45           | 9             | 45             | 1,630            | 1,160      | 63073-54    |
| 2.60          | 620 mm/24" Cambridge   | 45           | 10            | 45             | 1,880            | 1,250      | 63073-62    |
| 2.60          | 450/500 mm Star ring   | 42           | -             | 45             | 1,470            | 980        | 63073-56    |
| 2.60          | 550/600 mm Star ring   | 42           | -             | 45             | 1,850            | 1,230      | 63073-57    |
| 2.60          | 550 mm Cam ring        | 16           | -             | 30             | 1,020            | 680        | 63073-55    |
| 2.60          | 485-530 mm Crosskill   | 25           | -             | 40             | 1,100            | 730        | 63073-53    |
| 2.60          | 550-600 mm Crosskill   | 25           | -             | 40             | 1,570            | 1,050      | 63073-63    |
| 2.60          | 500 mm 2D-Corrugated   | 31           | 8             | 40             | 1,250            | 830        | 63073-50    |
| 2.60          | 550 mm 2D-Corrugated   | 31           | 9             | 40             | 1,290            | 860        | 63073-59    |
| 2.60          | 600 mm 2D-Corrugated   | 31           | 10            | 45             | 1,320            | 880        | 63073-60    |
| 3.00          | 510 mm/21" Cambridge   | 53           | 3             | 55             | 1,590            | 1,060      | 63074-51    |
| 3.00          | 510 mm/21" Cambridge   | 53           | 8             | 55             | 1,590            | 1,261      | 63074-46    |
| 3.00          | 560 mm/22.5" Cambridge | 53           | 9             | 60             | 1,910            | 1,320      | 63074-54    |
| 3.00          | 620 mm/24" Cambridge   | 53           | 10            | 60             | 2,150            | 1,430      | 63074-62    |
| 3.00          | 450/500 mm Star ring   | 50           | -             | 60             | 1,670            | 1,110      | 63074-56    |
| 3.00          | 550/600 mm Star ring   | 50           | -             | 60             | 2,100            | 1,400      | 63074-57    |
| 3.00          | 550 mm Cam ring        | 19           | -             | 40             | 1,220            | 820        | 63074-55    |
| 3.00          | 485-530 mm Crosskill   | 27           | -             | 55             | 1,250            | 830        | 63074-53    |
| 3.00          | 550-600 mm Crosskill   | 27           | -             | 55             | 1,760            | 1,170      | 63074-63    |
| 3.00          | 500 mm 2D-Corrugated   | 35           | 8             | 55             | 1,380            | 920        | 63074-50    |
| 3.00          | 550 mm 2D-Corrugated   | 35           | 9             | 55             | 1,440            | 960        | 63074-59    |
| 3.00          | 600 mm 2D-Corrugated   | 35           | 10            | 60             | 1,480            | 990        | 63074-60    |

- Steel cast ring, 8 year breakage warranty

## STANDARD EQUIPMENT

- Three-point mounting for cat. 2.
- Support stand, pins and locking pins.

## EXTRA EQUIPMENT



| Description                                        | Weight, kg | Item Number |
|----------------------------------------------------|------------|-------------|
| LED lights, complete with wire and socket, mounted | 4          | 63003-01    |
| Set of reflective warning boards (2 pieces)        | 8          | 67055-74    |
| Stone box set (2 pieces)                           | 32         | 630555005   |

### GRASS-SEEDER KIT EXCL. MULTI-SEEDER

| Work Width, m | Description                                                                                                                  | Item Number |
|---------------|------------------------------------------------------------------------------------------------------------------------------|-------------|
| 2.60          | 230 mm adjustable plain roller behind the implement, adjustable longfinger harrow in front and mounting set for Multi-Seeder | 63073-20    |
| 3.00          | 230 mm adjustable plain roller behind the implement, adjustable longfinger harrow in front and mounting set for Multi-Seeder | 63074-20    |