

SWING-ROLLER



- Strong frame construction of sectional tubes.
- Uncomplicated change-over between transport and working position when the tractor is stopped.
- All sections are centre suspended and mutually independent.
- HE-VA SAT-System: The weight balance system transfers the weight of the construction (drawbar, cylinder and wheel) on all 5 sections to ensure a uniform soil pressure in the entire working width.
- Compact and low – safe and stable transport.
- Transport width of max. 2.70 m.

MACHINES

Work Width, m	Ring Type	No. of Rings	No. of Spokes	Power Req., HP	Weight, kg	Item Number	
10.20	510 mm/21" Cambridge	1 ^{1*}	199	3	150-180	6,010	63097-51
10.20	510 mm/21" Cambridge	1 ^{1*}	199	8	150-180	6,330	63097-46
10.20	450/500 mm Star ring	•/1 ^{1*}	194	-	150-180	6,120	63097-56
10.20	485-530 mm Crosskill	1 ^{1*}	105	-	150-180	5,960	63097-53
10.20	500 mm 2D-Corrugated	1 ^{1*}	125	8	150-180	5,500	63097-50
12.20	510 mm/21" Cambridge	1 ^{1*}	235	3	170-200	6,680	63098-51
12.20	510 mm/21" Cambridge	1 ^{1*}	235	8	170-200	7,050	63098-46
12.20	450/500 mm Star ring	•/1 ^{1*}	230	-	170-200	6,750	63098-56
12.20	485-530 mm Crosskill	1 ^{1*}	125	-	170-200	6,650	63098-53
12.20	500 mm 2D-Corrugated	1 ^{1*}	150	8	170-200	6,130	63098-50

^{1*}Requires 2 double-acting oil outlets

• Steel cast ring, 8 year breakage warranty

STANDARD EQUIPMENT

- Wheels:
 - 400/60x15.5 – 16 PLY.
- Towing eye, secured by bolts, item no. 630757017.
- Adjustable supporting leg with gear.
- Parking device for hydraulic hoses.
- 60 mm shafts, special quality, mounted with triple-sealed ball bearings.
- Manual parking and transport protection of the wing sections.
- HE-VA SAT-System: Weight balance system on all 5 sections.

EXTRA EQUIPMENT

Description	Weight, kg	Item Number
LED lights complete with wire and socket, mounted	3	63098-01
Hydraulic supporting leg (Additional price)	15	63098-06
Stone box set (2 pieces)	32	630555001
Automatic protection of the wing sections during transport	47.5	63098-05
Air brakes factory-mounted	18	63098-07
Hydraulic brakes, factory-mounted	7	63098-08
Rubber sealed/non-lubricant ball bearings (Additional price per machine)	-	63067-73

CAST STEEL RINGS

Description	Weight, kg	Item Number
510 mm/21" Cambridge / 550 mm 2D-Corrugated. Steel cast quality. 8 spokes. Recommended in a non-ploughed syst. and in extreme conditions. (Add. price per m)	+ 8 per m	690150078

8 YEAR WARRANTY ON STEEL CAST RINGS