

# TRIPLE-TILLER (THREE-POINT MOUNTED)



- Optimal cultivating with only 25 cm row spacing.
- 3 rows of harrow sections with good clearance with 85 cm frame height, 75 cm tine spacing and 70 cm bar spacing.
- 4 tine options:
  - Spring tine double-twisted 35 x 35 mm for 3.00 - 3.50 m models. Work depth: 0 - 20 cm.
  - Spring tine double-twisted 40 x 40 mm for 4.00 - 5.00 m models. Work depth: 0 - 30 cm.
  - Shear bolt - preloaded for 2,550 kg. Work depth: 0 - 30 cm.
  - Automatic w/spring /auto reset preloaded for 560 kg. Work depth: 0 - 30 cm.
- Eradicator discs, standard equipment, w/centre spindle adjustment, stone protected by rubber suspension.
- Hydr. depth adjustment –w/depth stop by means of distance clips.

## MACHINES

### THREE-POINT MOUNTED RIGID 1-SECTION MODELS WITHOUT HYDRAULIC FOLDING

| Work Width, m | Roller Type                | Stone Protection           | No. of Tines | Power Req., HP | Lifting Req., kg | Transport Width, m | Weight, kg | Item Number |
|---------------|----------------------------|----------------------------|--------------|----------------|------------------|--------------------|------------|-------------|
| 3.00          | Square Tube Roller Ø550 mm | 1 <sup>†</sup> Spring tine | 12           | 100-200        | 4,070            | 3.00               | 1,850      | 4503022     |
| 3.00          | Square Tube Roller Ø550 mm | 1 <sup>†</sup> Shear bolt  | 12           | 100-200        | 4,070            | 3.00               | 1,850      | 4503024     |
| 3.00          | Square Tube Roller Ø550 mm | 1 <sup>†</sup> Automatic   | 12           | 100-200        | 4,070            | 3.00               | 1,850      | 4503020     |
| 3.00          | Wave roller Ø600 mm        | 1 <sup>†</sup> Spring tine | 12           | 100-200        | -                | 3.00               | -          | 4503072     |
| 3.00          | Wave roller Ø600 mm        | 1 <sup>†</sup> Shear bolt  | 12           | 100-200        | -                | 3.00               | -          | 4503074     |
| 3.00          | Wave roller Ø600 mm        | 1 <sup>†</sup> Automatic   | 12           | 100-200        | -                | 3.00               | -          | 4503070     |
| 3.00          | U-Profile Roller Ø600 mm   | 1 <sup>†</sup> Spring tine | 12           | 100-200        | 5,000            | 3.00               | 2,100      | 4503082     |
| 3.00          | U-Profile Roller Ø600 mm   | 1 <sup>†</sup> Shear bolt  | 12           | 100-200        | 5,000            | 3.00               | 2,100      | 4503084     |
| 3.00          | U-Profile Roller Ø600 mm   | 1 <sup>†</sup> Automatic   | 12           | 100-200        | 5,000            | 3.00               | 2,100      | 4503080     |
| 3.00          | V-Profile Roller Ø600 mm   | 1 <sup>†</sup> Spring tine | 12           | 100-200        | 5,430            | 3.00               | 2,470      | 4503062     |
| 3.00          | V-Profile Roller Ø600 mm   | 1 <sup>†</sup> Shear bolt  | 12           | 100-200        | 5,430            | 3.00               | 2,470      | 4503064     |
| 3.00          | V-Profile Roller Ø600 mm   | 1 <sup>†</sup> Automatic   | 12           | 100-200        | 5,430            | 3.00               | 2,470      | 4503060     |
| 3.50          | Square Tube Roller Ø550 mm | 1 <sup>†</sup> Spring tine | 14           | 120-240        | 4,690            | 3.50               | 2,135      | 4503522     |
| 3.50          | Square Tube Roller Ø550 mm | 1 <sup>†</sup> Shear bolt  | 14           | 120-240        | 4,690            | 3.50               | 2,135      | 4503524     |
| 3.50          | Square Tube Roller Ø550 mm | 1 <sup>†</sup> Automatic   | 14           | 120-240        | 4,690            | 3.50               | 2,135      | 4503520     |
| 3.50          | Wave roller Ø600 mm        | 1 <sup>†</sup> Spring tine | 14           | 120-240        | -                | 3.50               | -          | 4503572     |
| 3.50          | Wave roller Ø600 mm        | 1 <sup>†</sup> Shear bolt  | 14           | 120-240        | -                | 3.50               | -          | 4503574     |
| 3.50          | Wave roller Ø600 mm        | 1 <sup>†</sup> Automatic   | 14           | 120-240        | -                | 3.50               | -          | 4503570     |
| 3.50          | U-Profile Roller Ø600 mm   | 1 <sup>†</sup> Spring tine | 14           | 120-240        | 5,620            | 3.50               | 2,540      | 4503582     |
| 3.50          | U-Profile Roller Ø600 mm   | 1 <sup>†</sup> Shear bolt  | 14           | 120-240        | 5,620            | 3.50               | 2,540      | 4503584     |
| 3.50          | U-Profile Roller Ø600 mm   | 1 <sup>†</sup> Automatic   | 14           | 120-240        | 5,620            | 3.50               | 2,540      | 4503580     |
| 3.50          | V-Profile Roller Ø600 mm   | 1 <sup>†</sup> Spring tine | 14           | 120-240        | 6,290            | 3.50               | 2,860      | 4503562     |
| 3.50          | V-Profile Roller Ø600 mm   | 1 <sup>†</sup> Shear bolt  | 14           | 120-240        | 6,290            | 3.50               | 2,860      | 4503564     |
| 3.50          | V-Profile Roller Ø600 mm   | 1 <sup>†</sup> Automatic   | 14           | 120-240        | 6,290            | 3.50               | 2,860      | 4503560     |
| 4.00          | Square Tube Roller Ø550 mm | 1 <sup>†</sup> Spring tine | 16           | 140-250        | 5,290            | 4.00               | 2,420      | 4534022     |
| 4.00          | Square Tube Roller Ø550 mm | 1 <sup>†</sup> Shear bolt  | 16           | 140-250        | 5,290            | 4.00               | 2,420      | 4534024     |
| 4.00          | Square Tube Roller Ø550 mm | 1 <sup>†</sup> Automatic   | 16           | 140-250        | 5,290            | 4.00               | 2,420      | 4534020     |
| 4.00          | Wave roller Ø600 mm        | 1 <sup>†</sup> Spring tine | 16           | 140-250        | -                | 4.00               | -          | 4534072     |
| 4.00          | Wave roller Ø600 mm        | 1 <sup>†</sup> Shear bolt  | 16           | 140-250        | -                | 4.00               | -          | 4534074     |
| 4.00          | Wave roller Ø600 mm        | 1 <sup>†</sup> Automatic   | 16           | 140-250        | -                | 4.00               | -          | 4534070     |
| 4.00          | U-Profile Roller Ø600 mm   | 1 <sup>†</sup> Spring tine | 16           | 140-250        | 6,570            | 4.00               | 3,010      | 4534082     |
| 4.00          | U-Profile Roller Ø600 mm   | 1 <sup>†</sup> Shear bolt  | 16           | 140-250        | 6,570            | 4.00               | 3,010      | 4534084     |
| 4.00          | U-Profile Roller Ø600 mm   | 1 <sup>†</sup> Automatic   | 16           | 140-250        | 6,570            | 4.00               | 3,010      | 4534080     |
| 4.00          | V-Profile Roller Ø600 mm   | 1 <sup>†</sup> Spring tine | 16           | 140-250        | 7,185            | 4.00               | 3,300      | 4534062     |
| 4.00          | V-Profile Roller Ø600 mm   | 1 <sup>†</sup> Shear bolt  | 16           | 140-250        | 7,185            | 4.00               | 3,300      | 4534064     |
| 4.00          | V-Profile Roller Ø600 mm   | 1 <sup>†</sup> Automatic   | 16           | 140-250        | 7,185            | 4.00               | 3,300      | 4534060     |

<sup>†</sup>Requires 1 double-acting oil outlet.

## MACHINES (CONTINUED)

### THREE-POINT MOUNTED 2-SECTION MODELS WITH HYDRAULIC FOLDING

| Work Width, m | Roller Type                | Stone Protection          | No. of Tines | Power Req., HP | Lifting Req., kg | Transport Width, m | Weight, kg | Item Number |
|---------------|----------------------------|---------------------------|--------------|----------------|------------------|--------------------|------------|-------------|
| 4.00          | Square Tube Roller Ø550 mm | <sup>1*</sup> Spring tine | 16           | 140-250        | 6,470            | 2.48               | 2,570      | 4504022     |
| 4.00          | Square Tube Roller Ø550 mm | <sup>1*</sup> Shear bolt  | 16           | 140-250        | 6,470            | 2.48               | 2,570      | 4504024     |
| 4.00          | Square Tube Roller Ø550 mm | <sup>1*</sup> Automatic   | 16           | 140-250        | 6,470            | 2.48               | 2,570      | 4504020     |
| 4.00          | Wave roller Ø600 mm        | <sup>1*</sup> Spring tine | 16           | 140-250        | -                | 2.48               | -          | 4504072     |
| 4.00          | Wave roller Ø600 mm        | <sup>1*</sup> Shear bolt  | 16           | 140-250        | -                | 2.48               | -          | 4504074     |
| 4.00          | Wave roller Ø600 mm        | <sup>1*</sup> Automatic   | 16           | 140-250        | -                | 2.48               | -          | 4504070     |
| 4.00          | U-Profile Roller Ø600 mm   | <sup>1*</sup> Spring tine | 16           | 140-250        | 8,100            | 2.48               | 3,090      | 4504082     |
| 4.00          | U-Profile Roller Ø600 mm   | <sup>1*</sup> Shear bolt  | 16           | 140-250        | 8,100            | 2.48               | 3,090      | 4504084     |
| 4.00          | U-Profile Roller Ø600 mm   | <sup>1*</sup> Automatic   | 16           | 140-250        | 8,100            | 2.48               | 3,090      | 4504080     |
| 4.00          | V-Profile Roller Ø600 mm   | <sup>1*</sup> Spring tine | 16           | 140-250        | 8,290            | 2.48               | 3,400      | 4504062     |
| 4.00          | V-Profile Roller Ø600 mm   | <sup>1*</sup> Shear bolt  | 16           | 140-250        | 8,290            | 2.48               | 3,400      | 4504064     |
| 4.00          | V-Profile Roller Ø600 mm   | <sup>1*</sup> Automatic   | 16           | 140-250        | 8,290            | 2.48               | 3,400      | 4504060     |
| 5.00          | Square Tube Roller Ø550 mm | <sup>1*</sup> Spring tine | 20           | 140-250        | 6,470            | 2.48               | 3,880      | 4505022     |
| 5.00          | Square Tube Roller Ø550 mm | <sup>1*</sup> Shear bolt  | 20           | 140-250        | 6,470            | 2.48               | 3,880      | 4505024     |
| 5.00          | Square Tube Roller Ø550 mm | <sup>1*</sup> Automatic   | 20           | 140-250        | 6,470            | 2.48               | 3,880      | 4505020     |
| 5.00          | Wave roller Ø600 mm        | <sup>1*</sup> Spring tine | 20           | 140-250        | -                | 2.48               | -          | 4505072     |
| 5.00          | Wave roller Ø600 mm        | <sup>1*</sup> Shear bolt  | 20           | 140-250        | -                | 2.48               | -          | 4505074     |
| 5.00          | Wave roller Ø600 mm        | <sup>1*</sup> Automatic   | 20           | 140-250        | -                | 2.48               | -          | 4505070     |
| 5.00          | U-Profile Roller Ø600 mm   | <sup>1*</sup> Spring tine | 20           | 140-250        | 8,100            | 2.48               | 4,560      | 4505082     |
| 5.00          | U-Profile Roller Ø600 mm   | <sup>1*</sup> Shear bolt  | 20           | 140-250        | 8,100            | 2.48               | 4,560      | 4505084     |
| 5.00          | U-Profile Roller Ø600 mm   | <sup>1*</sup> Automatic   | 20           | 140-250        | 8,100            | 2.48               | 4,560      | 4505080     |
| 5.00          | V-Profile Roller Ø600 mm   | <sup>1*</sup> Spring tine | 20           | 140-250        | 8,290            | 2.48               | 4,870      | 4505062     |
| 5.00          | V-Profile Roller Ø600 mm   | <sup>1*</sup> Shear bolt  | 20           | 140-250        | 8,290            | 2.48               | 4,870      | 4505064     |
| 5.00          | V-Profile Roller Ø600 mm   | <sup>1*</sup> Automatic   | 20           | 140-250        | 8,290            | 2.48               | 4,870      | 4505060     |

<sup>1\*</sup>Requires 2 double-acting oil outlets.

## STANDARD EQUIPMENT

- 75 x 12 mm reversible and height adjustable concave wearing point (double curved).
- Ø410 mm scalloped eradicator discs with centre spindle adjustment, stone protected by rubber suspension.
- Ø550 mm Square Tube Roller, Ø600 mm Wave Roller, Ø600 mm U-Profile or V-Profile Roller.
- Scraper between the rings, on Wave roller, Single V and U-Profile Roller.
- Automatic transport locking devices, operated hydr. together w/the folding function.
- All models have hydr. depth adjustment of the roller with the possibility of fixed stop via the distance clips.
- Three-point linkage with cat. 3 pins and cat. 2 distance.

# TRIPLE-TILLER (TRAILED)



- Optimal cultivating with only 25 cm row spacing.
- 3 rows of harrow sections with good clearance with 85 cm frame height, 75 cm tine spacing and 70 cm bar spacing.
- 4 tine options (see page 118):
  - Spring tine double-twisted 35 x 35 mm for 3.00 - 3.50 m models. Work depth: 0 - 20 cm.
  - Spring tine double-twisted 40 x 40 mm for 4.00 - 5.00 m models. Work depth: 0 - 30 cm.
  - Shear bolt - preloaded for 2,550 kg. Work depth: 0 - 30 cm.
  - Automatic w/spring /auto reset preloaded for 560 kg. Work depth: 0 - 30 cm.
- Eradicator discs, standard equipment, w/centre spindle adjustment, stone protected by rubber suspension.
- Hydr. depth adjustment –w/depth stop by means of distance clips.

## MACHINES

### TRAILED RIGID 1-SECTION MODELS WITHOUT HYDRAULIC FOLDING

| Work Width, m | Roller Type                | Stone Protection | No. of Tines | Power Req., HP | Transport Width, m | Weight, kg | Item Number |
|---------------|----------------------------|------------------|--------------|----------------|--------------------|------------|-------------|
| 3.00          | Square Tube Roller Ø550 mm | 1* Spring tine   | 12           | 100-200        | 3.00               | 2,430      | 4513022     |
| 3.00          | Square Tube Roller Ø550 mm | 1* Shear bolt    | 12           | 100-200        | 3.00               | 2,430      | 4513024     |
| 3.00          | Square Tube Roller Ø550 mm | 1* Automatic     | 12           | 100-200        | 3.00               | 2,430      | 4513020     |
| 3.00          | Wave roller Ø600 mm        | 1* Spring tine   | 12           | 100-200        | 3.00               | -          | 4513072     |
| 3.00          | Wave roller Ø600 mm        | 1* Shear bolt    | 12           | 100-200        | 3.00               | -          | 4513074     |
| 3.00          | Wave roller Ø600 mm        | 1* Automatic     | 12           | 100-200        | 3.00               | -          | 4513070     |
| 3.00          | U-Profile Roller Ø600 mm   | 1* Spring tine   | 12           | 100-200        | 3.00               | 2,700      | 4513082     |
| 3.00          | U-Profile Roller Ø600 mm   | 1* Shear bolt    | 12           | 100-200        | 3.00               | 2,700      | 4513084     |
| 3.00          | U-Profile Roller Ø600 mm   | 1* Automatic     | 12           | 100-200        | 3.00               | 2,700      | 4513080     |
| 3.00          | V-Profile Roller Ø600 mm   | 1* Spring tine   | 12           | 100-200        | 3.00               | 3,050      | 4513062     |
| 3.00          | V-Profile Roller Ø600 mm   | 1* Shear bolt    | 12           | 100-200        | 3.00               | 3,050      | 4513064     |
| 3.00          | V-Profile Roller Ø600 mm   | 1* Automatic     | 12           | 100-200        | 3.00               | 3,050      | 4513060     |
| 3.50          | Square Tube Roller Ø550 mm | 1* Spring tine   | 14           | 120-240        | 3.50               | 2,715      | 4513522     |
| 3.50          | Square Tube Roller Ø550 mm | 1* Shear bolt    | 14           | 120-240        | 3.50               | 2,715      | 4513524     |
| 3.50          | Square Tube Roller Ø550 mm | 1* Automatic     | 14           | 120-240        | 3.50               | 2,715      | 4513520     |
| 3.50          | Wave roller Ø600 mm        | 1* Spring tine   | 14           | 120-240        | 3.50               | -          | 4513572     |
| 3.50          | Wave roller Ø600 mm        | 1* Shear bolt    | 14           | 120-240        | 3.50               | -          | 4513574     |
| 3.50          | Wave roller Ø600 mm        | 1* Automatic     | 14           | 120-240        | 3.50               | -          | 4513570     |
| 3.50          | U-Profile Roller Ø600 mm   | 1* Spring tine   | 14           | 120-240        | 3.50               | 3,100      | 4513582     |
| 3.50          | U-Profile Roller Ø600 mm   | 1* Shear bolt    | 14           | 120-240        | 3.50               | 3,100      | 4513584     |
| 3.50          | U-Profile Roller Ø600 mm   | 1* Automatic     | 14           | 120-240        | 3.50               | 3,100      | 4513580     |
| 3.50          | V-Profile Roller Ø600 mm   | 1* Spring tine   | 14           | 120-240        | 3.50               | 3,440      | 4513562     |
| 3.50          | V-Profile Roller Ø600 mm   | 1* Shear bolt    | 14           | 120-240        | 3.50               | 3,440      | 4513564     |
| 3.50          | V-Profile Roller Ø600 mm   | 1* Automatic     | 14           | 120-240        | 3.50               | 3,440      | 4513560     |
| 4.00          | Square Tube Roller Ø550 mm | 1* Spring tine   | 16           | 140-250        | 4.00               | 3,090      | 4544022     |
| 4.00          | Square Tube Roller Ø550 mm | 1* Shear bolt    | 16           | 140-250        | 4.00               | 3,090      | 4544024     |
| 4.00          | Square Tube Roller Ø550 mm | 1* Automatic     | 16           | 140-250        | 4.00               | 3,090      | 4544020     |
| 4.00          | Wave roller Ø600 mm        | 1* Spring tine   | 16           | 140-250        | 4.00               | -          | 4544072     |
| 4.00          | Wave roller Ø600 mm        | 1* Shear bolt    | 16           | 140-250        | 4.00               | -          | 4544074     |
| 4.00          | Wave roller Ø600 mm        | 1* Automatic     | 16           | 140-250        | 4.00               | -          | 4544070     |
| 4.00          | U-Profile Roller Ø600 mm   | 1* Spring tine   | 16           | 140-250        | 4.00               | 3,615      | 4544082     |
| 4.00          | U-Profile Roller Ø600 mm   | 1* Shear bolt    | 16           | 140-250        | 4.00               | 3,615      | 4544084     |
| 4.00          | U-Profile Roller Ø600 mm   | 1* Automatic     | 16           | 140-250        | 4.00               | 3,615      | 4544080     |
| 4.00          | V-Profile Roller Ø600 mm   | 1* Spring tine   | 16           | 140-250        | 4.00               | 3,900      | 4544062     |
| 4.00          | V-Profile Roller Ø600 mm   | 1* Shear bolt    | 16           | 140-250        | 4.00               | 3,900      | 4544064     |
| 4.00          | V-Profile Roller Ø600 mm   | 1* Automatic     | 16           | 140-250        | 4.00               | 3,900      | 4544060     |

<sup>1</sup>Requires 2 double-acting oil outlets.

## MACHINES (CONTINUED)

### TRAILED 2-SECTION MODELS WITH HYDRAULIC FOLDING

| Work Width, m | Roller Type                | Stone Protection          | No. of Tines | Power Req., HP | Lifting Req., kg | Transport Width, m | Weight, kg | Item Number |
|---------------|----------------------------|---------------------------|--------------|----------------|------------------|--------------------|------------|-------------|
| 4.00          | Square Tube Roller Ø550 mm | <sup>1*</sup> Spring tine | 16           | 140-250        | 6,470            | 2.48               | 3,240      | 4514022     |
| 4.00          | Square Tube Roller Ø550 mm | <sup>1*</sup> Shear bolt  | 16           | 140-250        | 6,470            | 2.48               | 3,240      | 4514024     |
| 4.00          | Square Tube Roller Ø550 mm | <sup>1*</sup> Automatic   | 16           | 140-250        | 6,470            | 2.48               | 3,240      | 4514020     |
| 4.00          | U-Profile Roller Ø600 mm   | <sup>1*</sup> Spring tine | 16           | 140-250        | 8,100            | 2.48               | 3,760      | 4514082     |
| 4.00          | U-Profile Roller Ø600 mm   | <sup>1*</sup> Shear bolt  | 16           | 140-250        | 8,100            | 2.48               | 3,760      | 4514084     |
| 4.00          | U-Profile Roller Ø600 mm   | <sup>1*</sup> Automatic   | 16           | 140-250        | 8,100            | 2.48               | 3,760      | 4514080     |
| 4.00          | V-Profile Roller Ø600 mm   | <sup>1*</sup> Spring tine | 16           | 140-250        | 8,290            | 2.48               | 4,070      | 4514062     |
| 4.00          | V-Profile Roller Ø600 mm   | <sup>1*</sup> Shear bolt  | 16           | 140-250        | 8,290            | 2.48               | 4,070      | 4514064     |
| 4.00          | V-Profile Roller Ø600 mm   | <sup>1*</sup> Automatic   | 16           | 140-250        | 8,290            | 2.48               | 4,070      | 4514060     |
| 5.00          | Square Tube Roller Ø550 mm | <sup>1*</sup> Spring tine | 20           | 140-250        | 6,470            | 2.48               | 4,550      | 4515022     |
| 5.00          | Square Tube Roller Ø550 mm | <sup>1*</sup> Shear bolt  | 20           | 140-250        | 6,470            | 2.48               | 4,550      | 4515024     |
| 5.00          | Square Tube Roller Ø550 mm | <sup>1*</sup> Automatic   | 20           | 140-250        | 6,470            | 2.48               | 4,550      | 4515020     |
| 5.00          | U-Profile Roller Ø600 mm   | <sup>1*</sup> Spring tine | 20           | 140-250        | 8,100            | 2.48               | 5,230      | 4515082     |
| 5.00          | U-Profile Roller Ø600 mm   | <sup>1*</sup> Shear bolt  | 20           | 140-250        | 8,100            | 2.48               | 5,230      | 4515084     |
| 5.00          | U-Profile Roller Ø600 mm   | <sup>1*</sup> Automatic   | 20           | 140-250        | 8,100            | 2.48               | 5,230      | 4515080     |
| 5.00          | V-Profile Roller Ø600 mm   | <sup>1*</sup> Spring tine | 20           | 140-250        | 8,290            | 2.48               | 5,540      | 4515062     |
| 5.00          | V-Profile Roller Ø600 mm   | <sup>1*</sup> Shear bolt  | 20           | 140-250        | 8,290            | 2.48               | 5,540      | 4515064     |
| 5.00          | V-Profile Roller Ø600 mm   | <sup>1*</sup> Automatic   | 20           | 140-250        | 8,290            | 2.48               | 5,540      | 4515060     |

<sup>1\*</sup>Requires 3 double-acting oil outlets.

## STANDARD EQUIPMENT

- 75 x 12 mm reversible and height adjustable concave wearing point (double curved).
- Ø410 mm scalloped eradicator discs with centre spindle adjustment, stone protected by rubber suspension.
- Ø550 mm Square Tube Roller, Ø600 mm Wave Roller, Ø600 mm U-Profile or V-Profile Roller.
- Scraper between the rings, on Wave roller, Single V and U-Profile Roller.
- Automatic transport locking devices, operated hydr. together w/the folding function.
- Wheels:
  - 3.00 and 3.50 m 1-section: 11.5/80x 15.3 – 14 PLY.
  - 4.00 m 1-section: 4.00 m and 5.00 m 2-section: 400/60 x 15.5 – 16 PLY.
- Pivotal towing eye, secured by bolts, item no.. 630757017
- Three-point linkage with cat. 3 pins and cat. 2 distance.

## EXTRA EQUIPMENT - THREE-POINT MOUNTED / TRAILED

| Work Width, m | Description  | Weight, kg | Item Number |
|---------------|--|------------|-------------|
| 3.00 - 4.00   | LED lights complete with wire and socket mounted on three-point mounted 1-section models | 3          | 4519510     |
| 4.00 - 5.00   | LED lights with wire and socket, mounted on three-point mounted 2-section models         | 3          | 4519515     |
| 3.00 - 5.00   | Set of reflective warning boards (2 pieces)  | 8          | 67055-74    |
| 3.00 - 5.00   | Narrow wear point, 50x25 mm – Same price as for standard point                           | -          | 4509310     |
| 2.50 - 6.00   | Concave reversible tip - 19 mm thickness (Additional price per meter)                    | -          | 4509306     |
| 3.00 - 5.00   | Tip with tungsten with twisted mould board (Additional price per meter)                  | -          | 4509309     |
| 3.00 - 5.00   | Goose foot tip (Additional price per meter)  | -          | 4509308     |
| 3.00 - 5.00   | Goose-foot tip with hardmetal (Additional price per meter)                               | -          | 4509307     |
| -             | Edge disc set - hydraulic folding (Price per set)  | 33         | 4519451     |
| -             | Edge disc set - rigid (Price per set)  | 33         | 4519452     |
| 3.00 - 3.50   | Trail kit for rigid models, 11.5/80x15.3   | 580        | 4519701     |
| 4.00          | Trail kit for rigid model, 400/60x15.5   | 590        | 4519702     |
| 4.00          | Trail kit for models with hydraulic folding, 400/60x15.5                                 | 650        | 4519705     |
| -             | Support /depth wheels mounted in front, 10.0/80x12, 2 pcs. (only trailed models)         | 275        | 4519750     |

## EXTRA EQUIPMENT - THREE-POINT MOUNTED / TRAILED (CONTINUED)

### QUICK CHANGE KIT - INCL. ONE SET OF CHISEL POINTS - 75 MM WIDE AND ONE SET OF 260 MM WIDE WING SHARES.

| Work Width, m | Description   | Weight, kg | Item Number |
|---------------|---|------------|-------------|
| 3.00          | "Quick change kit" with twisted mould board, <b>factory-mounted</b> (Additional price)                | 20         | 4509030     |
| 3.50          | "Quick change kit" with twisted mould board, <b>factory-mounted</b> (Additional price)                | 23         | 4509035     |
| 4.00          | "Quick change kit" with twisted mould board, <b>factory-mounted</b> (Additional price)                | 26         | 4509040     |
| 5.00          | "Quick change kit" with twisted mould board, <b>factory-mounted</b> (Additional price)                | 33         | 4509050     |
| 3.00 - 5.00   | "Quick change kit" with twisted mould board. (Left) <b>retrofitting</b> (Additional price per meter)  | -          | 4509019     |
| 3.00 - 5.00   | "Quick change kit" with twisted mould board. (Right) <b>retrofitting</b> (Additional price per meter) | -          | 4509020     |
| 3.00          | "Quick change kit" with straight mould board, <b>factory-mounted</b> (Additional price)               | 23         | 4509230     |
| 3.50          | "Quick change kit" with straight mould board, <b>factory-mounted</b> (Additional price)               | 27         | 4509235     |
| 4.00          | "Quick change kit" with straight mould board, <b>factory-mounted</b> (Additional price)               | 30         | 4509240     |
| 5.00          | "Quick change kit" with straight mould board, <b>factory-mounted</b> (Additional price)               | 38         | 4509250     |
| 3.00 - 5.00   | "Quick change kit" with straight mould board. <b>retrofitting</b> (Additional price per meter)        | -          | 4509220     |

### MOUNTING SET FOR MULTI-SEEDER INCL. STEPS, INCL. MOUNTING ON NEW TRIPLE-TILLER MAX. 300 KG LOAD IN FINE SEED HOPPER. PRICES AND INFO ON MULTI-SEEDER

| Work Width, m | Type      | Description                                    | Item Number - 8 Outlets |
|---------------|-----------|--|-------------------------|
| 3.00 - 4.00   | Rigid     | For three-point mounted and trailed models     | 4509930                 |
| 4.00 - 5.00   | Hydraulic | For trailed models - only for AC and EC-models | 4509940                 |
| 4.00          | Hydraulic | For three-point mounted models                 | 4509435                 |

