

DISC-ROLLER CLASSIC (THREE-POINT MOUNTED)



- Sabre disc" 510 x 4 mm large scalloped disc with specially designed coulter profile - thus ensuring an improved cutting of surface stubble preparation.
- Maintenance-free disc-hubs.
- Working depth of up to 125 mm in minimal tillage cultivations.
- DSD – Technology: Depth Synchronised Disc-Aggressiveness.
- Available with 600 mm V-Profile rings. Makes the Disc-Roller Classic suitable for stubble cultivations, seed bed preparations or land packing after ploughing.
- Available with 600 mm Wave roller that is good for carrying up the machine's weight on light and loose soil.
- Available with 550 mm Square Tube Roller made of strong sectional tubes. This roller is good on loose soil and it is reducing the lifting requirement.

MACHINES

| Model, m | Work Width, m | Roller Type | No. of Rings | No. of Discs | Power Req., HP | Weight, kg | Item Number |
|---------------------------------------------------|---------------|-----------------------------|---------------|--------------|----------------|------------|-------------|
| 1-SECTION, RIGID WITHOUT HYDRAULIC FOLDING | | | | | | | |
| 2.50 | 2.25 | Square Tube Roller / 550 mm | - | 18 | 90 + | 1,260 | 63090-45 |
| 2.50 | 2.25 | Wave roller / 600 mm | 20 | 18 | 90 + | 1,560 | 63090-73 |
| 2.50 | 2.25 | V-Profile Roller / 600 mm | 16 | 18 | 90 + | 1,780 | 63090-60 |
| 3.00 | 2.75 | Square Tube Roller / 550 mm | - | 22 | 100 + | 1,460 | 63091-45 |
| 3.00 | 2.75 | Wave roller / 600 mm | 24 | 22 | 100 + | 1,810 | 63091-73 |
| 3.00 | 2.75 | V-Profile Roller / 600 mm | 20 | 22 | 100 + | 2,080 | 63091-60 |
| 3.50 | 3.25 | Square Tube Roller / 550 mm | - | 26 | 110 + | 1,670 | 63096-45 |
| 3.50 | 3.25 | Wave roller / 600 mm | 28 | 26 | 110 + | 2,125 | 63096-73 |
| 3.50 | 3.25 | V-Profile Roller / 600 mm | 23 | 26 | 110 + | 2,395 | 63096-60 |
| 4.00 | 3.75 | Square Tube Roller / 550 mm | - | 30 | 120 + | 1,880 | 63092-45 |
| 4.00 | 3.75 | Wave roller / 600 mm | 32 | 30 | 120 + | 2,440 | 63092-52 |
| 4.00 | 3.75 | V-Profile Roller / 600 mm | 26 | 30 | 120 + | 2,710 | 63092-50 |
| 2-SECTION, WITH HYDRAULIC FOLDING | | | | | | | |
| 4.00 | 3.75 | Square Tube Roller / 550 mm | ^{1*} | 30 | 120 + | - | 63092-74 |
| 4.00 | 3.75 | Wave roller / 600 mm | ^{1*} | 32 | 120 + | 2,760 | 63092-73 |
| 4.00 | 3.75 | V-Profile Roller / 600 mm | ^{1*} | 26 | 120 + | 3,120 | 63092-60 |
| 5.00 | 4.75 | Square Tube Roller / 550 mm | ^{1*} | 38 | 150 + | - | 63093-74 |
| 5.00 | 4.75 | Wave roller / 600 mm | ^{1*} | 40 | 150 + | 3,290 | 63093-73 |
| 5.00 | 4.75 | V-Profile Roller / 600 mm | ^{1*} | 32 | 150 + | 3,750 | 63093-60 |

^{1*}Requires 2 double-acting oil outlets.

STANDARD EQUIPMENT

- Mechanical adjustment of working depth on 1-section models.
- Hydraulic adjustment of working depth on 2-section models.
- Edge equipment with disc for retain soil on right side.
- Scraper between the rings.
- 60 mm axles fitted with 60 mm triple-sealed ball bearings.

EXTRA EQUIPMENT

| Work Width, m | Description | Weight, kg | Item Number |
|---------------|----------------------------------------------------------------------|------------|-------------|
| 2.50 - 4.00 | LED lights with wire and socket, rigid models | 3 | 63091-01 |
| 4.00 - 5.00 | LED lights with wire and socket, hydraulic models | 3 | 63092-01 |
| 2.50 - 5.00 | Set of reflective warning boards (2 pieces) | 8 | 67055-74 |
| 2.50 - 4.00 | Hydr. adjustment of working depth and disc angle, rigid models | - | 63092-92 |
| 2.50 - 4.00 | Electrical depth stop for rigid models | 4 | 63091-85 |
| 4.00 - 5.00 | Electrical depth stop for hydraulic models | 8 | 63092-85 |
| 2.50 | Material damper guard | 50 | 63090-98 |
| 3.00 | Material damper guard | 60 | 63091-98 |
| 3.50 | Material damper guard | 70 | 63096-98 |
| 4.00 | Material damper guard | 80 | 63092-98 |
| 5.00 | Material damper guard | 100 | 63093-98 |
| 2.50 - 4.00 | Trail kit for 1-section models, 11.5/80x15.3 | 550 | 63091-55 |
| 4.00 - 5.00 | Trail kit for 2-section models, 400/60x15.3 | 560 | 63092-55 |
| 2.50 - 4.00 | Rubber sealed/non-lubricant ball bearings (Additional price per set) | - | 63090-02 |
| 4.00 - 5.00 | Rubber sealed/non-lubricant ball bearings (Additional price per set) | - | 63090-04 |
| - | Bearing protector for packing roller (Per unit) | 0.9 | 7355054 |
| - | Ø510 x 5 mm "Sabre discs" HD aggressive (Additional price per m) | 7.6 | 63090-10 |



Rubber sealed ball bearings.



Bearing protector for packing roller.



Ø510 x 5 mm "Sabre discs" HD aggressive.

MOUNTING SET FOR MULTI-SEEDER INCL. STEPS, INCL. MOUNTING ON NEW DISC-ROLLER MAX. 300 KG LOAD IN FINE SEED HOPPER. PRICES AND INFO ON MULTI-SEEDER

| Work Width, m | Type | Item Number - 8 Outlets | Item Number - 12 Outlets |
|---------------|-----------|-------------------------|--------------------------|
| 2.50 | Rigid | 63090-12 | - |
| 3.00 | Rigid | 63091-12 | - |
| 3.50 | Rigid | 63096-12 | - |
| 4.00 | Rigid | 63092-12 | 63092-11 |
| 4.00 | Hydraulic | 63092-16 | 63092-13 |
| 5.00 | Hydraulic | 63093-16 | 63093-11 |

DISC-ROLLER CLASSIC (TRAILED)



5.00 m with V-Profile ring and material damper guard.



- “Sabre disc” 510 x 4 mm large scalloped disc with specially designed coulter profile – thus ensuring an improved cutting of surface stubble preparation.
- Maintenance-free disc-hubs.
- Working depth of up to 125 mm in minimal tillage cultivations.
- DSD – Technology: Depth Synchronised Disc-Aggressiveness.
- Available with 600 mm V-Profile rings where you have the most versatility implement with a high own weight. Good for stubble cultivations, seed bed preparations or land packing after ploughing.
- Available with 600 mm Wave roller that is good for carrying up the machine’s weight on light and loose soil.

MACHINES

| Model, m | Work Width, m | Roller Type | No. of Rings | No. of Discs | Power Req., HP | Weight, kg | Item Number |
|---------------------------------------------------|---------------|-----------------------------|------------------|--------------|----------------|------------|-------------|
| 1-SECTION, RIGID WITHOUT HYDRAULIC FOLDING | | | | | | | |
| 3.00 | 2.75 | Square Tube Roller / 550 mm | ^{1*} - | 22 | 100 + | - | 63091-74 |
| 3.00 | 2.75 | Wave roller / 600 mm | ^{1*} 24 | 22 | 100 + | 2,360 | 63091-72 |
| 3.00 | 2.75 | V-Profile Roller / 600 mm | ^{1*} 20 | 22 | 100 + | 2,630 | 63091-64 |
| 3.50 | 3.25 | Square Tube Roller / 550 mm | ^{1*} - | 26 | 110 + | - | 63096-74 |
| 3.50 | 3.25 | Wave roller / 600 mm | ^{1*} 28 | 26 | 110 + | 2,670 | 63096-72 |
| 3.50 | 3.25 | V-Profile Roller / 600 mm | ^{1*} 23 | 26 | 110 + | 2,945 | 63096-64 |
| 4.00 | 3.75 | Square Tube Roller / 550 mm | ^{1*} - | 30 | 120 + | - | 63092-46 |
| 4.00 | 3.75 | Wave roller / 600 mm | ^{1*} 32 | 30 | 120 + | 2,990 | 63092-47 |
| 4.00 | 3.75 | V-Profile Roller / 600 mm | ^{1*} 26 | 30 | 120 + | 3,260 | 63092-48 |
| 2-SECTION, WITH HYDRAULIC FOLDING | | | | | | | |
| 4.00 | 3.75 | Square Tube Roller / 550 mm | ^{2*} - | 30 | 120 + | - | 63092-75 |
| 4.00 | 3.75 | Wave roller / 600 mm | ^{2*} 32 | 30 | 120 + | 3,320 | 63092-72 |
| 4.00 | 3.75 | V-Profile Roller / 600 mm | ^{2*} 26 | 30 | 120 + | 3,680 | 63092-65 |
| 5.00 | 4.75 | Square Tube Roller / 550 mm | ^{2*} - | 38 | 150 + | - | 63093-75 |
| 5.00 | 4.75 | Wave roller / 600 mm | ^{2*} 40 | 38 | 150 + | 3,850 | 63093-72 |
| 5.00 | 4.75 | V-Profile Roller / 600 mm | ^{2*} 32 | 38 | 150 + | 4,300 | 63093-65 |

^{1*}Requires 2 double-acting oil outlets.

^{2*}Requires 3 double-acting oil outlets.

STANDARD EQUIPMENT

- Mechanical adjustment of working depth on 1-section models.
- Hydr. adjustment of working depth on 2-section models.
- Adjustable drawbar height with parking device for hydraulic hoses.
- Edge equipment with disc for retain soil on right side.
- Scraper between the rings.
- 60 mm axles, fitted with 60 mm triple-sealed ball bearings on all models.
- Wheels:
 - 3.00-4.00 m 1-section: 11.5/80x 15.3 – 14 PLY.
 - 4.00-5.00 m 2-section: 400/60 x 15.5 – 16 PLY.
- Pivotal towing eye, secured by bolts: 3.00 – 5.00 m, item no.. 630757028.

EXTRA EQUIPMENT

| Work Width, m | Description | Weight, kg | Item Number |
|---------------|----------------------------------------------------------------------|------------|-------------|
| 2.50 - 4.00 | LED lights w/wire and socket, rigid models | 3 | 63091-01 |
| 4.00 - 5.00 | LED lights w/wire and socket, foldable models | 3 | 63092-01 |
| 3.00 - 4.00 | Hydr. adjustment of working depth and disc angle for rigid models | - | 63093-93 |
| 3.00 - 4.00 | Electrical depth stop for rigid models | 4 | 63091-85 |
| 4.00 - 5.00 | Electrical depth stop for hydraulic models | 8 | 63092-85 |
| 3.00 - 5.00 | Drawbar extension, 300 mm for bolting on | 25 | 63091-95 |
| 3.00 - 5.00 | Air brakes | 18 | 63093-96 |
| 3.00 - 5.00 | Hydraulic brakes | 7 | 63093-94 |
| 3.00 | Material damper guard | 60 | 63091-98 |
| 3.50 | Material damper guard | 70 | 63096-98 |
| 4.00 | Material damper guard | 80 | 63092-98 |
| 5.00 | Material damper guard | 100 | 63093-98 |
| 3.00 - 3.50 | Rubber sealed/non-lubricant ball bearings (Additional price per set) | - | 63090-02 |
| 4.00 - 5.00 | Rubber sealed/non-lubricant ball bearings (Additional price per set) | - | 63090-04 |
| - | Bearing protector for packing roller (Per unit) | 0.9 | 7355054 |
| - | Ø510 x 5 mm "Sabre discs" HD aggressive (Additional price per m) | 7.6 | 63090-10 |



| Work Width, m | Type / Description | Weight, kg | Item Number |
|--------------------------------------------------------------------|-------------------------------------------|------------|-------------|
| SPRING-BOARD | | | |
| 3.00 | Rigid 1-section 1 ^{1/2} * | 280 | 63391-00 |
| 3.50 | Rigid 1-section 1 ^{1/2} * | 325 | 63396-00 |
| 4.00 | Rigid 1-section 1 ^{1/2} * | 375 | 63592-00 |
| 4.00 | Hydraulic 2-section 1 ^{1/2} * | 375 | 63592-00 |
| 5.00 | Hydraulic 2-section 1 ^{1/2} * | 450 | 63593-00 |
| - | Edge equipment set for Spring-Board tines | | 63301-00 |
| SPRING-BOARD WITH SLICING PLATES | | | |
| 3.00 | Rigid 1-section 1 ^{1/2} * | - | 63791-00 |
| 3.50 | Rigid 1-section 1 ^{1/2} * | - | 63796-00 |
| 4.00 | Rigid 1-section 1 ^{1/2} * | - | 63892-00 |
| 4.00 | Hydraulic 2-section 1 ^{1/2} * | - | 63892-00 |
| 5.00 | Hydraulic 2-section 1 ^{1/2} * | - | 63893-00 |
| TRANSVERSE LOCKING SYSTEM - CONNECTS THE SPRING-BOARD TINES | | | |
| 3.00 | Rigid 1-section 1* | - | 63491-00 |
| 3.50 | Rigid 1-section 1* | - | 63496-00 |
| 4.00 | Rigid 1-section 1* | - | 63692-00 |
| 4.00 | Hydraulic 2-section 1* | - | 63692-00 |
| 5.00 | Hydraulic 2-section 1* | - | 63693-00 |

¹Requires 1 additional double-acting oil outlet.

²Drawbar extension is recommended, when the tractor is equipped with twin wheels.

SET OF PIVOTING SUPPORT WHEELS, MOUNTED IN FRONT, HEIGHT ADJUSTABLE WHEELS: 2 X 300/65X12- 8 PLY

| Work Width, m | Description | Weight, kg | Item Number |
|---------------|--------------------------------------|------------|-------------|
| 3.00 - 5.00 | For trailed models | 140 | 63091-07 |
| 3.00 - 5.00 | For trailed models with Spring-Board | 180 | 63091-08 |

MOUNTING SET FOR MULTI-SEEDER INCL. STEPS, INCL. HYDRAULIC LIFTING OF SEED WHEEL AND MOUNTING ON NEW DISC-ROLLER - MAX. 300 KG LOAD IN THE FINE SEED HOPPER. PRICES AND INFO ON MULTI-SEEDER

| Work Width, m | Type | Item Number 8 Outlets | Item Number 12 Outlets | Item Number 16 Outlets |
|---------------|-----------|--------------------------|---------------------------|---------------------------|
| 3.00 | Rigid | 63091-14 | - | - |
| 3.50 | Rigid | 63096-14 | - | - |
| 4.00 | Rigid | 63092-14 | 63092-27 | - |
| 4.00 - 5.00 | Hydraulic | 63092-18 | 63092-26 | 63092-19 |