

SUB-TILLER COMBI



- Intended as front tool / tool carrier for maize seed drills.
- Loosens the soil down to 40 cm depth in front of each crop row.
- Net weight of approx. 10 tons ensures extremely stabile depth control.
- Various possibilities for the composition of the machine.
- Possible to mount fertilizer equipment on sub soiler.

MACHINES

Work Width, m	Stone Protection	No. of Tines	Row Spacing	Item Number
6.00	Quick-Push	8	75	64535-00
6.00	Hydraulic	8	75	64535-01
6.00	Quick-Push	12	45	64535-02
6.00	Hydraulic	12	45	64535-03

For machines in special working widths, contact HE-VA.

STANDARD EQUIPMENT

- Standard fitted with 4-ton double-acting lift at the rear.
- Lift with cat. 3 snap-couplings and cat. 3 distance (1,010 mm middle - middle).
- Wheels: 710/40 R22.5.
- Hydr. support wheel 300x65/12 8 PLY, in front.
- Ball joint towing eye, cat. 4 / Ø51 mm, item no.. 7420006
- Hydr. depth control via the roller and support wheel.
- For Quick-push stone protection: 8 steps per bolt.
- Scraper between the rings.
- Points with 200 mm wing shares, mounted on 25 mm wide tine.
- Incl. 3 x double acting oil socket and extension cable t / light. 2 sets 1/4 and 1 set 3/8.

EXTRA EQUIPMENT

Description	Weight, kg	
LED lights cpl. with wire and socket, mounted	-	64500-05
Points with 120 mm wing shares (Price reduction per tine)	-	645000043A
Points 120 mm with hard metal plate (Additional price per tine)	-	645000043TA
Points with 350 mm wing shares (Additional price per tine)	-	645000063A
Points 200 mm with hard metal plate (Additional price per tine)	-	645000044TA
Easy-Draft kit. 15 mm tine w/120 mm wear point with hard metal plate. Max working depth: 300 mm. Quick-Push stone protection (Additional price per tine)	-	64509-12
Easy-Draft kit. 15 mm tine w/120 mm wear point with hard metal plate. Max working depth: 300 mm. Quick-Push stone protection (Retrofitting per tine)	90	64509-16
Easy-Draft kit. 15 mm tine w/120 mm wear point with hard metal plate. Max working depth: 300 mm. Hydraulic auto release (Additional price per tine)	-	64509-09
Easy-Draft kit. 15 mm tine w/120 mm wear point with hard metal plate. Max working depth: 300 mm. Hydraulic auto release (Retrofitting per tine)	125	64509-17
120 mm wear point for Easy-Draft, with hard metal plate in center + wings (Additional price per tine)	-	645000056TA
200 mm wear point for Easy-Draft, with hard metal plate in center (Additional price per tine)	-	645000054A
200 mm wear point for Easy-Draft, with hard metal plate in center + wings (Additional price per tine)	-	645000054TA
Air brakes, factory-mounted	18	64509-34
Hydraulic brakes, factory-mounted	7	64509-33
Discs for 6.00 m. (8 tines) - with Ø470 mm discs in front of tine, turnable and protected from stones via rubber suspension, maintenance free bearings (not for retrofitting)	-	64539-00
Discs for 6.00 m. (12 tines) - with Ø470 mm discs in front of tine, turnable and protected from stones via rubber suspension, maintenance free bearings (not for retrofitting)	-	64539-01
One extra set of double-acting hydraulic hoses 3/8", with female quick-acting coupling.	-	64539-20
A set of air brake outlets	-	64539-21