

FRONT-TANK



- Produced in materials that can handle fertilizer.
- With window and tarpaulin.
- With hydraulic driven fan. Requires 35 l/min from oil outlet with flow control and return to sump without pressure.
- Three-point linkage with category 2 pins and category 2 distance.

MACHINES

| Tank, L | Description | | Length, mm | Width, mm | Operating Height, mm | Item Number |
|---------|--|----|------------|-----------|----------------------|-------------|
| 1,100 | HE-VA Front-Tank Manual adjustment of the seed rate. | 2* | 1,440 | 2,210 | 1,900 | 0537500 |
| 1,100 | HE-VA Front-Tank ISOBUS (Speed signal is retrieved from tractor) | 1* | 1,440 | 2,210 | 1,900 | 0537610 |
| 1,600 | HE-VA Front-Tank Manual adjustment of the seed rate. | 2* | 1,440 | 2,210 | 2,100 | 0537581 |
| 1,600 | HE-VA Front-Tank ISOBUS (Speed signal is retrieved from tractor) | 1* | 1,440 | 2,210 | 2,100 | 0537582 |
| 2,000 | HE-VA Front-Tank Manual adjustment of the seed rate. | 2* | 1,440 | 2,210 | 2,200 | 0537611 |
| 2,000 | HE-VA Front-Tank ISOBUS (Speed signal is retrieved from tractor) | 1* | 1,440 | 2,210 | 2,200 | 0537612 |
| - | Distributor heads with different number of outlets, please request prices and delivery times. | - | - | - | - | - |
| - | Separate terminal for ISOBUS system on HE-VA Front-Tank | - | - | - | - | 0520373 |

¹Requires 1 double-acting oil outlet.

²Requires 2 double-acting oil outlets.

STANDARD EQUIPMENT

- Headlight with working light, tank light and direction indicator.
- Parking leg, loading platform and Cat. II three-point linkage.
- Hydraulic fan
- 5 m firm tube and 10 m flexible tube for tractor mounting.
- Only Front-Tank mechanical:
 - Seed wheel with hydraulic lifting.
- Only Front-Tank ISOBUS:
 - Electronic control of the seed rate, monitoring, test turning etc.
- Only for Sub-Tiller:
 - Factory mounting on a new Sub-Tiller when adding a mounting set.