

HE-VA

Front-Tiller

The Robust Front Harrow



HE-VA

Front-Tiller

The HE-VA Front-Tiller is a 2-row front harrow for working depths of up to 300 mm. The Front-Tiller can be used together with a seeding combination or in stubble fields, whereby optimal utilization of the tractor is achieved.



There are two types of tines to choose from:

The automatic tine with spring release for 560 kg...



... or the double-twisted spring tine 40x40 mm.

Both types are equipped with 50x25mm reversible wear points.



The robust pivot depth wheels (10.0/80x12) ensure reliable depth control.

Adjustment is easily done using spindles.

Extra Equipment

Warning Boards



LED Marking Lights



Edge Equipment



Revers. Wear Point 75x12



Revers. Wear Point 75x19



Tungsten Point



Goose Foot Point



Goose Foot P., Hardmetal



Technical Specifications



3.00 - 4.00 m



1,090 - 1,695 kg



9 - 13 pcs.

Working Width, m	Description	Number of Tines	Weight, kg
3.00	Front-Tiller with double coil springs or spring release	9	1,090 / 1,405
4.00	Front-Tiller with double coil springs or spring release	13	1,240 / 1,695



Tel.: +45 97 72 42 88
E-mail: info@he-va.com

Web: www.he-va.com

N.A. Christensensvej 34
DK-7900 Nykøbing Mors

Your HE-VA dealer

HE-VA reserves the right to make design and construction changes without notice

